

Index

- Accent lighting, 195–196, 200–201.
See also Lighting
- Accessible design
 - bathrooms, 219–223
 - bathubs, 221–222
 - cooking center layout, 217
 - counter heights, locations, 216
 - grab bars, 222–224
 - kitchen sink center, 216–217
 - kitchens, 215–217
 - knee space, 215, 220–221
 - lavatory layout, 220–221
 - lighting in kitchens, 217
 - pocket doors in baths, 219, 223
 - refrigerator work center, 217
 - roll-in shower, 221–222
 - storage areas, 216
 - toilet space, 221
 - wheelchair turning space, 215, 222–223
- Acid rain, and copper flashing, 7
- Acoustical sealant, 190, 193
- Acrylic
 - sealants, 40
 - sinks, 252–253
 - tubs and showers, 253, 255
- ACZA (ammoniacal copper zinc arsenate), 136–137, 147. *See also* Pressure-treated wood
- Adhesives
 - comparison chart, 41
 - drywall, 160–163
 - epoxy, 41
 - exterior, 40–42
 - lamine flooring, 179
 - low-VOC, 179
 - plastic moldings, 34–36, 185
 - polyurethane, 41
 - resilient flooring, 171
 - roofing tile, 69–70
 - yellow glue, 40–41
- Agglomerates, stone tile, 230–232, 239
- Air cleaners, 269, 277–281
 - applications, 269
 - comparison chart, 279
 - effectiveness and particle size, 278–281
 - effectiveness in real-world, 281
 - electronic, 278–280
 - gas removal, 278, 280
 - HEPA filters, 278–281, 282
 - mechanical filters, 278–279
 - negative-ion generators, 280
 - particles vs. gases, 277–278
 - portable, 281
 - radon removal, 278
 - turbulent flow precipitators, 280
- Air conditioning, biological pollutants from, 282, 289
- Air infiltration
 - effect of sheathing wraps, 3
 - effect on wall drying, 1
- Air leakage, window ratings, 104, 113, 117
- Air pollution, effect on flashings, 7, 82.
See also Indoor pollutants
- Air quality. *See* Indoor air quality
- Air space
 - under cedar shingles, 15
 - double-layer building paper, 4
 - draining housewraps, 4–5
 - in rain-screen wall, 2–3
 - reducing extractive bleeding, 5
 - under wood siding, 5, 10
 - between wood siding and foam, 3
- Air-to-air heat exchangers.
See Energy-recovery ventilators, Heat-recovery ventilators
- Algae
 - on low-slope roofing, 94
 - on metal roofing, 74
 - resistance to, asphalt shingles, 53
 - on wood roofing, 87, 93
 - See also* Mildew
- Aluminized steel, metal roofing, 82–83
- Aluminum
 - corrosion of, 137, 146
 - effects of salt spray, 7, 82, 84–85
 - exposed-fastener panels, 74–76
 - fascia details, 23
 - metal roofing, 82–83
 - modular shingles, 74, 80–81
 - moldable pipe flashing, 72, 77
 - siding nails, 11
 - standing-seam roofing, 78
 - wall flashing, 7
- Ambient lighting, 194–195, 197, 200–203.
See also Lighting
- American Architectural Manufacturers Association (AAMA), 107, 109–111
- Americast, bathtubs, 254–255
- Amowrap, permeance rating, 4
- ANSI, grab bar guidelines, 222–224
- Antiscald protection, 219, 258–259
- Arches, drywall, 163–164
- Architectural shingles, 52–53. *See also* Asphalt shingles
- Argon, gas fill for windows, 112
- Armacyrl, tubs and showers, 255
- Asbestos, 284, 292
 - in fiber-cement, 19
- ASHRAE
 - air cleaner standards, 279–280
 - formaldehyde standard, 288
 - ventilation standards, 269–271
- Asphalt felt
 - ASTM standard, 3–4
 - corner splines, 13
 - effect on wet siding, 2
 - interlayment for shakes, 88–90
 - properties, 2, 4
 - roofing underlayment, 54, 66–69
 - sealing around windows, 122
 - underlayment for sidewall shingles, 15
 - See also* Underlayment
- Asphalt roofing cement
 - incompatible with metal roofing, 84
 - incompatible with modified bitumen, 96
 - sealing shingles, 53, 57, 59–61
 - sealing tile roofing, 71–74
- Asphalt shingles
 - algae resistance 53
 - eaves flashing, 54–56
 - fastening, 58–59
 - flashing for, 59–61
 - high-wind installation, 58
 - installation 57–62
 - installation temperature, 57
 - laminated, 52–53
 - low-slope installation, 59
 - manual sealing, 57
 - offsets, 57
 - organic vs. fiberglass, 51–52
 - quality, 51
 - reroofing with, 62
 - steep-slope installations, 59
 - types, 51–52
 - underlayment for, 54–55
 - valleys, 59–61
 - warranties, 53–54
 - wind resistance, 53
- Asthma, and indoor air quality, 268–269, 282, 288–289, 293–294
- ASTM
 - asphalt felt standard, 4
 - asphalt shingle standards, 53
 - building paper standard, 3–5
 - galvanized steel standards, 141, 143
 - roofing tile standards, 63
 - sealant standards, 39
 - stainless-steel standards, 141, 143
- Awnings, shading with, 118–119
- Awning windows, 105
- Backdrafting, 270–272, 293–296
 - effects of range hoods, 263
 - effects of ventilation systems, 270, 273, 275
 - preventing, 293, 295–296
 - testing for, 296
- Backer rod, use in caulk joints, 38–39, 237
- Backerboard
 - cement, 232–239, 256
 - gypsum, 235
 - See also* Ceramic tile
- Back-priming
 - fiber-cement siding, 21
 - wood siding 5, 9–10, 45
- Balusters, fastening, 148, 150
- Bamboo floors, 175
- Band joist
 - connection to ledger, 144–146
 - flashing, 6, 145
 - stucco control joints at, 26

- Bark-side down, wood trim, 31
- Bath fans, 261–262
- balancing supply-only ventilation, 275
 - controls, 262,
 - ductwork, 262
 - fan sizing, 261
 - noise levels, 261
 - providing whole-house ventilation, 271
- Bathrooms
- accessible design, 219–223
 - antiscald protection, 219
 - bathub clearances, 218
 - design guidelines, 217–219
 - flooring comparison chart, 225–226
 - flooring options, 223, 225–226
 - GFCIs required in, 219
 - lavatory clearances, 217
 - lighting, 205–206, 219
 - mirror heights, 217
 - shower sizes, 217–218
 - toilet/bidet clearances, 219
 - tub steps safety, 218
 - typical layouts, 219–220
 - ventilation from HRV/ERV, 275–277
 - ventilation from multipoint exhaust, 271–272
 - venting with bath fans, 261–262
 - See also* Accessible design
- Bathroom ventilation, 261–262. *See also* Whole-house ventilation
- Bathtubs
- acrylic, 253, 255
 - enameled cast iron, 253–254
 - enameled steel, 253
 - fiberglass, 253–255
 - jetted, 255–257
 - lighting over, 206
 - material comparison chart, 254
 - mixing valves, 258–259
 - scald protection, 258–259
 - See also* Jetted tubs
- Battens
- metal roofing on, 76, 81, 87–89
 - tile roofing on, 67–69, 72
 - wood roofing on, 87–88
- Beams
- deck span chart, 148
 - post connections, 147
- Bedrooms
- carpeting for, 181–182
 - sound control recommended, 192–193, 195
- Biological pollutants, indoor, 282, 289
- Bisque, characteristics of tile, 227
- Bleaching
- corrosion from, 46
 - to remove mildew, 46
 - to remove moss and lichen, 93
- Bleaching oils
- applications, 47
 - finishing cedar shingles, 19
- Boat test, defined, 3
- Bond breakers, use with sealants, 38–39, 236–237
- Borate, preservative treatment, 137, 291
- Brick veneer
- water leakage in, 2
 - weep holes required, 2
- Building paper
- code requirements, 3
 - effect on wet cladding 2
 - used as drainage plane, 2
 - See also* Asphalt felt
- Built-up roofing (BUR), 87, 94–95
- Bullnose, drywall trim, 162–163
- Butyl flashing tapes
- compatibility with sealants, 6
 - vs. modified bitumen, 5
 - See also* Flashing types
- Butyl sealant
- characteristics, 38, 40
 - sealing metal roofs, 78, 80, 84
- Butyl tape, sealing metal roofs, 78, 80, 84
- Byrne, Michael, tile consultant, 237–238
- Cabinets. *See* Casework; Kitchen cabinets
- Callbacks
- avoiding on low-slope roofs, 54
 - ceramic tile, 227
 - rare with EPDM, 96
 - water-leakage related, 1
- Cambara, decking, 139, 142
- Capillary action, through siding, 1
- Capillary break
- in EIFS, 29
 - in rain screen, 2
 - from termite shields, 7
- Carbon monoxide, 290, 293–294, 295–296
- Carpet and Rug Institute (CRI), 182
- Carpeting
- comparison chart, 181
 - Green Tag program, 292
 - health effects, 183, 292
 - installation, 182
 - material choices, 180–181
 - padding types, 181–182
 - pollution source if wet, 289
 - sound control with, 189, 193
- Casement windows, 103–105, 107, 117
- Casework
- material options, 186
 - with MDF, MDO, 186
 - with particleboard, 186
 - shelving spans, 186
 - with veneer-core plywood, 186
- Cast iron. *See* Enameled cast iron
- Cast polymer
- composite sinks, 252, 253
 - countertops, 248–250
- Caulking
- acrylic latex, 40
 - bond breakers, 38–39, 237
 - comparison chart, 38
 - exterior trim, 36–37
 - failures cause leakage, 1
 - joint design, 37, 39
 - required by MEC, 3
 - types described, 37–40
 - windows and doors, 13
 - See also* Sealants
- CCA. *See* Chromated copper arsenate
- Cedar Breather, 87–88, 90–91
- Cedar Shake and Shingle Bureau, 15, 86, 92
- Cedar
- decking, 138–139, 142
 - degrading building paper, 2
 - degrading housewrap, 5
 - effects on copper flashing, 7, 92
 - extractive bleeding of, 10, 46
 - paintability of, 31
 - reaction with galvanized nails, 11, 13
 - roofing shakes, shingles, 85–86
 - siding shakes and shingles, 15–19
 - siding nails, 11, 17–18
 - siding, 9–14
 - unfinished shingles, 19, 47
 - unfinished siding and trim, 47
 - See also* Shakes; Wood shingles
- Cellular PVC, trim, 35–36
- Cement backerboard, for tile, 232–239, 243, 256
- Central vacuum systems, 269, 289, 292
- Ceramic coatings, for deck fasteners, 141
- Ceramic tile
- bisque characteristics, 227
 - over cement backerboard, 232–239, 256
 - comparison chart, 229–230
 - over concrete slabs, 235
 - countertop details, 233–235, 250
 - crack isolation, 237–238
 - over Dens-Shield, 235
 - over drywall, 235
 - over existing surfaces, 235
 - flooring pros and cons, 225
 - framing requirements, 232, 235
 - glazed vs. unglazed, 227–228
 - grouting, 241–242
 - over gypsum backerboard, 235
 - isolation membranes, 232, 237
 - leveling compounds, 235–236
 - medium-set installation, 240
 - mosaic, 228
 - pavers, 228–230
 - porcelain, 228–229
 - quarry tile, 229, 230–231
 - selecting tile, 227–231
 - setting compounds, 237–240
 - setting-compound comparison chart, 239
 - shower pans, 241–243
 - slip protection, 228
 - strength and water absorption, 227
 - subflooring requirements, 232
 - substrates for 232–236
 - thinset installation, 239–240
 - waterproofing membranes, 236, 242–243
 - wear ratings, PEI scale, 228
- Chandeliers. *See* Pendants
- China, sinks, 252, 253
- Chromated copper arsenate
- health concerns, 135–136
 - phase out, 135
- Clad windows, 105–107, 120
- aluminum, 107
 - fiberglass, 107
 - vinyl, 107
- Cladding
- leakage in, 1, 8–10, 12, 37
 - in rain screen, 2
 - See also* EIFS; Siding; Shakes; Stucco; Vinyl siding; Wood siding; Wood shingles
- Clear finishes
- exterior, 46–47
 - interior, 188–189
- Closet lighting, 203
- Color temperature, of common lamps, 199
- Color-rendering index. *See* CRI
- Combustion appliances, 293–296
- chimney problems, 295
 - fireplaces, 269, 272, 278, 293–296
 - health effects, 293–294
 - induced-draft, 295
 - power-vented, 29
 - sealed-combustion, 295
 - woodstoves, 269, 278, 293–296
- Compact fluorescents, 195, 197–199, 201–203, 206

- Composite decking, 138, 140–141
 - screws for, 141–142
- Concrete, substrate for flashing membranes, 6
- Concrete slabs
 - installing wood flooring on, 168–170
 - radiant heating with, 175
- Condensation, on windows, 117–118
- Connectors, for exterior decks, 141, 143, 147–149
- Control joints
 - EIFS, 29
 - concrete, 38
 - drywall, 161
 - polyurethane sealant for, 38, 40
 - tile crack isolation, 237–238
 - See also* Expansion joints
- Cooktops
 - accessible work center, 217
 - work center, 211–212
- Copper
 - corrosion from cedar, 7, 92
 - effects of salt spray, 84–85
 - metal roofing, 83
 - modular shingles, 80
 - standing-seam, 78
 - tile roof flashings, 72–73, 75
 - tile roofing nails, 68
 - twisted wires, 69–70
 - use in algae-resistant shingles, 53
 - use to protect wood roofing, 93
 - wall flashing, 7
- Copper azole (CBA-A, CA-B), 135–137, 139–141, 146. *See also* Pressure-treated wood
- Copper nails
 - staining wood siding, 11
 - for tile roofs, 68
- Copper naphthenate, 94
- Copper octoate, 94
- Copper quat (ACQ), 135–137, 139, 141, 146–147. *See also* Pressure-treated wood
- Cork flooring, 177–179, 226
 - in kitchens and baths, 226
- Corner boards
 - fiber cement, 34
 - LVL, 33
 - PVC, 35
 - rain-screen type, 37
 - for vinyl siding, 24
 - wood siding, 8, 13
- Corners
 - shake and wood shingle, 17–18
 - vinyl siding, 24
 - wall flashing for, 8, 13
- Corrosion
 - and wood preservatives, 137, 141, 143, 146
 - of copper flashing, 7, 92
 - of metal roofing, 76, 79, 83, 84
- Countertops
 - accessible, 216
 - cast polymer, 248–250
 - ceramic tile, 250
 - comparison chart, 249
 - cultured marble, 248–250
 - design guidelines, 210–212, 248
 - for eating areas, 212–213
 - engineered stone, 250
 - high-pressure laminate, 248
 - material options, 247–248
 - natural stone, 250
 - solid surfacing, 250
 - stain-resistance of, 248
 - substrate for tile, 233–235
- Cove lighting, 201
- Crack isolation, ceramic tile joints, 237–238
- CRI
 - of fluorescents, 198, 203
 - rating explained, 200
- Cultured marble
 - countertops, 248–250
 - sinks, 252–253
- Cunapsol, on wood roofing, 94
- Cupping
 - of flat-sawn lumber, 31
 - resistance to, 32
- Cuprinol Clear Wood Preservative, 45
- Cutting
 - fiber-cement, 20–21
 - interior doors, 187
 - metal roofing, 76, 82
- Dap Woodlife, 45
- Decay resistance
 - of cedar, 9, 138–139
 - of cypress, 9,
 - of decking material, 138–140
 - of redwood, 9, 138–139
 - of tropical hardwoods, 139–140
 - wood species chart, 31, 47
 - of younger, smaller trees, 30
- Decking
 - composite, 138, 140–141
 - decay-resistant wood, 138–140
 - fastener schedule, 142
 - finishes for, 154–155
 - hardwood, 138, 139–140
 - hidden fasteners for, 142–143
 - porch floor, 151
 - pressure-treated, 138–139
 - for rooftop decks, 151
 - vinyl and plastic, 138, 140–141
 - See also* Decks
- Deckmaster deck fasteners, 143
- Decks, 135–151, 153–155
 - bracing for, 147
 - decking comparison chart, 138
 - decking materials, 137–141
 - framing materials, 135–137, 138
 - freestanding, 146
 - ledger connections, 144–146
 - ledger flashing, 8, 145–146
 - lumber comparison chart, 136
 - plastic lumber for, 137
 - posts and beams for, 146–147
 - railings for, 147–150
 - rooftop, 150–151
 - span charts, 148
 - structural connectors, 143–144
 - See also* Decking; Porches
- Dehumidifiers, source of biological pollution, 282, 289
- Dens-Shield, 235
- Diagonal wood siding, 9–10
- Doors
 - drywall trim, 163
 - flashing tapes for, 5
 - vinyl siding trim, 23
 - See also* Interior doors; Exterior doors
- DOP, HEPA filter rating, 280
- Double nailing
 - of fiber-cement, 20
 - of wood siding, 12
- Douglas fir
 - extractive bleeding of, 46
 - decay resistance of, 47
 - pressure treated, 135–138, 148
 - paintability, 45
- Downlights, 195, 197, 200, 204–205. *See also* Recessed lights
- Drain, clamping-type in shower pan, 242–243
- Drainage EIFS, 28–29. *See also* EIFS
- Drainage plane
 - in rain screen, 2
 - behind stucco, 24–25
 - behind wood siding, 10
- Draining housewraps
 - characteristics, 5
 - with shakes and shingles, 15
 - under trim, 37
 - See also* HomeSlicker
- Drawers
 - construction of, 248
 - slides for, 248
- Drip edge
 - with eaves membranes, 55–57
 - placement when reroofing, 62
 - shingle overhang at, 56
 - with underlayment, 54, 56
- Dry-set mortar, for ceramic tile, 238
- Drywall, 159–163
 - adhesives for, 160–161
 - arches, 163–164
 - corner bead, 161
 - curves in, 161–162
 - fasteners, 160–161
 - fire-resistant, 159
 - floating corners, 161
 - framing for, 160–161
 - installation, 160–162
 - moisture-resistant, 159
 - specialty trims, 162–163
 - substrate for ceramic tile, 235
 - taping and finishing, 162
 - trimming windows, doors with, 163
- Ductwork
 - cleaning, 289
 - sealing from radon entry, 287
 - sizing for bath fans, 262
 - sizing for range hoods, 263
- Duradek, 96–97
- Dust mites, 278, 282, 289, 292
- Dust-spot efficiency, of air cleaners, 279–280
- Eaves flashing
 - installation, 54, 56
 - low-slopes, 54–55
 - at skylights, 56, 126–127
 - for wood roofing, 89
- Eb-Ty deck fasteners, 143
- EIFS
 - drainage type, 28–29
 - failures in barrier type, 28–29
- Electronic air cleaners, 278–280. *See also* Air cleaners
- Enameled cast iron
 - bathtubs, 253–254
 - sinks, 252–253
- Enameled steel
 - bathtubs, 253–254
 - sinks, 252
- End grain, sealing at corners, joints, 8, 13–14, 31, 37, 45

- Energy efficiency
 - effect of roof color, 98
 - of exterior doors, 129–130
 - of metal roofing, 74, 85
 - of skylights, 125–126
 - of tile roofing, 62, 74, 81, 85, 98
 - of windows, 112–119
- Energy Star
 - window labels, 112
 - window recommendations, 113–115
- Energy-recovery ventilators, 270, 275–277
 - controls, 275
 - cost-effectiveness, 276–277
 - ducting, 275–276
 - maintenance, 276
- Engineered stone, countertops, 249–250
- Engineered wood floors, 172–176
 - floating, 173–174
 - glueless, 174
 - installation, 173
 - in kitchens and baths, 226
 - materials, 173
 - over radiant heat, 172–174, 175–176
- EPA TEAM study, 267, 290
- EPDM
 - foot traffic on, 96
 - roofing, 96
 - for rooftop decks, 150–151
 - weatherstripping, 130
- Epoxy
 - adhesive, 42
 - deck fastener coatings, 141
 - mortar and grout, 238–239, 241
- ERVs. *See* Energy-recovery ventilators
- Exhaust-only ventilation, 271–272
 - heat-pump water heaters, 272
 - multi-port, 270–272
 - single-port, 270, 271
- Expansion joints
 - ceramic tile, 236–237
 - stucco, 26
 - See also* Control joints
- Exterior doors, 127–131
 - comparison chart, 128
 - composite, 129
 - energy efficiency of, 129–130
 - fiberglass, 129
 - flashing, 130–131
 - frames, 129
 - pan flashing, 130–131
 - steel, 128–129
 - sweeps, 130
 - weatherstripping, 130
 - wood, 128
- Exterior Insulation and Finish System.
 - See* EIFS
- Exterior trim
 - cellular PVC, 35–36
 - fiber-cement, 34
 - finger-jointed, 31–32
 - hardboard, 32–33
 - installation, 36–37
 - laminated-veneer lumber, 33–34
 - material comparison chart, 30
 - polymer, 34
 - preprimed, 45
 - rain-screen installation, 36–37
 - solid wood, 29–31
 - unfinished, 47
 - wood, solid, 29–31
 - wood with vinyl siding, 24
- Extractive bleeding, 5, 10, 46, 94
- Fading
 - effect of shading, 118–119
 - from skylights, 123
 - UV light effect, 114, 117
 - of vinyl cladding, 107, 109
 - of vinyl siding, 21
- Fascia, aluminum trim for, 23
- Fasteners
 - ceramic coated, 141
 - drywall, 160–161
 - exposed metal roofing, 76
 - for exterior decks, 141–144
 - hidden deck, 142–143
 - wood siding, 11–12
 - See also* Nails; Screws; Connectors
- Faucets, 257–258
 - materials, 257
 - scald protection, 258–259
 - valve types, 257–258
- Felt paper. *See* Asphalt felt; Building paper; Sheathing wrap
- Fiber-cement roofing, 65–66
- Fiber-cement siding, 19–21
 - blind nailing, 21
 - cutting, 20–21
 - finishing, 21
 - standard nailing, 20
- Fiber-cement trim, 34
- Fiberglass duct board, to reduce noise, 194
- Fiberglass insulation, as soundproofing, 193
- Fiberglass shingles, 51–52. *See also* Asphalt shingles
- Fiberglass tubs and showers, 253–255
- Fiberglass windows
 - clad, 107
 - pultruded, 109–110
- Finger-jointed trim, 31–32
- Finishes
 - clear exterior, 46–47
 - clear interior, 188–189
 - comparison charts, 43, 155
 - for decks, 154–155
 - for siding and trim, 42–44
 - for wood flooring, 171–172
 - See also* Finishing; Paints; Painting; Stains
- Finishing
 - exterior decking, 154–155
 - exterior siding and trim, 42–47
 - interior stains and dyes, 188
 - interior trim, 188–189
 - open-grain wood, 188
 - pressure-treated wood, 45–46
 - unfinished shingles, 19, 47
 - unfinished siding and trim, 47
 - wood flooring, 169–172
 - See also* Finishes; Painting; Stains
- Fire ratings
 - asphalt shingles, 51–52
 - fiber-cement roofing, 65
 - fiberglass shingles, 53
 - metal roofing, 74, 80, 82
 - roofing tile, 62–63
 - roofing underlayment, 54, 81, 82
 - treated wood shingles, 86
 - vinyl siding, 21
- Fireplaces, and backdrafting, 269, 272, 278, 293–296
- Fire-retardant treatment, of wood shingles
 - 86, 94
- Flange-type windows
 - flashing, 120–122
 - installation, 109
- Flashing
 - asphalt shingles, 59
 - clearance to wood shingles, 17
 - clearance to wood trim, 31
 - deck ledgers, 8, 145–146
 - exterior doors, 130–131
 - integrating with housewrap, 2
 - metal roofing, 76–77, 80
 - skylights, 56, 92–93, 126–127
 - tile roofs, 72–73, 75
 - valley lining, 59–61, 72–73, 75, 76–77, 82
 - wall corners, 8, 13
 - walls, 6–9
 - window pans, 120–121
 - windows with brickmold, 122–123
 - windows, flange-type, 120–122
 - wood roofs, 89, 92–93
 - See also* Roof flashing; Valley flashing; Wall flashing
- Flashing membranes
 - compatibility, 6
 - door pan flashing, 111
 - as eaves flashing, 54, 56
 - installation, 6
 - modified bitumen vs. butyl, 5
 - preventing galvanic corrosion, 84
 - properties, 5–6
 - protecting from splashback, 6
 - roofing trouble spots, 66
 - around skylights, 126–127
 - substrates for, 6
 - valley lining, 59–61, 75, 77
 - window pan flashing, 120–122
 - See also* Flashing; Flashing tapes
- Flashing tapes
 - modalable, 5, 120–122
 - properties, 5
 - protecting deck joists with, 142
 - sealing windows and doors with, 13, 120–122
- Flat roofs. *See* Low-slope roofing
- Flexible flashings. *See* Flashing membranes; Modalable flashing
- Flexwrap, 5, 122. *See also* Flashing tapes; Modalable flashing
- Floating corners, drywall, 161
- Floating floors
 - laminated, 179–180
 - wood, 173–174
- Flooring
 - K&B options, 223, 225–226
 - See also* Carpeting; Ceramic tile; Laminated flooring; Resilient Flooring; Stone; Wood floors
- Fluorescent lamps
 - characteristics, 198
 - ballasts for, 195
 - color temperature, 199–200
 - compact, 198
 - dimming, 198
 - efficacy of, 196–197
 - equivalency to incandescent, 197
 - recommended levels, 196–197, 203–205
 - uses, 199–205
- Fluoropolymer paints, 85
- Foam sheathing
 - and EIFS, 28–29
 - and rain-screen walls, 2–3
 - under wood siding, 2–3, 10

- Foot traffic
 on EPDM, 96
 on metal roofs, 74, 81
 on modified bitumen, 95–96
 on tile roofs, 64, 73
 walkable membranes, 96–97
- Formaldehyde, 171, 184, 186, 268–269, 280, 282, 287–289, 292
 in acid-cure urethanes, 171
 control strategies, 269, 282, 288–289
 exposure limits, 288
 filtering of, 280
 health effects, 268, 282, 288
 insulation ban, 287
 in MDF, 184, 186
 and moisture, 269
 in particleboard, 186
 in plywood, 186
 sealing strategies, 269
 sources of, 282, 287–288
- Framing
 for ceramic tile, 232, 235
 for drywall, 160–161
 exterior decks, 135–137, 143–147
 for toilets, 260–261
- FRP, tubs and showers, 255
- Furring strips
 under cedar shingles, 15
 in rain screen, 2
- Galvalume
 metal roofing, 75, 78, 83–84
 properties, 82–83
- Galvanic corrosion
 area effect, 84
 of metal roofing, 79, 82–84
 of valley flashing, 61
- Galvanic scale, 83–84
- Galvanized nails
 for asphalt shingles, 58
 for shakes and shingles, 17, 89
 staining wood siding, 11, 13
 for tile roofs, 67–68
- Galvanized steel
 ASTM standards 141, 143
 corrosion of, 84
 deck connectors, 141, 143
 flashing, 72, 75, 92
 metal roofing, 75, 82
 reaction with stainless steel, 141
See also Galvanic corrosion
- GFCEs
 in bathrooms, 219
 for jetted tubs, 256
 in kitchens, 213
- Girders. *See* Beams
- Glare, from skylights and windows, 117–119, 124–125
- Grab bars, guidelines, 222–224
- Grade D building paper
 properties, 4
 and stucco, 4, 24–25
- Granite
 countertops, 249–250
 flooring, 226, 230–232
- Grout
 ceramic tile installation, 241–242
 sealers for, 241
 types for ceramic tile, 241
- Gyp-Crete, radiant heating with, 175
- Gypsum backerboard, 235
- Halogen lamps, 198
- Hardboard
 paintability, 32
 trim material, 32–33
 water damage, 32–33
- Hardibacker, 233
- Hardwood
 exterior decking, 138–140
 flooring, 164–167
 interior trim, 183
 properties comparison chart, 184
- Health effects
 asbestos, 284, 292
 biological pollutants, 282, 289
 carpeting, 183
 formaldehyde, 268, 282, 288
 indoor air, 268, 281–285
 lead, 284, 291
 pesticides, 283, 291
 pressure-treated wood, 135–136
 radon, 268, 282, 285
 VOCs, 283, 290
See also Indoor air quality
- Healthy house. *See* Indoor air quality
- Heat-pump water heaters, for ventilation, 272
- Heat-recovery ventilators, 270, 275–277
 controls, 275
 cost-effectiveness, 276–277
 defrost cycle, 277
 ducting, 275–276
 maintenance, 276
See also Energy-recovery ventilators
- Hem-fir, pressure treated, 135–136, 138, 142, 148
- HEPA filters, 278–281, 282
- HEPA vacuums, 269, 281, 289, 292
- Hinges, cabinet 245–247
- Hips
 and roof ventilation, 99–100
 wood roofing detail, 92
- HomeSlicker, 5, 8, 10, 15, 37
 underlayment for shakes, shingles, 15
 use under trim, 37
- Hook Nail, tile attachment, 69
- Hopper windows, 105
- Hot roofs, 98
- Housewrap. *See* Building paper; Plastic housewrap; Sheathing wrap
- HRVs. *See* Heat-recovery ventilators, Energy recovery ventilators
- Hurricane Andrew, and window codes, 111
- Hurricane clips, in roofing tile installation, 69–70
- Hylar metal roof coating, 82, 85
- Hypalon roofing, 96
- Ice dams
 eaves flashing and, 54, 56
 preventing, 97–98
 around skylights, 56, 126–127
 tile roof battens and, 67–68
- Indirect lighting, 195, 197–198, 201, 203–204, 206
- Indoor air quality, 267–296
 acceptable risk, 267–268
 air cleaning, 269
 common pollutant sources, 281–296
 compared to outdoor air, 267
 control strategies, 268–269
 health effects, 268, 281–285
 source control, 268–269
 spot ventilation, 269 (*see also* Bath fans; Range hoods)
- whole-house ventilation, 270–277
See also Indoor pollutants; Ventilation;
 Whole-house ventilation
- Indoor pollutants, 281–296
 combustion by products, 293–294
 common hazards chart, 282–284
 formaldehyde, 171, 184, 186, 268–269, 280, 282, 287–289, 292
 mold, 268–269, 276–279, 281, 282, 289
 radon, 268, 270–272, 278, 282, 284–287
 source control, 268–269
See also Asbestos; Biological pollutants;
 Carpeting; Combustion appliances;
 Formaldehyde; Lead; Pesticides; Radon;
 Tobacco smoke; VOCs
- Infiltration. *See* Air infiltration
- Insects
 screening weep holes against, 2, 37
 termites, 7
 and unfinished siding, 67
- Insulation
 effect on ice dams, 98
 effect on wall drying, 1
 in hot roofs, 98
 rigid foam, 2–3, 10, 28–29
 and roof ventilation, 99–100
- Interior doors
 cutting and trimming, 187
 flush and molded, 186–187
 frame-and-panel, 186
 WDMA standards, 187
- Interior trim
 casework, 186
 finger-jointed, 183–184
 finishing, 188
 flexible polyester, 185–186
 hardwood comparison chart, 184
 hardwood, 183–184
 MDF, 184, 186
 paint-grade, 183–184
 polyurethane foam, 185
- International Building Code
 and water-resistive barriers, 3
 and wood siding, 11
- International Residential Code
 bathroom venting, 261
 coastal provisions, 111
 guardrails, 147
 kitchen venting, 263
 roof ventilation, 97
 stucco requirement, 25, 27
 water resistive barriers, 1
 wood roofing, 92
- Ipe, decking, 139, 142
- Islands
 cooktop counters, 211–212
 lighting of, 204–205
 sink counters, 212
 typical layouts, 214–215
- Isolation membranes, for tile, 232, 237
- J-channel, vinyl siding, 22–24
- Jetted tubs, 255–257
 heaters for, 256
 installation, 256–257
 jet types, 255–256
 noise, 255
- Joint compound, 160–163
 patching veneer plaster with, 164
- Junckers, hardwood flooring, 174

- Kenny, Russell, consultant, 29
- Kitchen cabinets
 doors and drawer fronts, 246
 drawers and slides, 248
 finish options, 244–245, 246
 framed vs. frameless, 245–246
 frontage recommendations, 210–211
 grades, 244
 hinges, 247
 material options, 244
 stock vs. custom, 244
- Kitchens
 accessible design, 215–217
 countertop recommendations, 210–212
 design guidelines, 209–215
 eating areas, 212–213
 flooring comparison chart, 225–226
 flooring options, 223, 225–226
 island layouts, 211–212, 214–215
 lighting, 203–205, 217
 natural lighting, 213–214
 typical layouts, 214–215
 undercabinet lighting, 195, 197–198, 204–205
- Kitchen tables, seating, 213
- Kitchen ventilation. *See* Range hoods;
 Whole-house ventilation
- Knee space, accessible, 215, 219, 221
- Kraft paper. *See* Grade D building paper
- Kraton
 sealant in shower pan, 242
 sealants, 39
- Krypton, gas fill for windows, 112
- Kynar, metal roof coating, 82, 85
- Laminate flooring, 179, 226
 in bathrooms, 179
 with radiant heating, 179
- Laminate
 high-pressure, cabinets, 244
 high-pressure, countertops, 248
 low-pressure, cabinets, 244
- Laminated shingles, 51–52, 58. *See also*
 Asphalt shingles
- Laminated-veneer lumber, trim, 33–34
- Lamp types, 197–198, 201–202
- Latex paint
 application, 44–45
 on cedar shingles, 19
 expected service life, 43
 on fiber-cement, 21
 vs. oil, 44
 sprayed on ceilings, 160
- Latex-modified thinset, for tile, 227–228, 231,
 233, 238, 234–240
- Lauan
 finishing characteristics, 32
 underlayment for resilient flooring, 177–178
- Lavatories
 accessible, 220–221
 clearances for, 217
- Lawsuits, water-leakage related, 1
- Lead
 health effects, 284, 291
 wall flashing, 7
- Lead-based paint, 291–292
- Lead-coated copper, 7
- Leakage. *See* Air infiltration; Air leakage;
 Water leakage
- Ledgers, for exterior decks, 8, 143–146.
See also Decks
- Leveling compounds
 for ceramic tile, 235–236
 for wood floors over concrete, 169
- Light tubes, 123–124
- Lighting, 194–206
 accent, 195
 ambient, 194–195, 203
 bathroom, 205–206, 219
 brackets, 201
 closet, 203
 color temperature, 199–200
 color-rendering index (CRI), 200
 cove, 201
 direct, 200–201
 fixtures (*see* Lighting, luminaires)
 glossary of terms, 195–196
 indirect, 201
 kitchen, 203–205, 213–214, 217
 lamp types, 197–198
 low-voltage, 198–199, 201–202, 204
 luminaires, 200–201
 pendants and chandeliers, 200, 204–205
 recessed, 196, 201–205
 recommended levels, 196–197, 203–205
 task, 195, 204
 track 196, 201–203
 undercabinet, 195, 197–198, 204–205
 wall sconces, 200
 wall washing, 195, 197, 200, 202, 204
See also Recessed lighting; Track lighting
- Limestone, flooring, 231
- Linoleum, 179
- Low-E glass, 112, 114–118, 125
 choosing by climate type, 115–116
 spectrally selective, 115–118, 123, 125
- Low-slope roofing, 94–96
 asphalt shingles, 59
 BUR, 95
 comparison chart, 95
 EPDM, 96
 metal, 74
 modified bitumen, 95–96
 roll roofing, 94
 skylight installation, 127
 tile, 66–68
 underlayment, 54–55
 walkable, 96–97
 wood roofing, 86–87
- Low-voltage lighting, 198–199, 201–202, 204
- Lumber
 for deck structures, 135–137
 plastic alternatives, 137
See also Pressure-treated wood
- LVL. *See* Laminated-veneer lumber
- Mahogany
 decking, 139
 flooring, 166
- Marble
 countertops, 226, 229–231, 239
 flooring, 229, 231, 248, 250
- Mastic
 for ceramic tile, 227, 237–240
 for ducts, 262, 287
- MDF, for casework, 184–187, 244
- MDO, for casework, 186
- Medex, formaldehyde-free MDF, 184
- Melamine
 finish on cabinets, 186, 244–246
 in high-pressure laminate, 179, 244, 248
- MERV, air cleaner rating, 280–281
- Metal lath, under stucco, 26
- Metal roofing, 74–85
 comparison chart, 83
 cutting 76, 82
 exposed-fastener, 74–78
 foot traffic, 74, 81
 flashing, 76–77, 80
 galvanic corrosion, 76, 79, 83–84
 galvanized steel, 82
 incompatible materials, 84–85
 installed on battens, 76, 81, 87–89
 metal choices, 81–83
 modular shingles, 80–81
 paints and coatings, 85
 panel movement, 75–76, 78–80
 slope requirements, 74
 standing-seam, 78–80
- Metal shingles. *See* Metal roofing; Modular
 metal shingles
- Miami-Dade County, window standards, 111
- Mildew
 on composite decking, 140
 health effects, 282
 on metal roofing, 74
 moisture levels and, 269, 289
 oil-based paint and, 44
 removal before painting, 46–47
 on unfinished wood, 47
 on wood roofing, 87, 93
See also Algae
- Mildewcide, in wood sealers, 45
- Mirrors
 height, 217
 lighting at, 205–206
- Mixing valves, 258–259. *See also* Scald
 protection
- Model Energy Code
 sheathing wrap requirements, 3
 and whole-house ventilation, 269
- Modified bitumen
 flashing membranes, 5
 flashing tapes, 5
 roofing, 95–96
- Modular metal shingles, 80–82
- Moisture
 biological pollutants and, 269, 289
 effect of HRVs and ERVs on, 277
 effect on formaldehyde, 269
 spot ventilation of, 269
See also Bath fans; Range hoods
- Moisture content
 and painting, 42
 of radiant slabs, 175
 of wood flooring, 167–168
 of wood siding, 9
- Moisture-cured urethanes, 171–172
- Mold
 and air cleaning, 277–279, 281
 causes, 269, 282, 289
 health effects, 268, 282, 289
 in HRVs, 276
- Moldable flashing, 5, 121–122, 126–127
- Moldings
 flexible polyester, 185–186
 urethane foam, 185
- Mothballs, and air quality, 291
- Nailing
 asphalt shingles, 58–59
 drywall, 160–161

- exterior decking, 141–142
- fiber cement siding, 20
- shake and shingle siding, 17–18
- tile roofs, 68–69
- underlayment for resilient flooring, 177–178
- vinyl siding, 22
- wood floors, 169–170
- wood roofing, 89, 91
- wood siding 11–12
- Nails
 - aluminum, 11, 17, 23, 89
 - for drywall, 160–161
 - galvanized and redwood, 11, 13
 - for shakes and shingles, 17, 89
 - stainless steel, 11, 13, 17, 20, 23, 36, 68, 89
 - stains from copper, 11
 - for wood siding, 11
- National Fenestration Rating Council (NFRC) 112–113
- Negative ion generators, 280
- Net free vent area, 97
- Nitrogen dioxide, 293–295
- Nose clips, for roofing tiles, 69–70
- Oil-based paint, 43–45
 - vs. latex, 44
 - mildew growth on, 44
- Oil-based primers, 44
 - on cedar shingles, 19, 44
- Oil-based stains, 19, 46, 94
- Oriented-strand board
 - EPDM substrate, 96, 150
 - flashing membrane substrate, 6
 - nail base for siding, 11
 - wood flooring substrate, 168
- OSB. *See* Oriented-strand board
- OSHA, formaldehyde standard, 288
- Paint
 - application, 44–45
 - for decking, 154–155
 - effect of air barrier, 2
 - expected service life, 43
 - failures over foam sheathing, 2, 10
 - finish for cabinets, 245
 - interior trim substrates for, 183–186
 - latex, 21, 43–45
 - latex vs. oil, 44
 - lead-based, 284, 291–292
 - for metal roofing, 85
 - oil-based, 19, 43–45
 - reflective, 81, 85
 - vs. stain, comparison chart, 43
- Paintability, by wood species, 30–32
- Painting
 - fiber-cement siding, 21–22
 - finger-jointed trim, 31–32
 - hardboard trim, 32
 - polymer trim, 35
 - pressure-treated wood, 45
 - rough vs. smooth side, 42–43
 - sealing and priming, 44–45
 - weathered wood, 43
 - wood species and, 43–44
 - wood trim, 30–31
- Pan flashing
 - at doors, 130–131
 - at windows, 120–121
- Panelized shingles, 18
- Particleboard, for casework, 186, 255
- Passive air inlets, 270–273
- Passive solar design
 - fixed overhangs, 119
 - selecting glazing, 112, 114–116, 118
 - shading, 118–119
- Passive vents, for radon removal, 286–287
- Peel-and-stick membranes. *See* Flashing membranes
- Pendants, lighting over tables, 200, 204–205
- Penetrating oil, floor finish, 170–172
- Penofin, decking finish, 139, 154
- Permeance
 - of asphalt felt, 4
 - of plastic housewrap, 4–5
 - of plywood, 3
 - of sheathing wraps, 3
- Pesticides, 290–291
- Pets, and indoor air, 289
- Pine, as siding material, 9, 31–32, 43–45, 47
- Plaster, veneer, 163–164
- Plastic decking, 140–141
- Plastic housewrap
 - bonding to flashing tape, 6
 - damage from extractives, 5
 - drainage plane, 2
 - draining type, 5, 15, 37
 - nonperforated, 5
 - performance, 2–5
 - sealing around doors, 130–131
 - sealing around windows, 120–122
 - use with stucco, 25
 - water resistance of, 3
 - See also* Draining housewraps
- Plastic lumber, 137
- Plumbing
 - faucets, 257–258
 - jetted tubs, 256
 - reducing noise, 193
 - scald protection, 258–259
 - sinks, 251–253
 - toilets, 259–261
- Plywood siding, 10–14
 - finishing, 43, 45–46
 - horizontal joints, 14
 - nailing for, 13
- Pocket doors, in accessible baths, 219, 223
- Pollutants. *See* Indoor pollutants
- Polyurethane
 - adhesives, 42
 - floor finish, 170–172
 - sealants, 40
 - See also* Urethane
- Porches, 151–153
 - covered, screened, 151–153
 - flashing ledger, 8, 145–146
 - See also* Decks
- Posts
 - connection to beam, 147
 - for exterior decks, 146–147
 - as railing supports, 147
- Preservative treatment
 - borate, 137
 - CCA phase-out, 135–136
 - wood roofing, 93–94
 - See also* Pressure-treated wood; Water-repellant preservatives
- Pressure-balancing valves, 258
- Pressure-treated wood
 - and corrosion, 137, 141, 143, 146
 - decking, 138–139
 - finishing, 45–46
 - health effects, 136–137
 - retention levels, 137
 - shakes and shingles, 86
 - See also* ACZA; Copper azole; Copper quat; Preservative treatment
- Primers
 - back-priming, 5, 9–10, 21, 45
 - oil-based, 19, 44
 - for siding, 44–45
 - stain blocking, 44–46
- PVC
 - cellular, 35–36
 - compatibility with flashing tapes, 6
 - window material, 108
- Q-Lon weatherstripping, 130
- Radiant barriers, 98
- Radiant heating
 - with engineered wood floors, 172–174, 175–176
 - panel systems, 175
 - staple-up systems, 175
 - subfloor over, 169–170
 - suitability of floor coverings, 225–226
 - thin slab method, 175–176
 - wood flooring over, 175–176
- Radon, 285–287
 - effect of air cleaners, 278
 - effects of ventilation systems, 270–272
 - health effects, 268, 282, 285
 - measuring, 285
 - remediation, 285–287
 - and tobacco smoke, 285
- Railings, 147–151
 - code requirements, 147
 - manufactured, 147, 150
 - post connections, 147–149
 - for rooftop decks, 96–97, 151
 - wood, details, 148–150
- Rain screen
 - defined, 2
 - double layer felt paper, 4
 - trim detail, 36–37
 - wood siding performance and, 10
- Raindrop Housewrap, 5
- Range hoods, 262–263
 - downdraft fans, 263
 - duct sizing, 263
 - effect on backdrafting, 263
 - fan sizing, 263
 - island hoods, 27
 - noise levels, 263
 - optimal location, 211–212
- Recessed lighting, 201–205
 - insulation contact, 201
 - in kitchens, 203–205
 - recommended levels/placement, 197, 203–205
 - spacing, 202
 - trims, 201–203
 - typical performance, 202, 205
 - See also* Lighting
- Redwood
 - copper flashing and, 7
 - damage to housewrap from, 2, 5
 - decay resistance, 137
 - decking, 138–139, 142
 - extractive bleeding, 10, 46

- Redwood (*Continued*)
 nails for, 11, 13
 paintability, 31
 siding, 9
 unfinished trim, 47
- Refrigerators
 accessible work center, 217
 work center, 212–213
- Relative humidity, effect on wood flooring,
 164, 167–168
- Reroofing
 with asphalt shingles, 62
 metal over asphalt, 76, 80
 wood shakes and shingles, 91
- Resilient channel
 drywall fastening schedule, 161
 installation, 193
 sound isolation strategy, 190
 STC, IIC ratings, 191–194
- Resilient flooring
 cork, 177–179, 226
 installation, 177
 linoleum, 179, 226
 sheet vinyl, 176, 225
 solid vinyl tile, 176–177, 225
 underlayment requirements,
 177–178
- Respirable particles, 277–280
- Ridge vents
 attic ventilation, 98–99
 metal roofing, 76–77
 wood roofing, 90, 92
- Rigid foam. *See* Foam sheathing
- Rigid thermofoil (RTF), cabinets, 245
- Roll roofing, 94
- Roof flashing
 asphalt shingles, 59–61
 membrane for trouble spots, 66
 membrane valley lining,
 59–61, 75, 77
 metal roofing, 76–77, 80
 skylights, 56, 92, 126–127
 tile roofs, 72–73, 75
 valleys, 59–61, 72–73, 75, 76–77, 82
 wood roofs, 89, 92–93
See also Eaves flashing; Valleys
- Roof ventilation, 97–100
 cathedral ceilings, 99–100
 code requirements, 97
 around skylights, 100
- Roofing
 asphalt shingles, 51–62
 low-slope, 94–97
 metal, 74–85
 tile, 62–74
 ventilation of, 97–100
 wood, 85–94
See also Asphalt shingles; Low-slope
 roofing; Metal roofing; Tile roofing;
 Wood roofing
- Roofing cement
 improves shingles wind resistance, 53
 incompatible with metal roofing, 84
 incompatible with modified bitumen, 96
 manual sealing of shingles, 57, 59
 sealing valleys, 60–61
- Rooftop decks, 150–151. *See also* Foot
 traffic
- RTF. *See* Rigid thermofoil
- Rubber tiles, kitchen flooring, 226
- R-Wrap, permeance, 4
- Salt air
 and cedar shingles, 19
 and clay tile, 63
 and unfinished wood, 47
- Salt spray
 and aluminum, 7, 82, 84–85
 and copper, 84–85
 and galvanized steel, 82, 83
 and stainless steel, 84
- Scald protection, 258–259
 retrofit, 258
- Sconces, wall lights, 200
- Screening
 manufactured systems, 152
 porch enclosures, 151–153
- Screws
 for composite decking, 141–142
 for drywall, 160–161
 for exterior decks, 141–142
 gasketed for metal roofs, 76
- Sealants
 butyl, 40
 comparison chart, 38
 compatible with metal roofing, 84
 for EIFS, 29
 for metal roofs, 77–78, 80
 for radon remediation, 287
 polyurethane, 40
 silicone, 39–40
 types, 37–40
See also Caulks
- Sealers
 undercoating for paint, 45–46
- Secondhand smoke. *See* Tobacco smoke
- Seismic zones, tile roofing in, 69–71
- Shading
 with awnings and shutters, 118–119
 with fixed overhangs, 118
 with shades screens, 119
 to reduce solar gain, 118–119
 of skylights, 123
- Shakes
 finishing, 19
 grades, 15–16
 sidewall installation, 15–19
 roofing installation, 85–94
 self-ventilating, 2
- Sheathing wrap
 code requirements, 3
 installation, 5
 performance characteristics, 3–5
 sealing around doors, 130–131
 sealing around windows, 119–123
 types, 4–5
 at water table, 8
See also Asphalt felt; Building paper;
 Plastic housewrap
- Sheetrock. *See* Drywall
- Shelving
 accessible design, 216
 allowable spans, 186
 in kitchen cabinets, 246
- Shingles. *See* Asphalt shingles; Modular metal
 shingles; Wood shingles
- Shower pans
 mortar-bed, 242–243
 prefab, 242
- Showers
 acrylic, 253, 255
 fiberglass, 253–255
 jetted tubs as, 255
 lighting of, 206
 material comparison chart, 254
 mixing valves, 258–259
 scald protection, 258–259
See also Shower pans
- Siding. *See* Cladding; Vinyl siding; Wood siding
- Silicone
 incompatible with metal roofing, 84
 sealants, 39–40
 weatherstripping, 130
- Silicone-modified polyesters, 85
- Sinks
 acrylic, 252–253
 china, 252–253
 composite, 252–253
 cultured marble, 252–253
 enameled cast-iron, 252–253
 enameled steel, 252
 faucet sets, 257–258
 flush-set (tile-edge), 251
 materials comparison chart, 252
 self-rimming vs. undermount, 252–252
 solid surfacing, 252–253
 stainless-steel, 252–253
 work center layout, 211
- Skylights, 123–127
 condensation on, 125–126
 controls, 123
 eaves flashing/underlayment, 56, 126–127
 energy performance, 125–126
 flashing with asphalt shingles, 56, 126–127
 flashing in wood roofing, 92
 glare from, 124–125
 glazing types, 123
 installation, 126–127
 kitchen lighting with, 213–214
 low-slope installations, 127
 roof ventilation around, 100
 shades and screens, 123
 sizing for daylighting, 124
 splayed wells, 125
 steep-slope installations, 127
 ventilation from, 125
- Slabs on grade
 radiant, 175
 under wood floors, 168–170
- Slate countertops, 250
- SmartDeck, railing system, 148
- Snow
 buildup at skylights, 56, 126–127
 buildup on roofs, 54, 97–98
 on low-slope roofs, 94
 metal roofs and, 78
 protecting siding from, 6, 9
 protecting deck ledgers from, 146
 tile roofs and, 64–65, 67–69, 72, 75
 wood roofs and, 87–89, 92
- Soaking tubs, 255–257. *See also* Jetted tubs
- Soapstone countertops, 250
- Soffits
 venting details, 98–100
 vinyl and aluminum, 23
- Solar design. *See* Passive solar design
- Solar-heat-gain coefficient, 116
- Solid surfacing
 characteristics, 249–250
 countertops, 250
 sinks, 252–253
- Sones, fan noise rating, 261, 263, 271
- Sound control, 188–194
 flanking paths, 190–193

- floor STC, IIC ratings, 193–194
- materials and workmanship, 193–194
- plumbing noise, 193
- principles, 189–190
- recommended levels, 192–193
- wall STC ratings, 190–192
- Spaced sheathing, for wood roofs, 87–89
- Splashback
 - and flashing membranes, 6
 - staining wood shingles, 19
 - and wall flashing, 9
 - and wood sidings, 1, 10, 47
- Spruce, as siding material, 9, 31–32, 43–45, 47
- Stainless steel
 - ASTM standards, 141, 143
 - for exterior decks, 141, 143
 - nails for fiber-cement, 20
 - nails for shakes and shingles, 17
 - reaction with galvanized, 141
 - roofing nails, 68, 89
 - salt spray and, 84–85
 - siding nails, 11, 13
 - sinks, 252–253
 - twisted wires, 69–70
- Stains
 - for decking, 154–55
 - and dyes, 188
 - effect of air barrier, 2
 - semi-transparent oil-based, 46, 154–55
 - solid-color, 44–45, 154–155
 - for wood shakes and shingles, 19
- Standing seam roofing
 - clip vs. flange systems, 78, 80
 - roofing panels, 78–80
- Step flashings
 - installation, 8
 - integrated with housewrap, 2
 - wood roofing and, 92–93
 - wood siding and, 14
- Stone
 - countertops, 249–250
 - kitchen and bath flooring, 226, 229–232
 - tile installation, 231–241
 - sealers for, 232
 - See also* Agglomerates; Engineered stone; Granite; Limestone; Marble
- Storm-resistant windows, 111–112
- Stucco
 - bonding to building paper, 25
 - degrading building paper, 2
 - drainage plane, 24–25
 - thin-coat, 28
 - three-coat, 25–28
 - underlayment for, 4
 - weather and application, 27–28
 - weep screeds, 24–26, 28–29
 - See also* EIFS
- StuccoWrap, 5
- Subflooring
 - for ceramic tile, 232
 - for resilient flooring, 178
 - for stone tile, 231
 - for wood flooring, 168
- Sulfur dioxide, 293–295
- Supply-only ventilation, 272–275
 - forced-air supply, 270, 273–274
 - multiport supply, 270, 274–275
- Swedish floor finishes, 171
- Sweeps, at exterior doors, 130
- Synthetic decking. *See* Composite decking; Plastic decking
- Tables, kitchen seating, 213
- Tannins, in redwood, cedar, 2, 11, 46, 92, 94.
 - See also* Extractive bleeding
- Task lighting, 195, 204. *See also* Lighting
- Telegraphing, of finger-jointed trim, 31
- Termite shields, 7
- Thinset
 - setting compounds, 237–239
 - tile installation, 239–240
- Tile nails, roofing tiles, 69
- Tile roofing
 - broken tiles, 74–75
 - clay tile, 63–64
 - concrete tile, 64–65
 - energy efficiency, 62, 74, 81, 85, 98
 - fastening, 68–71
 - fiber-cement tile, 65–66
 - flashings, 72–73
 - foot traffic, 63–64, 73
 - high-wind installation, 67, 69–71
 - installation on battens, 67–69, 72
 - installation on solid sheathing, 67–72
 - layout and stacking, 68
 - seismic installation, 69–71
 - sheathing types, 66–68
 - slope requirements, 66–69
 - types, 62–64
 - underlayment, 66–67
- TimberTech decking, 140
- Tobacco smoke, 268–269, 277–278, 280, 282, 287, 290, 294
- Toilets, 259–261
 - gravity-flush, 259
 - installation, 260–261
 - low-flow comparison chart, 259
 - power-assisted, 259–260
 - sweating of, 260
 - vacuum-assisted, 260
- Track lighting, 196, 201–203
- Trex decking, 140
- Trim. *See* Exterior trim; Interior trim
- Tropical hardwoods
 - decking, 138, 139–140
 - flooring, 164, 166
- Tubs. *See* Bathtubs
- Turbulent flow precipitators, 280
- Twisted wires, roofing tile, 69–70
- Tyle-Tye, 69
- Tyvek
 - Flex-Wrap, 6
 - permeance, 4
 - water resistance of, 3
 - See also* Plastic housewrap
- U-factor, window ratings, 112–113
- Ultraviolet (UV) radiation
 - effects on asphalt felt, 4
 - effects on exteriors, 19, 35, 42, 44–47
 - effects on fading, 114–115, 117, 123
 - effects on sealants, 38–40
 - effects on vinyl, 21, 36, 108–109
 - effects on wood roofing, 94
- Undercabinet lighting, 195, 197–198, 204–205
- Underlayment
 - for asphalt-shingle valleys, 59–60
 - for asphalt shingles, 54
 - for low-slope roofs, 54–55
 - for resilient flooring, 177
 - for sidewall shingles, 15
 - around skylights, 126
 - for tile roofs, 66–67
- for wood roofs, 87
- ventilating type, 87–88, 90, 91
- Unvented roofs, 98
- Urea-formaldehyde. *See* Formaldehyde
- Urethane
 - floor finishes, 171–172
 - foam moldings, 185
 - sealant for metal roofs, 78, 80, 84
 - See also* Polyurethane
- UV-cured urethanes, 171
- Valley flashing
 - asphalt shingles 59–61
 - metal roofs, 76–77
 - tile roofs, 72–73
 - wood roofs, 92–93
- Valleys
 - asphalt shingles comparison chart, 60
 - closed-cut, 60
 - open type, 61
 - roof ventilation and, 99–100
 - woven type, 60
- Vapor barriers, cold side, 6
- Veneer plaster, 163–164
- Ventilation
 - bathroom, 261–262
 - from casement windows, 105
 - effective window area, 103
 - kitchen, 262–263
 - from skylights, 115
 - See also* Roof ventilation; Whole-house ventilation
- Vertical wood siding
 - horizontal joints, 14
 - moisture problems, 9
 - nauling for, 12
 - water leakage in, 2
- Vikrell, FRP composite tubs, 255
- Vinyl
 - compatibility with flashing membranes, 6
 - finish on cabinets, 245
- Vinyl siding, 21–24
 - installation, 22–24
 - materials, 21–22
 - nauling, 22
 - self-ventilating, 2
 - trim details, 22–24
 - water leakage, 2
 - wood trim and, 24
- Vinyl windows
 - clad type, 107
 - installation, 109
 - solid type, 107–109
- Visible transmittance, window ratings, 116–117
- VOCs, 170, 179, 269, 282–283, 287, 290–292
 - in adhesives, 179, 292
 - in carpeting, 292
 - in floor finishes, 170
 - health effects, 283, 290
 - in new homes, 269
 - reducing exposure, 290
 - sources, 283, 289–290
 - See also* Formaldehyde; Pesticides
- Volatile organic compounds. *See* VOCs
- Vycor Deck Protector, 142
- Wall flashing
 - aluminum, 7
 - copper, 7
 - details, 7–9
 - materials, 6

- Warm edge spacers, for window, 114
- Water damage
 - to EIFS, 28–29
 - to hardboard trim, 32–33
- Water leakage
 - in brick veneer, 2
 - in claddings, 2
 - in diagonal wood sidings, 9–10
 - in EIFS, 28–29
 - through exteriors, 1–2, 8–10, 12, 37
 - splashback, 2, 10, 12
 - in vertical wood sidings, 9–10, 12
- Water resistance
 - of Grade D building paper, 4
 - of plastic housewrap, 4
 - of sheathing wrap, 3
 - tests for, 3
- Water table, detail, 7–8
- Water-based paints. *See* Latex paint; Paints
- Water-based stains, 188
- Waterborne urethanes, 170–172
- Waterproofing membranes
 - for ceramic tile, 236, 238–239
 - in shower pans, 242–243
- Water-repellant preservatives
 - as clear finish, 46–47
 - for decking, 139, 154–155
 - vs. paint, stain, 43
 - to seal end grain, 13
 - as sealer, 45
 - in wood window construction, 106
- Water-resistive barrier, code requirements, 1, 3
- Wax, floor finishes, 171–172
- Waxing, wood floors, 172
- WeatherBest decking, 140
- Weatherstripping
 - as bond breaker, 130
 - at exterior doors, 130
 - on windows, 104, 117
- Weep holes, in rain screen, 2, 37
- Weep screed, in stucco, 24–26, 28–29
- Western Wood Products Association, 9, 11–12, 45
- Wheelchairs
 - clear floor space, 215–216, 219–223
 - knee space for, 215, 220–221
 - turning circle, 215, 222–223
 - See also* Accessible design
- White cedar shingles, 15–17, 19
- Whole-house ventilation
 - balanced systems, 270, 275–277
 - comparison chart, 270
 - exhaust-only, 271–272
 - forced-air supply, 270, 273
 - installation, 271
 - sizing, 270–271
 - supply-only, 270, 272–275
 - See also* Air cleaners; Energy-recovery ventilators; Exhaust-only ventilation; Heat-recovery ventilators; Supply-only ventilation
- Window and Door Manufacturers Association (WDMA), 107, 110
- Windows
 - aluminum, 110
 - aluminum-clad, 107
 - awning and hopper, 105
 - casement, 105
 - certification of, 110, 112–113
 - comparison chart, 104
 - condensation on, 117
 - drywall trim detail, 163
 - effective open area, 103
 - energy comparison chart, 114
 - energy performance, 112–119
 - fading from, 114, 117
 - fiberglass, 109–110
 - fiberglass-clad, 107
 - flashing of, 119–123
 - flashing tapes for, 5
 - leakage around, 29
 - low-E, 112, 114–118
 - matching to climate, 113–115
 - material options, 105
 - orientation of, 117
 - performance grade and design pressure, 111
 - shading of, 118–119
 - single and double hung, 103–105
 - sliding, 105
 - solid vinyl, 107–109
 - storm-resistant, 111–112
 - tilt-turn, 105
 - types compared, 103–105
 - vinyl clad, 107
 - vinyl siding trim, 23
 - warm-edge spacers, 114
 - wood, 105–107
 - See also* Low-E; Shading; Skylights
- Wind resistance
 - of asphalt shingles, 53
 - of tile roofing, 67, 69–71
- Wood
 - bark-side down, 31
 - decay-resistance by species, 30–31, 47
 - equilibrium moisture content, 167
 - finger-jointed, 31–32
 - flooring species, 165–166
 - moisture content and painting, 42
 - paintability by species, 31–32
 - trim material, 30–31
 - vertical vs. flat grain, 43–44
- Wood finishes. *See* Finishes; Finishing; Paints; Painting
- Wood floors
 - over concrete, 168–170
 - engineered, 172–176
 - finish comparison chart, 171
 - finishing, 169–172
 - grades, 166–167
 - hardwood vs. softwood, 164, 166
 - installation, 168–169
 - in kitchens and baths, 171, 223, 226
 - moisture content, 167–168
 - nailing, 169–170
 - plank, 166
 - over radiant heat, 175–176
 - refinished, 172
 - relative humidity effects, 167
 - species chart, 165–166
 - subflooring for, 168
 - See also* Engineered wood floors
- Wood roofing, 85–94
 - over battens, 87–88
 - eaves flashing for, 89
 - flashings, 92–93
 - grades, 86
 - hip and ridge, 91–92
 - maintenance of, 93–94
 - nailing, 89, 91
 - pressure-treated, 86
 - reroofing with, 91
 - shake installation, 89–91
 - shingle installation, 89, 91–92
 - slope and exposure, 86–87
 - spaced sheathing, 87–89
 - valleys, 92–93
 - ventilating underlayment, 87–88, 90, 91
 - See also* Shakes; Wood shingles
- Wood shingles
 - bleaching oils, 19, 47
 - finishing, 19
 - grades, 15–16
 - oil-based primer on, 19
 - panelized, 18
 - roofing, 85–94
 - self-ventilating, 2
 - siding, 15–19
 - unfinished, 19
 - See also* Shakes; Wood roofing
- Wood siding
 - back-priming, 5, 9–10
 - details, 10–14
 - discoloration of, 46
 - fasteners for, 11
 - over foam sheathing, 2–3, 10
 - furred out, 2
 - grading, 9
 - installation, 10–14
 - leakage in vertical, diagonal, 9–10, 12
 - moisture content, 9
 - nailing schedule, 11–12
 - porous to water, 1
 - profiles, 9–10
 - sealing end grain, 13
 - species, 9
 - unfinished, 47
 - See also* Finishing
- Wood veneer, on cabinets, 244
- Woodstoves, and backdrafting, 269, 278, 293–296
- Woodwork
 - clear finish comparison chart, 189
 - paint-grade materials, 183–186
 - stains and clear finishes for, 188
 - See also* Casework; Interior trim
- Work triangle, in kitchens, 210, 214
- Xenon, undercabinet lighting, 198, 204
- Yellow glue, water-resistant, 40–41
- Zinc
 - in algae-resistant shingles, 53
 - metal roofing, 83
 - strips on wood roofing, 93
- Zinc coatings
 - Galvalume, 83
 - in galvanized steel, 72, 82–83
 - incompatible with PT wood, 84