

# Index

## A

- actuators and damper motors (duct system)
  - actuator motor characteristics, 316
  - installing, 316–320
  - modutrol motors, 314–316
  - troubleshooting, 320–321
  - types of, 313–314
  - uses of, 313
- air conditioning systems and duct furnaces, 340–341, 342–343
- air distribution systems, proprietary, 336–338
- air eliminators for steam heating systems, 545–547
- air supply in atmospheric injection gas burners, 57, 58, 60–61
- air switches for fans, 236–237
- air velocities, recommended and maximum for duct systems, 327
- aluminum, 2S, table of thicknesses, gauges, and weights, 301
- American National Standards Institute (ANSI) Codes and Standards, 451
- American Petroleum Institute (API), 451
- American Society for Testing Materials (ASTM) Material Specifications, 452
- American Society of Heating, Refrigerating, and Air-Conditioning Engineers (ASHRAE), 81, 295, 384–385
- American Society of Mechanical Engineers (ASME) Boiler Construction and Unfired Pressure Vessel Code, 452
- angle valves, 454–456
- anthracite coal, sizes of, 78–79
- ASHRAE Guide (1960), 81
- ASHRAE *Handbook of Fundamentals*, 295
- atmospheric injection gas burners
  - air supply in, 57, 58, 60–61
  - flame color and, 60–61
  - gas velocity and, 60–61
  - primary air ratios, 60
  - secondary air in, 60
- automatic controls
  - adjusting Honeywell step controller, 270–271
  - auxiliary switches, 269
  - balancing relays, 268
  - capacitors and, 284–287
  - contactors, cleaning, 280
  - contactors, defined and described, 275–277
  - contactors, replacing, 280–281
  - contactors, troubleshooting, 277–280
  - control panels (heating and cooling), 293
  - for fans, 233–244
  - for gas burners, 61–62
  - heating relays/time-delay relays, 261–263
  - high-pressure cutout switches, 288–289
  - inherent protectors, 282–283
  - low-pressure cutout switches, 289–290
  - manual switches, 269
  - motor starters, 281
  - overload relay heaters, 281–282
  - pilot duty motor protectors, 283–284
  - potential (start) relays, 263–265
  - pressure switches, 265–266
  - sail switches, 266–267
  - sequence controllers, 269–275
  - time-delay relays/heating relays, 261–263

## 640 Index

- automatic controls (*continued*)
  - time-delay switching, 271, 273, 275
  - transformers, 290–293
- automatic control systems
  - controlled device for, 99
  - controller for, 99
  - humidistats, 134–137, 140–143
  - temperature control circuits for, 100, 101
  - thermostats, 100–134
- automatic pilot safety valves, 174–178
- automatic valves
  - actuators for, 476
  - described, 475
  - lift adjustments and, 486–487
  - linkages for, 483–487
  - motorized operators for, 477
  - pneumatic operators, 476
  - safety precautions for, 478
  - self-actuating steam heating systems and, 482
  - servicing, 478–480
  - solenoid operators, 476
  - springless pneumatic operators for, 476–477
  - uses for, 476
  - valve operators, 476
  - zoning and, 477, 480–481
- auxiliary switches, 269
- B**
- Bacharach smoke scale, for oil burners, 44
- balancing relays, 268
- balancing valves, valve adapters, and filters for steam heating systems, 561–564
- bituminous coal, firing methods for, 80–81
- brass pipes, 369
- brass tubing, 369
- Bunsen burners, 57, 59, 60–61
- burners, conversion
  - gas, 63
  - gas piping for, 68–71
- burners, gas
  - atmospheric injection, 57–61
  - automatic controls and, 61–62
  - conversion burners, 63
  - defined, 57
  - electrical circuits and, 61
  - flame sensors, 214–217
  - gas conversion, described, 66–68
  - gas conversion, piping for, 68–71
  - inshot, 64
  - integral-type, 65–66
  - main, 63–64, 66
  - mercury flame sensors in, 216
  - operating principles for, 57–61
  - pilot, 63–64
  - precedence of local electrical codes
    - over manufacturer instructions, 61
  - safety precautions and, 72–73
  - troubleshooting, 73–75
  - upshot, 64
  - venting system and, 71–72
- burners, oil
  - adjustments to, 43–48
  - air delivery and blower adjustment, 42–43
  - air systems in, 38–39
  - burner flame detection and, 222
  - cadmium cell primaries, 220–223
  - and carbon dioxide in flue gas, 45–48
  - combination oil and gas, 19, 21
  - combination primary control and aquastat, 227–231
  - combustion chamber dimensions, 37
  - combustion testing of, 43–48
  - defined, 1
  - delayed ignition, 50
  - electrodes, 36
  - external warning signals for maintenance of, 48–49
  - flame retention head, 16
  - fuel pump capacity and, 26
  - fuel pump nozzles for, 32–36
  - fuel pump pressure, adjusting, 29–30
  - fuel pump priming, 29
  - fuel pump service and maintenance, 26–29
  - fuel pump troubleshooting, 31–32
  - fuel temperature and, 22

fuels used in, 22  
gun-type (atomizing), 1-2, 3-16  
high-static, 16  
installing, 40-42  
measuring carbon dioxide in flue  
  gas of, 46  
net stack temperature and, 45  
noise, excessive, 49  
odor, excessive, 50  
overfire drafts and, 46, 48  
primary controls, 219-220  
primary safety control services,  
  39-40  
puffbacks, 36-38  
rotary, 2-3, 16-18  
single-stage fuel pumps and, 21,  
  23-24  
smoke, excessive, 49-50  
stack detector primary controls,  
  223-227  
stack thermometer, use of, 45  
starting, 42  
troubleshooting, 48-56  
troubleshooting electrodes in, 38  
troubleshooting primary controls  
  in, 231-232  
two-stage fuel pumps and, 25  
vaporizing (pot-type), 2, 18-20  
burners, pilot (gas)  
  aerated, 196  
  flame adjustment, 202  
  flame positioning, 200  
  installing, 198-200  
  lighting, 201-202  
  and main burner ignition,  
    202-203  
  nonaerated, 197  
  operation of, 194-196  
  pilot bracket in, 197  
  pilot ports in, 197-198  
  pilot orifices, 198, 200-201  
butterfly valves, 465-467

**C**

capacitors  
  capacitor-start, capacitor-run  
    motors, 285-287  
  capacitor-start motors, 284-285  
  discharging, 287  
  replacing, 287

  testing, 287  
  troubleshooting, 287  
capacitor-start motors, 284-285  
chain wrenches, 406, 407  
check valves  
  described, 458-460  
  horizontal-lift 460-461, 467  
  lift-check, 460-461, 467  
  swing-check, 460, 464, 465, 466  
  vertical, 461  
  Watts Blackflow Preventer and,  
    461-462  
circulators for steam heating  
  systems  
  end suction pumps in, 510-511  
  inline centrifugal, 510  
  installation of, 515-516  
  lubrication requirements for, 509  
  operation of, 516-517  
  pressure drop, 514  
  pump head, 514  
  safety precautions for, 508, 509  
  selection of, 511-515  
  three-piece booster pumps,  
    506-509  
  troubleshooting, service, and  
    maintenance, 517-518  
  volute in, 507  
  wet-rotor, 509-510  
coal firing methods  
  anthracite coal and, 78-80  
  automatic controls for stokers,  
    86-90  
  bituminous coal and, 80-81  
  for boiler, 77  
  central cone, 81  
  draft requirements for, 77-78  
  for furnace, 77  
  hand-firing, 77  
  semibituminous coal and, 81  
  stoker firing, 81-86  
coal, sizes of anthracite, 78-79  
coal stokers  
  adjustment of coal feed, 94  
  air adjustment, manual, 92  
  air control, automatic, 92  
  air ducts and, 85  
  ashpits for, 86  
  automatic controls for, 86-90  
  bin-fed, 82-83

**642 Index**

- coal stokers (*continued*)
  - changing coal feeds for, 92
  - classes of, 81–82
  - clinker removal, 94
  - and coal burning capacity, 81–82
  - coal feeds, changing, 92
  - and coal selection, 91
  - coal storage methods and, 82–84
  - construction of, 84–86
  - Drawz, 82, 83, 86
  - electric motors and, 85–86
  - fans and, 85
  - feed worms and, 86
  - hold-fire controls and, 87
  - limit controls and, 87
  - lubrication, 93
  - motor overload protection for, 92–93
  - natural stack draft, 91–92
  - obstruction removal, 93
  - operating instructions, 90–91
  - retorts and, 85
  - stack switches (stack thermostats) and, 89
  - starting the fire, 91
  - summer service for, 93–94
  - thermostats and, 87
  - timers and, 88–89
  - transmission overload protection for, 93
  - transmissions for, 86
  - troubleshooting, 94–97
  - underfed, 82–83
- codes and standards for ducts and duct systems, 295
- combination gas valve, 62
- combustion chambers for gas
  - conversion burners, 67–68
- combustion testing and adjustments, oil burner, 43–48
- composite tubing (PAX), 369
- compressors, size and motor current ratings of, 277
- condensate pumps for steam heating systems
  - centrifugal, 499
  - duplex, 499
  - for gravity flow systems, 497–498
  - as mechanical lifts, 501
  - operation of, 498–499
  - types of, 498
  - vertical, 501
- connections, valve pipe
  - butt-welding, 495–496
  - for flanged end valves, 488, 489
  - fusion welding for, 492
  - for grooved end valves, 488
  - installation pointers, 489–492
  - silver brazing, 493–495
  - socket-welding, 496
  - soldering, 493–495
  - types of, 487
- contactors
  - cleaning, 280
  - defined, 275
  - described, 275–277
  - replacing, 280–281
  - troubleshooting, 277–280
- control panels (heating and cooling), 293
- controls, gas
  - automatic pilot safety valves, 174–178
  - burner primary, 145–152
  - combination gas valves, 187–194
  - continuous pilot dual automatic valves, 191–194
  - diaphragm valves, 164–166
  - direct-acting heat motor valves, 163–164
  - electrical circuits and, 146
  - electronic ignition modules, 203–211
  - falling-pressure switches, 170, 173
  - igniters, 211–214
  - for LP gas, 176
  - manual reset pressure switches, 173
  - pilot burners, 194–203
  - pilot-operated diaphragm valves, 185–186
  - pilot-pressure switches, 203
  - pressure regulators, 166–174
  - pressure switches, 170–174
  - rising-pressure switches, 173–174
  - solenoid coils, 158–162
  - solenoid gas valves, 153–158
  - standing pilot combination valves, 187–191

thermocouples, 181–184  
thermopiles, 184–185  
thermopilot valves, 178–180  
universal electronic ignition  
  combination valves, 194  
  valves in, 153  
controls, oil  
  cadmium cell primary, 220–223  
  combination primary control and  
    aquastat, 227–231  
  delayed-discharge, 219  
  flame detection cells, 221–222  
  oil burner primary, 219–220  
  solenoid valves, 217–219  
  stack detector primary, 223–227  
  types of, 217  
  valves, 217–219  
conversion burners  
  gas, 63  
  gas piping for, 68–71  
copper and brass pipes and tubing  
  for hydronic radiant heating  
  panels, 366  
  pipes versus tubes, 363, 366  
  table of sizes and dimensions of  
  water tubes, 367  
  uses for, 363  
copper water tubes, table of sizes  
  and dimensions of, 367  
cross-linked polyethylene tubing  
  (PEX), 368

**D**

damper motors and actuators (duct  
  system)  
  actuator motor characteristics,  
  316  
  installing, 316–320  
  modutrol motors, 314–316  
  troubleshooting, 320–321  
  types of, 313–314  
  uses of, 313  
dampers, duct, 305–313  
designing duct systems, 322–323  
diaphragm valves, 166  
dimensions of pipe, table of  
  double extra-strong, 362  
  extra-strong, 360–361  
  standard, 358–359

DIN (Deutsche [German] Industry  
  Norm) rating system, 366  
direct-acting heat motor valves (gas),  
  163–164  
direct-spark ignition modules (gas)  
  207  
dirt pockets in pipe systems, 434  
discharging capacities of standard  
  pipe (table of), 388  
draft diverters for gas heating  
  equipment, 71–72  
draft hoods for gas heating  
  equipment, 71–72  
drips in steam heating systems,  
  432–434  
duct furnaces  
  and air conditioning systems,  
  340–341, 342–343  
  duct maintenance and, 346–347  
  examples of, 338–339  
  installing, 340–347  
  maintenance of, 346–347  
  uses of, 338  
duct heaters, electric  
  components of, 347–353  
  description of, 347–348  
  safety controls for, 350–351  
  vibration controls for, 353  
ducts  
  air leakage, 325  
  equal friction method of sizing,  
  326–331  
  heat gain in, 324–325  
  heat loss in, 324–325  
  insulation of, 325–326  
  maintenance of, 331–332  
  materials for, 298–299, 300  
  sizing of, 326–331  
duct systems  
  actuators and damper motors,  
  313–321  
  air leakage in, 325  
  air pressure and, 323–324  
  air supply and venting of, 305  
  air velocities, table of  
    recommended and maximum,  
    327  
  balancing, 331  
  blowers for, 322–321  
  boots and boot fittings, 310–311

## 644 Index

- duct systems (*continued*)
  - calculations for, 323-324
  - components of, 299-305
  - crawl-space plenum systems, 297-298
  - damper motors and actuators, 313-321
  - dampers, 305-313
  - designing, 322-323
  - diffusers, 301, 305
  - duct insulation and, 325-326
  - electric heaters for, 347-353
  - extended plenum, 297, 298
  - fans for, 322-321
  - furnaces for, 338-347
  - grilles for, 301, 303
  - heat loss and gain in, 324-325
  - ideal, 323
  - information sources for, 296
  - maintenance of, 331-332
  - mobile home, 333-336
  - perimeter, 295, 296-297
  - proprietary, 336-338
  - registers for, 304
  - return air and exhaust air inlets, 302
  - roof plenum units, 332
  - run fittings, 303-305
  - sizing of ducts in, 326-331
  - supply air registers, 301, 304
  - venting and air supply, 305
  - zoning and, 314
- E**
- electrical circuits for gas burners, 61
- electrical circuits for gas controls
  - burners, effect of relay positions on, 150
  - line voltage, 148
  - low voltage, 146, 147
  - millivolt, 149
  - primary control, 146-147
  - relay positions and effect on burners, 150
- electric heaters for duct systems, 347-353
- electric zone valves for steam heating systems, 559, 562
- electrodes in fuel oil burners
  - puffbacks and, 36-37
  - servicing, 38
  - troubleshooting, 38
- electronic ignition modules
  - described, 203-204
  - direct spark ignition modules, 207
  - flame sensors and, 214-217
  - hot-surface ignition modules, 207-211
  - intermittent pilot ignition modules, 205-207
- end suction pumps for steam heating systems, 510-511
- equal friction method of sizing ducts, 326-331
- expansion of pipe, table of, 378
- expansion tanks in steam and hot water heating systems
  - closed steel, 541-543
  - described, 540
  - diaphragm, 543
  - sizing, 543-544
  - troubleshooting, 544
- F**
- fan and limit controls, 62
- fan center, 239-241
- fan controls
  - air switches, 236-237
  - combination fan and limit control devices, 251-256
  - fan center, 239-241
  - fan manager, 241
  - fan timer switches, 241-242, 243-244
  - impedance relays, 259-561
  - limit control devices for furnace plenums, 244-247
  - on/off devices, 233-236
  - relays, 237-239
  - safety cutoff switch, 242
  - secondary high-limit switches, 248-251
  - switching relays, 256-259
  - temperature-driven on/off devices, 233-236
  - upper fan controls, 236
- fan relays, 237-239

## Index 645

- fittings, pipe
  - branching, 380–381
  - bushings, 379–380
  - caps, 382
  - classification of, 369–370
  - couplings, 375
  - crosses, 381
  - defined, 369
  - directional, 380
  - elbows, 380
  - elbows with side outlets, 381
  - enlarging, 379–380
  - extension, 370–378
  - flanges, 382
  - flow of liquids in, 389
  - hot water pipes and tubing,
    - sizing of, 391
  - hydronic pipes and tubing, sizing
    - of, 391
  - illustrated table of, 371–375
  - joining, 370–378
  - joints, 375
  - locknuts, 375
  - makeup, 382
  - nipples, 370, 376–377
  - nipples, standard lengths, table of,
    - 376–377
  - offsets, 375
  - pipes, hot water, sizing of, 391
  - plugs, 382
  - reducing, 379–380
  - return bends, 380
  - return bends with back or side
    - outlets, 381
  - shutoff or closing, 382
  - sizing hot-water (hydronic) pipes
    - and tubing, 391
  - and steam pipe runs, 385,
    - 390–391
  - tubing, hot water, sizing of,
    - 391
  - unions, 379, 382
  - Y branches, 381
- flame color in atmospheric injection
  - gas burners, 60–61
- flame-retention head burners, 16
- flame sensors, 62, 214–217
- flow control valves for steam
  - heating systems, 558, 561
- flue gas (oil burner)
  - carbon dioxide content and, 45–48
  - measuring carbon dioxide in, 46
  - overfire drafts and, 46, 48
- fuel pumps, oil burner
  - capacity, 26
  - nozzles, 32–36
  - pressure adjustments, 29–30
  - priming, 29
  - service and maintenance of, 26–29
  - troubleshooting, 31–32
- fluids, valves for
  - angle, 454–456
  - automatic, 475–487
  - bolted flanged connets, 447–448
  - bonnets, 446–448
  - butterfly, 465–467
  - check, 458–463
  - components of, 445, 446
  - connections to pipes, 487–489
  - damaged stems in, 475
  - described, 445
  - discs in, 450–451
  - externally controlled, 445
  - gate, 450, 456–458
  - globe, 454–456
  - for high-pressure service, 448
  - information sources for, 453–454
  - inside screw stems in, 450
  - leakage in, 474–475
  - for low-pressure service, 448
  - matching service use and materials
    - in, 453
  - materials for, 451, 453
  - nonrising stems in, 450
  - operation of, 445
  - operators for, 475–487
  - outside screw stems in, 449–450
  - rising stems in, 450
  - screwed bonnets, 447
  - seat leakage in, 474–475
  - selection of, 469–472
  - standards and specifications for, 451
  - stems in, 449–450, 475
  - stop, 463–465
  - stuffing-box leakage in, 474
  - terminology for, 445–446
  - three-way, 469
  - troubleshooting, 472–475

## 646 Index

fluids, valves for (*continued*)

two-way, 467-469

union bonnets, 447

valve stems in, 445-446

wedges in, 450

Y globe valves, 469

Y valves, 469

furnace plenums, limit controls for,  
244-247

furnaces, duct

and air conditioning systems,  
340-341, 342-343

duct maintenance and, 346-347

examples of, 338-339

installing, 340-347

maintenance of, 346-347

uses of, 338

## G

galvanized pipe, 363

gas burners

atmospheric injection, 57-61

automatic controls and, 61-62

conversion burners, 63

defined, 57

electrical circuits and, 61

flame sensors, 214-217

gas conversion, described, 66-68

gas conversion, piping for, 68-71

inshot, 64

integral-type, 65-66

main, 63-64, 66

mercury flame sensors in, 216

operating principles for, 57-61

pilot, 63-64

precedence of local electrical coes

over manufacturer

instructions, 61

safety precautions and, 72-73

troubleshooting, 73-75

upshot, 64

venting system and, 71-72

gas controls

automatic pilot safety valves,  
174-178

combination gas valves, 187-194

continuous pilot dual automatic  
gas valves, 191-194

diaphragm valves, 164-166

direct-acting heat motor valves,  
163-164

electrical circuits and, 146

electronic ignition modules,  
203-211

falling-pressure switches, 170, 173

gas burner primary, 145-152

igniters, 211-214

for LP gas, 176

manual reset pressure switches,  
173

pilot burners, 194-203

pilot-operated diaphragm valves,  
185-186

pilot-pressure switches, 203

pressure regulators, 166-174

pressure switches, 170-174

rising-pressure switches, 173-174

solenoid coils, 158-162

solenoid gas valves, 153-158

standing pilot combination gas  
valves, 187-191

thermocouples, 181-184

thermopiles, 184-185

thermopilot valves, 178-180

universal electronic ignition  
combination valves, 194

valves, 153

gas conversion burners, 66-71

gas pipe

capacity table, 69

installation of, 429-430

installation requirements for, 70

threading specifications, 70

gas-pressure regulators

balanced, 170

and other controls, 168-169

gas valves

balanced diaphragm solenoid,  
155-156

combination, 187-194

continuous pilot dual automatic,  
191-194

diaphragm, 164-166

direct acting heat motor, 163-164

manual, 153

pilot-operated diaphragm,  
185-186

pilot shutoff, 153

pilot valve, 157  
shutoff, 153  
solenoid, 153-158  
solenoid coils, 158-162  
standing pilot combination,  
187-191  
thermopilot, 178-180  
three way solenoid, 157-158  
types of, 153  
universal electronic ignition  
combination, 194  
gas velocity in atmospheric injection  
gas burners, 60-61  
gate valves  
double-disc, 456-457  
outside screw and yoke,  
457-458  
wedge, 456  
globe valves, 454-456  
gun-type oil burners  
burner control, 5-6  
burner motor and coupling, 7-8  
combustion air blowers and, 10  
construction details, 3-5  
fuel pumps and, 8  
gun assembly, 6-7, 9  
ignition transformer, 7  
operating principles of, 10-16  
primary safety control for, 6  
turbulators and, 11-12

## H

heating relays/time-delay relays,  
261-263  
high-pressure cutout switches,  
288-289  
high-static oil burners, 16  
Honeywell step controllers,  
adjusting, 270-271  
hot-surface ignition modules  
(gas)  
self-diagnostic capabilities in some,  
208-210  
operation of, 207-208  
principal components of, 207  
safety precautions for, 210  
wiring for, typical, 209  
hot-water heating controls for steam  
heating systems, 554-557  
hot-water (hydronic) pipes/tubing,  
sizing, 391-392  
humidistats  
described, 135  
electronic, 135-136  
location of, 140-142  
pneumatic, 136, 140  
troubleshooting, 142-143  
hydronic (hot water) heating systems  
air eliminators, 545-547  
balancing valves, 561-564  
circulator installation, 515-516  
circulators for, 505-518  
circulator selection for, 511-515  
coils for, making up, 435-438  
condensate pumps for, 497-502  
drips in, 432-434  
electric control valves, 548-550  
electric zone valves for, 559, 562  
expansion tanks in, 540-544  
filters for, 561-564  
flow control valves for, 558, 561  
Hartford connections for, 434  
hot-water heating controls for,  
554-557  
maifolds for, 564-565  
pipeline strainers in, 565  
pipeline valves and controls for,  
547-548  
pipe stress in, relieving, 438-439  
pressure tests, 444  
pumps for, 497-518  
regulators, 548-550  
siphons in, 434  
steam traps in, 518-540  
swivels and offsets, 439  
temperature regulators, 548  
vacuum pumps, 502-505  
valve adapters for, 561-564  
water circulating pumps,  
505-518  
water pockets, eliminating,  
439-444  
water-tempering valves for,  
550-554  
hydronic (hot-water) pipes/tubing,  
sizing, 391  
hydronic radiant heating panels,  
pipes and tubing for, 366

## 648 Index

### I

- igniters (gas)
  - ignition control lockout times for, 213
  - operation of, 212–213
  - replacing hot-surface type, 214
- ignition control lockout times chart, 213
- impedance relay fan controls, 259–261
- inherent protectors, 282–283
- inline centrifugal circulators for steam heating systems, 510
- inshot gas burners, 64
- installation of oil burners, 40–42
- Institute of Boiler and Radistor Manufacturers (IBR), 384–385
- insulating pipes, 430–431
- integral-type gas burners, 65–66
- intermittent pilot ignition modules (gas)
  - definitions related to, 206–207
  - described, 205
  - operating sequence for, 205–206

### J

- joint compound, 405–405

### L

- leakage in valves, 474–475
- limit controls for furnace plenums, 244–247
- liquid flow, resistance of valves and fittings to, 389
- LP gas and automatic pilot valves, 176
- low-pressure cutout switches, 289–290

### M

- main gas burner, 63–64
- main gas valve, 62
- maintenance of duct systems, 331–332
- manifolds for steam heating systems, 564–565
- manual switches, 268

- Manufacturers' Standardization Society of the Valve and Fitting Industry (MSS) Standard Practices, 452
- mercury flame sensors, 216–217
- mobile home duct systems, 333–336
- monkey wrenches, 405

### N

- National Electrical Code, 265, 290
- natural gas manifold pressures, table of, 346

### O

- offsets in pipe systems, calculating, 397–404
- oil burner nozzles
  - described, 32–33
  - hollow cone pattern, 34
  - solid cone pattern, 34
  - spray angles of, 35–36
- oil burners
  - air delivery and blower adjustment, 42–43
  - air systems in, 38–39
  - burner flame detection and, 222
  - cadmium cell primaries, 220–223
  - and carbon dioxide in flue gas, 45–48
  - combination oil and gas, 19, 21
  - combination primary control and aquastat, 227–231
  - combustion chamber dimensions, 37
  - combustion testing and adjustments, 43–48
  - defined, 1
  - delayed ignition, 50
  - electrodes, 36
  - external warning signals and, 48–49
  - flame retention head, 16
  - fuel pump capacity and, 26
  - fuel pump nozzles, 32–36
  - fuel pump pressure, adjusting, 29–30
  - fuel pump priming, 29

- fuel pump service and maintenance, 26–29
- fuel pump troubleshooting, 31–32
- fuels used in, 22
- fuel temperature and, 22
- gun-type (atomizing), 1–2, 3–16
- high-static, 16
- installing, 40–42
- measuring carbon dioxide in flue gas of, 46
- net stack temperature and, 45
- noise, excessive, 49
- odor, excessive, 50
- overfire drafts and, 46, 48
- primary controls, 219–220
- primary safety control services, 39–40
- puffbacks and, 36–38
- rotary, 2–3, 16–18
- single-stage fuel pumps and, 21, 23–24
- smoke, excessive, 49–50
- stack detector primary controls, 223–227
- stack thermometer, use of, 45
- starting, 42
- troubleshooting, 48–56
- troubleshooting electrodes in, 38
- troubleshooting primary controls in, 231–232
- two-stage fuel pumps and, 25
- vaporizing (pot-type), 2, 18–20
- oil controls
  - cadmium cell primary, 220–223
  - combination primary control and aquastat, 227–231
  - delayed-discharge, 219
  - flame detection cells, 221–222
  - oil burner primary, 219–220
  - solenoid valves, 217–219
  - stack detector primary, 223–227
  - types of, 217
  - valves, 217–219
- oil valves, 217–219
- open-end wrenches, 408
- operating principles for gas burners, 57–61
- overload relay heaters, 281–282

**P**

- PEX (cross-linked polyethylene) tubing, 368
- pilot burners (gas)
  - aerated, 196
  - flame adjustment, 202
  - flame positioning, 200
  - installing, 198–200
  - lighting, 201–202
  - and main burner ignition, 202–203
  - nonaerated, 197
  - operation of, 194–196
  - pilot bracket, 197
  - pilot orifices, 198, 200–201
  - pilot ports in, 197–198
- pilot duty motor protectors, 283–284
- pilot duty thermostats, 283–284
- pilot generators, 184–185
- pilot-pressure switches, 203
- pilot safety valves, automatic, 174–178
- pipe dimensions, table of
  - double-extra-strong, 362
  - extra-strong, 360–361
  - standard, 358–359
- pipe dope, 404–405
- pipe expansion, 382–384
- pipe fitting measurements
  - hot-water mains, 393
  - mains and branches, 393
  - steam mains, 392
  - using, 392, 394, 397
- pipe fitting methods and procedures,
  - ferrous metal pipes assembly and makeup, 415–419
  - bending, 414–415
  - cleaning, 414
  - cutting, 409–412
  - reaming, 414
  - tapping, 414
  - threading, 412–413
- pipe fitting methods and procedures, nonferrous pipes
  - for brass and copper, 419–420
  - braze welding, 425–426
  - brazing, 424–425

## 650 Index

- pipe fitting methods and procedures,
  - nonferrous pipes (*continued*)
  - pressure ratings for soldered joints,
    - table of, 423
  - sequence of operations for, 420
  - soldering, 420-424
  - welding, 426-426-429
- pipe fittings
  - branching, 380-381
  - bushings, 379-380
  - calculating offsets and,
    - 397-404
  - caps, 382
  - classification of, 369-370
  - closing, 382
  - couplings, 375
  - crosses, 381
  - defined, 369
  - directional, 380
  - elbows, 380
  - elbows with side outlets, 381
  - enlarging, 379-380
  - extension, 370-378
  - flanges, 382
  - flow of liquids in, 389
  - illustrated table of, 371-375
  - installation methods for,
    - 409-419
  - joining, 370-378
  - joints, 375
  - lift, 432
  - locknuts, 375
  - makeup of, 382
  - measurements, 392-397
  - nipples, 370, 376-377
  - nipples, standard lengths, table of,
    - 376-377
  - offsets, 375, 397-404
  - offsets, calculating, 397-404
  - plugs, 382
  - reducing, 379-380
  - return bends, 380
  - return bends with back or side
    - outlets, 381
  - shutoff, 382
  - sizing hot-water (hydraulic) pipes
    - and tubing, 391
  - and steam pipe runs, 385,
    - 390-391
  - unions, 379, 382
  - Y branches, 381
- pipe fitting wrenches, 405-408
- pipeline strainers for steam heating
  - systems, 565
- pipeline valves and controls for
  - steam heating systems
    - described, 547-548
    - electric control valves, 548-550
    - temperature regulators, 548
- pipe materials
  - brass, 363, 366
  - bronze, 363, 366
  - composites, 369
  - copper, 363, 366
  - corrosion and ferrous metal,
    - 356
  - expansion of pipe and, table, 378
  - galvanized steel, 363
  - plastic, 366-368
  - synthetic rubber, 368-369
  - wrought iron, 356-357
  - wrought steel, 357, 363
- pipes
  - brass, versus brass tubing, 369
  - connections to valves, 487-489
  - convectors, connecting to,
    - 431-432
  - copper water tubes, table of sizes
    - and dimensions of, 367
  - dimensions of double extra-strong,
    - table of, 362
  - dimensions of extra-strong, table
    - of, 360-361
  - dimensions of standard pipe, table
    - of, 358-359
  - drips in steam, 432-434
  - expansion of, table, 378
  - gas, for conversion burners, 68-71
  - installation procedures for gas,
    - 429-430
  - installation requirements for gas,
    - 70
  - insulating, 430-431
  - lift fittings and, 432
  - mains, connecting risers to, 431
  - radiators, connecting to, 431-432
  - relative discharging capacities of,
    - 388

risers, connecting to mains, 431  
sizing, 384–385  
specific gravities, table of  
multipliers for, 69  
steam mains, table of sizes of,  
392  
steam, sizing, 385, 390–391  
supports, 404  
threading specifications for, 70,  
384  
threads, standard, table of,  
386–387  
pipe sizing, 384–385, 390–391  
pipe supports, 404  
pipe systems  
dirt pockets in, 434  
drips in steam, 432–434  
siphons in, 434  
pipe tongs, 406, 407  
pipe vices, 408–409  
pipe wrench, 405  
plastic tubing  
cross-linked polyethylene (PEX),  
368  
failures and, 367  
polybutylene, 368  
temperatures and, 368  
uses for, 366  
potential (start) relays, 263–265  
pressure regulators, gas, 62  
defined, 166  
external bleed systems and, 168  
internal bleed systems and,  
167–168  
use of, 166  
vent hole orifice and, 167,  
168  
venting and, 166–168  
pressure switches, 265–266  
falling-pressure (gas), 170, 173  
manual reset (gas), 173  
pilot-pressure, 203  
rising-pressure (gas), 173–174  
proprietary air distribution systems,  
336–338  
pumps for steam heating systems  
circulators, 505–518  
condensate, 497–502  
vacuum, 502–505

**R**

relative discharging capacities of  
standard pipe, 388  
rotary boil burners, 16–18

**S**

safety precautions  
for capacitors, 287  
for cast-iron head (oil) burners,  
16  
for circulating pumps in steam  
heating systems, 515, 516  
for cross-linked polyethylene  
tubing (PEX), 368  
for duct furnaces, 343–345  
for electrically operated valves,  
478  
for flow control valves in steam  
heating systems, 558  
for gas burners, 72–73  
for gas-fired and oil fired  
equipment, 145  
for gas ignition modules, 204  
for gas piping, 429  
for hot surface ignition systems,  
210  
for oil burners, 40  
for servicing gas burner primary  
controls, 151–152  
for stop valves, 465  
for three-piece booster pumps,  
508, 509  
for transformers, 290, 291  
for water-tempering valves for  
steam heating systems, 550  
sail switches, 266–267  
semibituminous coal, 81  
sequence controllers, 269–275  
servicing gas burner primary  
controls, 151–152  
sheet metal, table of thicknesses,  
gauges, and weights, 300  
single-stage fuel pumps, oil burner  
described, 21, 23–24  
fuel and, 22  
siphons in steam pipe systems, 434  
smoke scale, Bacharach (for oil  
burners), 44

## 652 Index

- soldered joints, pressure ratings
  - table, 423
- solenoid coils (for gas valves)
  - construction of, 161-162
  - servicing, 160-162
  - temperature and, 158
- sprayers, fuel oil, 1
- steam heating systems
  - air eliminators, 545-547
  - balancing valves, 561-564
  - circulator installation, 515-516
  - circulators, 505-518
  - circulator selection for, 511-515
  - coils for, making up, 435-438
  - condensate pumps, 497-502
  - drips in, 432-434
  - electric control valves, 548-550
  - electric zone valves for, 559, 562
  - expansion tanks in, 540-544
  - filters for, 561-564
  - flow control valves for, 558, 561
  - Hartford connections for, 434
  - hot-water heating controls for, 554-557
  - manifolds for, 564-565
  - pipeline strainers, 565
  - pipeline valves and controls for, 547-548
  - pipe stress, relieving, 438-439
  - pressure tests, 444
  - pumps for, 497-518
  - regulators, 548-550
  - siphons in, 434
  - steam traps in, 518-540
  - swivels and offsets, 439
  - temperature regulators, 548
  - water circulating pumps, 505-518
  - water pockets, eliminating, 439-444
  - vacuum pumps, 502-505
  - valve adapters for, 561-564
  - water-tempering valves for, 550-554
- steam mains, table of size of, 392
- steam traps in steam heating systems
  - automatic heat-up and, 520
  - balanced-pressure thermostatic, 525-526
  - boiler return, 537-539
  - bucket, 530-534
    - description of, 518-519
  - flash, 534
  - float and thermostatic, 526-528
  - float traps, 523-524
  - impulse, 534, 536
  - information on, 519
  - installing, 522-523
  - lifting, 537, 538
  - maintenance of, 520
  - sizing, 519-520, 521, 522
  - thermodynamic, 529-530
  - thermostatic traps, 524
  - tilting, 536-537
- Stillson wrenches, 406, 407
- stokers, coal
  - adjustment of coal feed, 94
  - air adjustment, manual, 92
  - air control, automatic, 92
  - air ducts and, 85
  - ashpits for, 86
  - automatic controls for, 86-90
  - bin-fed, 82-83
  - changing coal feeds for, 92
  - classes of, 81-82
  - clinker removal, 94
  - and coal burning capacity, 81-82
  - and coal selection, 91
  - coal storage methods and, 82-84
  - construction of, 84-86
  - Drawz, 82, 83, 86
  - electric motors and, 85-86
  - fans and, 85
  - feed worms and, 86
  - hold-fire controls and, 87
  - limit controls and, 87
  - lubrication of, 93
  - motor overload protection for, 92-93
  - natural stack draft, 91-92
  - obstruction removal, 93
  - operating instructions, 90-91
  - retorts and, 85
  - stack switches (stack thermostats) and, 89
  - starting the fire, 91
  - summer service for, 93-94
  - thermostats and, 87

timers and, 88–89  
transmission overload protection,  
93  
transmissions for, 86  
troubleshooting, 94–97  
underfed, 82–83  
stoker firing, 81–86  
stop valves, 463–465  
strap wrenches, 408  
switching relays for fans, 256–259  
synthetic rubber hose, 368–369

## T

tables, gas pipe capacity, 69  
thermocouples, 62  
  functions of, 181  
  testing of, 181–183  
  troubleshooting, 183–184  
thermopiles, 184–185  
thermopilot valves, 178–180  
thermostats  
  anticipators, 111–112, 114–119  
  base wiring for, 111  
  bimetallic strip, 102–103  
  boiler, 129  
  calibration, 123–125  
  components of, 105–109  
  cylinder, 127, 129  
  defined, 100, 102  
  electrical resistance, 104–105  
  and gas burners, 61–62  
  immersion, 126–127  
  insertion, 125–126  
  installing room type, 121–123  
  mercury switch, 102–104  
  outdoor, 132–134  
  programmable, 125  
  proportional, 132  
  remote bulb, 129–132  
  room, 119–121  
  switching combinations for, 112  
  terminal identification standards  
  for, 109, 114  
  types of, 102–105  
threading specifications for gas pipe,  
70  
threads, pipe, 384, 386–387  
three-way valves, 469  
time-delay relays/heating relays,  
261–263  
transformers  
  defined, 290  
  installing, 291–293  
  local electrical codes and,  
292  
  sizing, 291  
  voltage circuits and, 290  
troubleshooting  
  capacitors, 287  
  coal stockers, 94–97  
  contactors, 277–280  
  damper motors, 320–321  
  expansion tanks, 544  
  fuel oil pumps, 31–32  
  gas burners, 73–75  
  humidistats, 142–143  
  oil burner electrodes, 38  
  oil burner primary control,  
231–232  
  oil burners, 48–56  
  thermocouples, 183–184  
  thermostats, 138–139  
  valves for fluids, 472–475  
tubes, copper water, table of sizes  
  and dimensions of, 367  
tubing, brass, versus brass pipes,  
369  
tubing, plastic  
  cross-linked polyethylene (PEX),  
368  
  failures and, 367  
  polybutylene, 368  
  temperatures and, 368  
  uses for, 366  
two-stage fuel pumps, oil burner  
  described, 25  
  fuel and, 22  
two-way valves, 467–469

## U

upshot gas burners, 64

## V

vacuum pumps for steam heating  
  systems  
  dry, 505  
  operation of, 502–505, 506, 507  
  use of, 502  
  wet, 505

## 654 Index

- valve pipe connections
  - butt-welding, 495-496
  - for flanged end valves, 488, 489
  - fusion welding for, 492
  - for grooved end valves, 488
  - installation pointers, 489-492
  - socket-welding, 496
  - soldering and silver brazing, 493-495
  - types of, 487
- valves, 384
- valves and fittings, resistance to flow of liquids, 389
- valves, check
  - described, 458-460
  - horizontal-lift check, 460-461, 467
  - lift-check, 460-461, 467
  - swing-check, 460, 464, 465, 466
  - vertical, 461
  - Watts Blackflow Preventer and, 461-462
- valves for fluids
  - angle, 454-456
  - automatic, 475-487
  - bolted flanged bonnets, 447-448
  - bonnets, 446-448
  - butterfly, 465-467
  - check, 458-463
  - components of, 445, 446
  - connections to pipes, 487-489
  - damaged stems in, 475
  - described, 445
  - discs in, 450-451
  - externally controlled, 445
  - gate, 450, 456-458
  - globe, 454-456
  - for high-pressure service, 448
  - information sources for, 453-454
  - inside screw stems in, 450
  - leakage in, 474-475
  - for low-pressure service, 448
  - matching of service use and materials in, 453
  - materials for, 451, 453
  - nonrising stems in, 450
  - operation of, 445
  - operators for, 475-487
  - outside screw stems in, 449-450
  - rising stems in, 450
  - screwed bonnets, 447
  - seat leakage in, 474-475
  - selection of, 469-472
  - standards and specifications for, 451
  - stems in, 449
  - stop, 463-465
  - stuffing-box leakage in, 474
  - terminology for, 445-446
  - three-way, 469
  - troubleshooting, 472-475
  - two-way, 467-469
  - union bonnets, 447
  - valve stems in, 445-446
  - wedges in, 450
  - Y globe valves, 469
  - Y valves, 469
- valves, gas
  - balanced diaphragm solenoid, 155-156
  - combination, 187-194
  - continuous pilot dual automatic, 191-194
  - diaphragm, 164-166
  - direct acting heat motor, 163-164
  - manual, 153
  - oil, 217-219
  - pilot-operated diaphragm, 185-186
  - pilot shutoff, 153
  - pilot valve, 157
  - shutoff, 153
  - solenoid, 153-158
  - solenoid coils, 158-162
  - standing pilot combination, 187-191
  - thermopilot, 178-180
  - three way solenoid, 157-158
  - types of, 153
  - universal electronic ignition combination, 194
- valves, oil, 217-219
- vaporizing (pot-type) oil burners, 18-20
- venting systems for gas burners, 71-73

vibration controls for electric duct heaters, 353  
vices, pipe, 408-409

## W

water-circulating pumps for steam heating systems  
end suction pumps, 510-511  
inline centrifugal, 510  
installation of, 515-516  
lubrication requirements and, 509  
operation of, 516-517  
pressure drop, 514  
pump head, 514  
safety precautions for, 508, 509  
selection of, 511-515  
three-piece booster pumps, 506-509  
troubleshooting, service, and maintenance, 517-518  
volute in, 507  
wet-rotor, 509-510  
water pockets in steam heating systems, 439-444

water-tempering valves for steam heating systems  
described, 550  
limitations of, 553  
safety precautions for, 550  
servicing, 550-551  
uses of, 552-553, 554  
Watts Backflow Preventer, 461-462  
wet-rotor circulators for steam heating systems, 509-510  
wrenches, pipe fitting, 405-408  
wrought-iron pipe  
corrosion and, 356  
grades of, 356-357  
marking of, 356  
table of dimensions of, 358-362  
wrought steel pipe  
bursting and working pressure for, table of, 364-365  
weights of, 357, 363

## Y

Y globe valves, 469  
Y valves, 469