

# Index

## A

- absolute humidity, 363
- absolute pressure, 370
- absorption dehumidifiers, 538–540
- absorption refrigeration, 398
- adiabatic compression, 372
- adjustable air valves, 98
- after filter, 567
- air
  - atmospheric pressure of, 368–370
  - calculating rate of change in, 386
  - cleaning and filtering, 374–376
  - components of, 362
  - compression of, 370–372
  - dehumidification of, 365  
(*see also* dehumidifiers)
  - dew point of, 364
  - drying effect of, 363–364
  - humidification of, 364 (*see also* humidifiers)
  - humidity of, 362–365
  - latent heat in, 368
  - measuring physical properties of, 372–374
  - properties of, 362–370
  - relative humidity of, 519–520
  - saturation of, 362, 363
  - sensible heat in, 368
  - temperature of, 365–368
  - water vapor in, 362
- air change method, 323–325
- air circulation. *See* circulation
- air cleaners. *See* electronic air cleaners
- air compressor, 46
- air conditioners. *See* air-conditioning equipment; air-conditioning systems
- Air-Conditioning Contractors of America (ACCA), 396–397
- air-conditioning equipment
  - adding refrigerant to, 465–467
  - choosing correct size of, 394–395
  - cleaning and filtering aspects of, 374–376
  - compression in, 370–372
  - compressors (*see* compressors)
  - condensers, 439–446
  - cooling load estimate form for, 379–383
  - defined, 361
  - dryers for, 457, 458
  - electrical components in, 438–439
  - estimating required British thermal units (Btus) for, 395
  - evaporative coolers, 398–400
  - evaporators for, 446–448
  - filters for, 457, 458
  - float valves, 452–454
  - maintenance of, 460, 463–470
  - mechanical refrigeration (*see* mechanical refrigeration equipment)
  - motors and engines for, 435–437
  - pressure-limiting controls in, 457–458
  - processes of, 361
  - rate of air change for, 386
  - receivers for, 443, 447
  - refrigerants for, 448–449  
(*see also* refrigerants)
  - repairing, 467–470
  - room units, 421, 424
  - silver-brazing repairs for, 467–470
  - water-regulating valves in, 458–459

## 648 Index

- air-conditioning systems
  - ACCA design manuals for sizing, 396–397
  - atmospheric air in, 368
  - automatic controls for, 459
  - capillary tubes in, 454
  - central (*see* central air-conditioning systems)
  - and the comfort chart, 377–379
  - cooling methods for (*see* cooling methods)
  - for cooling structures, 386–393
  - dampers for, 531–532
  - efficiency ratings of, 423–424
  - estimating heat gain for, 379–383
  - and indoor-outdoor design conditions, 383
  - recommended relative humidity for, 378
  - refrigerant piping in, 454–457
  - and standards of comfort, 376–377
  - troubleshooting problems in, 459, 462–463
  - and ventilation requirements, 384–386
  - year-round, 412, 413
- air-cooled condensers, 414, 415–416, 439, 443
- air filters
  - box-type, 575
  - common placement of, 572–573
  - dry, 574
  - functions of, 572–573
  - inspection of, 573–574
  - installation of, 575
  - maintenance of, 575
  - mat-type, 575
  - symptoms of problems with, 433
  - viscous, 574–575
- air horsepower (AHP), 315
- air intake, 326–327
- air leakage, 309–310
- Airmaster fans, 336–337
- air-restricting device, 407
- air scoop, 19
- air separator, 26–27
- air-source heat pumps, 476–480, 486
- air stratification, preventing, 139
- air valves
  - adjustable, 98
  - automatic, 87–92, 100
  - identifying clogs in, 100
  - manual, 86–87
  - nonadjustable, 98
  - for radiators, 86–92
- air velocity, 317
- air ventilation. *See* ventilation
- air venting, 18, 32, 33, 96
- air volume control, 347
- air washers, 376, 522–523, 541, 571–572, 573
- ambient temperature, 77
- American Society of Heating and Ventilating Engineers, 312–313
- American Society of Heating, Refrigeration, and Air-Conditioning Engineers (ASHRAE), 376
  - research of solar radiation, 388
  - ventilation standards of, 384–385
- anodes, 197, 232, 244
- anti-restart timer, 501
- antisiphon hole, 195–196
- aquastats
  - for circulating pumps, 230
  - for gas-fired pool heater, 258
  - in hydronic heating system, 19, 21
  - symptoms of problem in, 106
  - temperature-control, 263, 265
- ash dump, 152
- ashpit, 152
- Atlantic box stove, 174
- atmospheric air, 368–370
- atmospheric pressure, 368–370
- atomizing humidifiers, 522–523

- attic fans, 348
  - boxed-in, 349, 350
  - centrifugal, 349–350, 351
  - cleaning, 354
  - control of, 349
  - exhaust outlets for, 353, 354
  - fly screening for, 352, 354
  - importance of, 348
  - location of, 354
  - louvers for, 352
  - lubrication of, 354
  - outlet area for, 350
- attics, fresh air requirements for, 288, 384
- auditoriums, fresh air requirements for, 384
- automatic air valves, 87–92
- automatic air vent valve, 18
- automatic cooling control circuits, 459, 460, 461
- automatic expansion valves, 449–450
- automatic float vent valve, 19
- automatic gas shutoff device, 216, 220
- automatic gas valves, 257
- automatic pilot valve, 212–217
- automatic spark ignition systems, 256
- automatic storage water heaters, 180–182, 183, 204, 206
- available line voltage, 342
- axial-flow fans, 318
  
- B**
- backdraft diverter, 229
- backdrafts
  - causes of, 356
  - in chimneys, 168–169
  - preventing, 358
  - remedy for, 170
- backflow preventer, 19, 21
- baffles, 129, 133, 237
- balancing valves, 25
- ball valves, 19, 21
- barometers, 369
- baseboard heaters
  - around corners, 114, 115
  - electric (*see* electric baseboard heaters)
  - fin-and-tube, 108, 110–113
  - hydronic, 109–110, 119
  - installing, 113–119
  - location of, 107
  - maintenance of, 119
  - operating efficiency of, 115–116
  - and plaster walls, 116
  - rating output of, 108
  - types of, 108
- basic fan laws, 319–321
- bathroom exhaust fans, 356
- belt-driven fans, 341, 343, 358
- bleeders, 515, 516
- blower coils, 447
- blowers, 491, 499
- boiler drain valve, 19, 21
- boiler energy saver, 19
- boiler fill valve, 19
- boiler rooms, fresh air requirements for, 288, 384
- boilers
  - coal-fired, 6
  - drain valve for, 19, 21
  - electric, 7
  - gas-fired, 6
  - for heating pools, 250–251
  - in hydronic heating systems, 6–7
  - minimum temperature of, 107
  - oil-fired, 6
  - in piping diagram, 20–21
  - symptoms of problems with, 50
- booster heaters, 183–184
- boxed-in fans, 349, 350
- box-type filters, 575
- Boyle's law, 370–372
- brake horsepower (BHP), 316, 338–339
- brass adapter, 9
- brass coupling, 9
- British thermal units (Btu)
  - given off by cast-iron radiators, 105

## 650 Index

- for heat-exchanger pool heaters, 264
    - for measuring heat gain, 368
    - for measuring output of heat-emitting units, 71
    - needed for air-conditioning equipment, 395
  - bucket traps, 138
  - building codes, for water heaters, 230–231
  - built-in electronic air cleaners, 564
  - burners. *See* gas burners
  - butterfly dampers, 306–307
  - bypass humidifiers, 525–526, 527
    - common location for, 529
    - installation of, 532–534
  - bypass piping, 261
  - bypass valves, 257, 276
- C**
- cabinet-model electronic air cleaners, 563–564
  - capacitor motor, 333
  - capacitors, 431, 432, 498, 518
  - capillary tubes, 454
  - capture velocities, 329
  - carbon monoxide, 310–311
  - cast-iron radiators. *See* radiators
  - ceiling panel heating systems, 2–5
  - central air-conditioning systems
    - applications of, 410–421
    - cooling methods of, 397–410
    - energy efficiency of, 424
    - internal workings of, 423
  - central cooling packages, 414–417
  - centrifugal compressors, 429–430
  - centrifugal fans, 318, 349–350, 351, 407
  - cfm. *See* cubic feet per minute (cfm)
  - charged-media electronic air cleaners, 549–550
  - charging, 465–467
  - Charles's law, 370–372
  - check valves, 19–23, 230
  - chimney effect, 284–285, 309–310
  - chimneys
    - cap for, 164
    - cleanout traps in, 168
    - connecting water heater flues to, 239
    - construction details for, 164–165
    - downdraft in, 168–169
    - and fireplaces, 145
    - flues in, 165–167
    - foundation for, 164
    - for gas-fired water heaters, 227
    - induced draft in, 285, 286
    - liners in, 165–167
    - metal, 169, 171, 173
    - providing good draft in, 162, 164
    - smoke pipe in, 167–168
    - troubleshooting problems in, 170
  - circuit breakers, symptoms of
    - tripped, 106, 242, 278, 340, 514, 517
  - circuits
    - defined, 7
    - signs of defect in, 277
  - circulating fans, 348
  - circulating pumps, 230
    - control of water flow by, 31
    - for heat-exchanger pool heaters, 264
    - for hydronic radiant heating system, 26
    - in piping diagram, 21
    - symptoms of problems with, 50–51
  - circulating tank, 245
  - circulation, 281, 296, 315
  - cleanout door, 152
  - cleanout traps, 168
  - clogged-filter indicators, 556–557, 558
  - closed-loop ground coupling system, 482–483
  - coal-fired boilers, 6
  - Coefficiency of Performance (COP), 267, 488

- coils
    - condenser, 403
    - dehumidifying, 541
    - evaporator, 402, 404
    - for heat pumps, 491
    - for manual water heaters, 245
    - patterns of, 41–43
    - symptoms of problems with, 514, 515
    - testing of, 46–48
    - used in hydronic radiant floor heating systems, 41–43
    - water-cooled, 401
  - cold-water coil cooling, 401, 420
  - cold-water supply lines, 194–195, 246
  - collector plates, 553–554
  - combination gas valves, 221–225, 257
  - combination water heaters, 191–192
  - comfort chart, 377–379
  - comfort cooling, 325
  - comfort levels, 520
  - commercial water heaters, 179
  - compound gauge, 373–374, 376
  - compressed-air test, 46
  - compression, 370–372
  - compression fittings, 13
  - compression tanks, 20–21, 26, 27
  - compressors
    - centrifugal, 429–430
    - contactor for, 498
    - control box on, 495–497
    - defined, 424
    - disconnecting, 435
    - dual, 486
    - and evacuated refrigerant, 465
    - function of, 424
    - for heat pumps, 490
    - hermetic, 429–430, 490
    - internal devices for, 434–435
    - knocking in, 465
    - open-type, 429
    - protection from short-cycling, 500
    - and pumping down refrigerant, 464
  - reciprocating, 424–425, 495–496
  - for refrigeration dehumidifiers, 542
  - replacement of, 435
  - rotary, 427–428
  - scroll, 426, 497
  - semihhermetic, 430
  - symptoms of freezing in, 431
  - symptoms of improper wiring of, 431, 432
  - symptoms of overheating in, 432
  - symptoms of problems with valves in, 462
  - symptoms of tightness in, 432, 433
  - troubleshooting problems with, 430–434, 517–518, 544
  - types of, 424–430
- concrete work, 34–35, 36
  - condensation
    - and heat sink, 473
    - latent heat of, 362, 363
    - in roof ventilators, 299–300
  - condensation drain line, 509
  - condensation gutters, 299–300
  - condenser coils, 403
  - condensers
    - air-cooled, 439, 443
    - in central cooling package, 414, 417
    - common operating problems in, 445
    - defined, 439
    - evaporative, 441–442, 445
    - maintenance of, 442–443
    - shell-and-coil construction for, 441, 444
    - in steam cooling systems, 409–410
    - symptoms of problems with, 433, 445, 462, 517
    - types of, 439, 440, 441, 442, 443
    - water-cooled, 441, 444

## 652 Index

- contactor, 498
- control box
  - capacitors in, 498
  - compressor contactor for, 498
  - defrost control board in, 499–500
  - for heat pumps, 494–499
  - on reciprocating compressor, 495–496
  - relays in, 499
  - on scroll compressor, 497
  - three-phase unit, 498
- control circuit, 257, 529
- convection, 71
- convection loss, 1
- convector capacities, 104–105
- convector coils, 412
- convectors
  - access door for, 101, 102
  - basic description of, 100
  - checking wiring in, 107
  - cleaning heating element of, 101, 102
  - determining capacities of, 104–105
  - heating element in, 101, 102
  - hydronic fan, 106–107
  - picture of, 101
  - pipng connections for, 101, 103–105
  - rating of, 101
  - types of, 100
- converter-type heater applications, 207
- cooling coils, 447
  - in central cooling packages, 414
  - in gas absorption refrigeration cooling, 404–405
  - for refrigeration dehumidifiers, 541, 542
  - symptoms of problems with, 462
  - in warm-air heating systems, 417–418, 419
- cooling control circuits, 459, 460, 461
- cooling cycle, in heat pumps, 473, 474, 491–493, 494, 511
- cooling loads, 379–383, 395–397
- cooling methods
  - absorption refrigeration, 398
  - cold-water coil, 401
  - evaporative, 398–400
  - gas absorption refrigeration, 403–408
  - gas compression refrigeration, 401
  - list of, 397
  - mechanical refrigeration cycle, 401–403
  - with steam, 398, 408–410
  - thermoelectric refrigeration, 397–398, 408
- cooling systems
  - for hydronic radiant floor heating systems, 68–69
  - working with heating system, 418–419
- cooling tower fans, 348
- cooling with steam, 398, 408–410
- copper heating elements, 111–112, 114
- copper tubing
  - bending, 9
  - cause of leaks in, 9
  - coil lengths of, 9–10
  - determining proper size of, 9
  - fittings for, 10–11
  - for indirect water heaters, 185–188
  - inside diameters (ID) of, 8, 9
  - in radiant floor heating systems, 8–10
  - spacing between, 10
  - straightening, 9
  - Type L, 8–9
- corrosion, in water heater storage tanks, 193
- counterflow spiral tube coil pattern, 41, 42
- coupling systems, 482–484
- crack method, 392
- crankcase heaters, 503, 505
- crimping fittings, 13

- cross-linked polyethylene (PEX) tubing, 11–14, 44–48
- cubic feet per minute (cfm), 320, 322, 323–326
- D**
- dampers, 153–155
  - in air-conditioning systems, 531–532
  - butterfly, 306–307
  - controlling, 304
  - in dehumidifier, 540
  - for fans, 333
  - in gas absorption refrigeration units, 407–408
  - louver, 305
  - in modified fireplace, 156
  - in roof ventilators, 296
  - sliding cone, 306
  - sliding sleeve, 306
  - and stiffener angles, 303
  - symptoms of problems with, 170
  - types of, 305
  - for ventilators, 304–307
- decoiler bending device, 9
- defrost cycle
  - for dehumidifiers, 543
  - in heat pumps, 473, 475–476
- defrost systems, 499–500
- defrost thermostat, 499
- defrost timer, 511
- dehumidification, 365, 537
- dehumidifiers
  - absorption, 538–540
  - air washers as, 571–572, 573
  - defined, 521
  - defrost cycle for, 542–543
  - and ice formation, 542–543
  - liquid-absorbent, 540
  - locating, 542
  - maintenance of, 542–543
  - refrigeration, 541–543
  - rotating-bed, 538, 539
  - spray, 541
  - stationary-bed, 538–540
  - troubleshooting problems in, 543–545
  - types of, 537–538
- dehydrators, 457, 458
- demand-frost controls, 499
- depressurization, 281
- desuperheat, 486
- desuperheaters, 494
- dew point, 364
- dew-point thermostats, 541
- dimmer switches, 57
- dining rooms, fresh air requirements for, 288, 384
- dip tubes, 194–196, 230–231, 234, 243
- direct-connected fans, 333
- direct-driven fans, 344, 358
- direct-expansion coils, 447
- direct-fired water heaters, 180
- direct-type pool heaters, 251, 255
- discharge valves, 433, 436
- disconnect switch, 23, 501
- distribution manifold, 17
- domestic water heaters, 179
- double delta burner, 211
- double-pipe condensers, 441, 444
- double serpentine coil pattern, 41, 42
- double-venting, 98
- downrafts, 168–169, 170, 237–238
- downward ventilation, 311
- draft hoods, 228–229, 272
- dry air filters, 574
- dry-bulb temperature, 365–367, 373, 398, 400
- dryers, 457, 458, 503
- dry installations, 6, 34, 39–40
- dual capacitor, 498
- dual compressors, 486
- dual-fuel heat pumps, 486
- dual-source heat pumps, 486
- ductless heat pumps, 487
- ductless split system, 420
- ducts, figuring proper length for, 327–328

## 654 Index

### E

- effective temperature, 377
- ejectors, 409–410
- electrical shock
  - from electric baseboard heaters, 124
  - and electric cable installations, 65
  - from heat pumps, 512, 517
  - from pool heaters, 273, 278
  - risk during electrical installations, 58
- electric baseboard heaters, 119–120
  - continuity of grounding in, 126–127
  - heating element in, 120–121
  - installing, 124–127, 128, 129, 130
  - preventing electrical shock from, 124
  - supply voltage of, 124, 125
  - temperature-limit switch in, 121, 124
  - thermostats for, 121, 123
  - time-delay relay in, 121
- electric boilers, 7
- electric cable, 65, 68
- electric furnace cabinet, 67
- electric motors, for mechanical refrigeration equipment, 435–437
- electric pool heaters, 260–263
- electric radiant floor heating systems
  - automatic controls of, 54–57
  - eliminating potential health risks from, 52
  - floor sensors for, 56
  - ground fault circuit interrupter for, 57
  - installation of electric cable for, 65
  - installation of heating mats for, 58–65
  - servicing and maintaining, 67
  - system components of, 52–57
  - troubleshooting problems in, 67–68
- electric water heaters, 227, 240–244
- electromagnetic fields, eliminating potential health risks from, 52
- electronic air cleaners
  - airflow through, 564
  - air volume adjustment for, 564
  - automatic controls for, 554–555
  - cabinet-model, 563–564
  - charged-media, 549–550
  - checking performance of, 563
  - clogged-filter indicator for, 556–557, 558
  - control panels for, 563–564
  - filters for, 565, 567
  - function of, 547
  - independent cabinet units, 549, 555–556
  - in-place water-wash controls for, 561–563
  - installation of, 564
  - locations of, 547–548
  - maintenance of, 565, 567
  - multi-position, 549, 550, 551
  - on-off control of, 559–561
  - operating, 563–564
  - performance lights for, 557–559, 560, 569–570
  - replacing ionizing wires in, 568–569, 570
  - return grille, 548–549, 552–553, 554, 565, 566, 569, 570
  - sail switch for, 559–561
  - system/blower controls for, 563
  - troubleshooting problems in, 569–571
  - two-stage, 553–554, 556
  - wiring of, 564–565
- electronic cells, 567, 568–569, 571
- Energy Efficiency Ratio (EER), 424, 488
- energy recovery ventilators (ERVs), 358

- Energy Star Rating, 488
  - engine rooms, fresh air
    - requirements for, 288
  - Environmental Protection Agency (EPA), 483
  - equivalent square feet of direction radiation (EDR), 104
  - evacuating the system, 464–465
  - evaporation, latent heat of, 363
  - evaporation loss, 1
  - evaporative condensers, 441–442, 445
  - evaporative cooling, 398–400, 419
  - evaporator coils, 402, 404, 446
    - controlling flow of refrigerant to, 450–452
    - in warm-air heating systems, 417–418, 419
  - evaporator pads, 525
  - evaporators, 446–448, 452, 455, 456
  - exhaust fans, 344, 345, 348, 355–356
  - exhaust hoods, 332, 355
  - expansion devices, 449–454
  - expansion joints, 114, 115
  - expansion tank, 19, 26, 27
  - expansion valves
    - automatic, 449–450
    - and evaporators, 452
    - symptoms of problems with, 433, 434, 456
    - thermostatic (TXV), 450–453, 493–494
  - exposed radiators, 72
- F**
- factory buildings, fresh air
    - requirements for, 288, 384
  - fan coils, 420–421
  - fans
    - air intakes for, 344, 346
    - ampere ratings for, 334–337
    - applications of, 347–348
    - for attic ventilation, 348–354
    - available line voltage of, 342
    - axial-flow, 318
    - basic laws of, 319–321
    - belt-drive arrangement in, 333
    - belt-driven, 341, 343
    - centrifugal, 318
    - circulating, 348
    - codes and standards for, 315
    - controlling air volume of, 347
    - covering air intake of, 326–327
    - decreasing noise of, 347
    - determining air intake of, 326
    - determining cubic feet per minute (cfm) of, 320, 323–326
    - direct-connected, 333
    - direct-driven, 344
    - and duct systems, 344
    - exhaust, 348, 355–356
    - friction losses in, 327
    - furnace blowers, 319
    - general ventilation from, 322
    - for heat pumps, 499
    - horsepower input of, 316
    - inlet area of, 316
    - inspection of, 346–347
    - installation of, 344–347
    - kitchen, 348
    - for local ventilation systems, 328–331
    - maximum tolerable noise level of, 342
    - mechanical efficiency (ME) of, 319
    - minimum fan capacity (cfm) of, 343
    - motors for, 333–341
    - mounting arrangement of, 342
    - outlet area of, 316
    - overload relay heaters for, 337
    - parallel operation of, 321
    - performance curves for, 322
    - propeller, 318, 341
    - quantifying qualities of, 316–317
    - screen efficiency of, 326–327
    - selection of, 333, 341–344
    - series operation of, 321
    - static pressure of, 327–328, 341–342

## 656 Index

- fans (*continued*)
  - symptoms of problems with, 514, 545
  - temperature of ambient air in, 342
  - terms and definitions dealing with, 315–317
  - troubleshooting problems with, 337–341
  - tubeaxial, 318
  - types of, 317–318
  - unitary system, 348
  - in unit heaters, 139–140
  - vaneaxial, 318
  - for ventilating kitchens, 355
  - for ventilation systems, 287
  - for water heater venting systems, 227–228
  - for whole-house ventilation, 356–359
- fan ventilators, 294–295
- Federal Clean Air Act, 513
- feed water pressure regulator, 22, 23
- felt sleeves, 114, 115, 116
- fill valves, 20–21
- filter dryers, 503
- filters
  - in air-conditioning equipment, 375–376
  - air washers as, 571–572, 573
  - for electronic air cleaners, 565, 567
  - See also* air filters
- fin-and-tube baseboard heaters, 101
  - design features of, 108, 110
  - expansion of heating elements in, 113–114
  - heating element in, 108, 111
  - integral, 112–113
  - keeping enclosure surface temperature down in, 119
  - metals used for, 111–112
  - separate, 108, 110–112
- fireboxes, 150–151, 156, 160, 162
- fireman switch, 257
- fireplaces
  - ash dump in, 152
  - ashpit in, 152
  - chimneys for (*see* chimneys)
    - cleanout door in, 152
    - components of, 146, 149–150
    - construction details of, 149–150
    - dampers for, 153–155
    - dimensions of, 146–149
    - elevation of, 146
    - firebox in, 150–151
    - freestanding, 157–158, 160, 161
    - hearth of, 148, 149, 151
    - importance of well-designed chimney to, 162
    - lintel in, 151
    - location of, 145
    - mantel in, 151
    - modified, 156–157, 158
    - Rumford, 158, 160, 162, 163
    - smoke chamber of, 150, 152
    - troubleshooting problems in, 170
- fittings
  - for copper tubing, 10
  - for cross-linked polyethylene (PEX) tubing, 13
  - used in hydronic radiant heating systems, 9
  - for water storage tanks, 194, 195
- flexible ducts, 420–421
- float valves, 453–454, 525
- float vent, 19
- floor covering materials, 40–41
- floor panel heating systems, 2, 3.
  - See also* hydronic radiant floor heating systems
- floor sensors, 56–57
- flow check valves, 19
- flow-control valves, 19, 20–21, 22
- flow rate, 9
- flow switch, 257
- flue effect, 284–285
- flue gases, 227, 229
- flue liner, 165, 166
- flues
  - backdraft diverter in, 229
  - connecting to chimney, 239
  - construction of, 167

- function of, 165
  - for gas-fired water heaters, 228–229
  - induced draft in, 285, 286
  - placement in automatic storage heaters, 181, 182, 183
  - for pool heater ventilation, 272
  - serving two fireplaces, 166, 167
  - and smoke pipes, 178
  - symptoms of clogging in, 170, 233, 234, 235, 236
  - in water heaters, 183–184
  - fluid dynamics, 319–321
  - fly screening, 352, 354
  - forced-air cooling, 68–69
  - forced-air unit heaters, 135
  - formulas
    - for air change rate, 386
    - for air supplied per minute, 385
    - for calculating heat gain, 394
    - for calculating heat leakage, 387
    - for change in watt output, 125
    - for compression of air, 371–372
    - for determining air intake, 326
    - for determining cubic feet per minute (cfm) of fans, 320, 323, 325
    - for determining heat gain from solar radiation, 387, 388, 389–391
    - for determining rate of flow, 285
    - for equivalent square feet of direct radiation (EDR), 104
    - for fan air velocity, 317
    - for fan tip speed, 317
    - for fan velocity pressure (VP), 317
    - for measuring fan power, 320–321
    - for mechanical efficiency (ME), 316
    - for relative humidity, 363
    - for relative radiating surface, 77
    - rpm ratio, 320
    - for static pressure, 330–331
    - for theoretical draft of chimneys, 164
    - for total heating load, 26
  - Franklin stoves, 175, 176, 177
  - freestanding fireplaces, 157–158, 160, 161
  - Freon. *See* refrigerants
  - fresh air, requirements for, 287–289, 384–385
  - friction loss, 9
  - fuel pumps, 277
  - furnace plenums, 530, 531
  - furnaces
    - air filters in, 572, 573, 574, 575
    - capture velocities for, 329
    - humidistat in, 526–527, 528
    - steam humidifiers in, 525
    - used for heat pump, 486
  - fuses, blown, 242, 278, 340, 514, 517
- G**
- galvanizing plants, fresh air requirements for, 288, 384
  - garages
    - fresh air requirements for, 288, 384
    - placement of ventilators for, 308–309
    - ventilation of, 310–311
  - gas absorption refrigeration, 403–408
  - gas burners
    - automatic pilot valves on, 212, 213–214, 215, 216, 217
    - gas cocks for, 214, 217
    - for gas-fired pool heater, 258
    - in gas-fired water heaters, 210, 211
    - lighting pilot of, 223, 224–225
    - shutoff device for, 216, 220
    - symptoms of problems with, 233, 234, 235, 274, 276
    - types of, 211
  - gas cocks, 214, 217
    - for lighting pilot, 223, 224–225
    - symptoms of problems with, 235, 274
  - gas compression refrigeration, 401

## 658 Index

- gas engines, 437
  - gases, compression of, 370–371
  - gas-fired boilers, 6
  - gas-fired heat pumps, 485–486
  - gas-fired pool heaters, 255–259, 272, 274–276
  - gas-fired unit heaters, 140–141, 142–143
  - gas-fired water heaters
    - automatic controls on, 210–220
    - automatic gas shutoff device for, 216, 220
    - automatic pilot valve on, 212, 213–214, 215, 216, 217
    - burners for, 210, 211
    - combination gas valves for, 221–225, 226
    - draft hoods for, 228–229
    - gas cocks for, 214
    - gas supply line to, 229
    - general description of, 209
    - installation and operation of, 225–229
    - location of, 226
    - placement of flues in, 181, 182, 183
    - pressure regulators for, 214–215, 217–219
    - pressure relief valve for, 220
    - safety controls for, 215–220
    - slow-recovery, 189
    - storage capacity of, 209
    - temperature relief valve for, 216, 219
    - thermostatic valves for, 212, 213
    - troubleshooting problems in, 233–237
    - venting regulations for, 226–227
    - venting systems for, 227–229
  - gaskets, 80–84, 229
  - gas meters, 229
  - gas-pressure regulators, 257
  - gas ranges, 172
  - gas shutoff valves, 258
  - gas supply lines, 229, 232, 236, 275
  - gas valve regulators, 276
  - gate valves, 19, 21
  - gauge manifold, 503, 506
  - gauge pressure, 370
  - general ventilation, 322
  - geothermal heat pump, 7, 481–483
  - globe valves, 19, 21
  - gravity air convectors, 101, 103, 104–105
  - gravity ventilators, 306, 307
  - ground fault circuit interrupter (GFCI), 56, 57
  - ground-source coupling system, 482–483
  - ground-source heat pumps, 477, 481–483, 486
- H**
- headers, 258
  - hearths, 148, 149, 151
  - heat
    - external sources of, 386–392
    - internal sources of, 392–393
  - heat-emitting units
    - convectors, 100–107
    - list of, 71
    - output of, 71
    - radiators (*see* radiators)
    - selection of, 71
  - heat-exchanger pool heaters, 263–264, 265
  - heat exchangers
    - air-to-air, 356, 358
    - in central cooling package, 414
    - in gas absorption refrigeration units, 405
    - for gas-fired pool heater, 258
    - for ground-source coupling systems, 482
    - liquid-to-air, 418
    - maintaining constant flow of water through, 257
    - pipng connections for, 207
    - in pool heaters, 255
    - in radiant heating systems, 27
    - temperature-control aquastats for, 263, 265

- heat gain
  - estimating, 379–383
  - from infiltration and ventilation, 388, 392, 394
  - from occupants of conditioned spaces, 393
  - from solar radiation, 387–388, 389–391
  - total instantaneous, 388
- heating coils
  - for manual water heaters, 245
  - patterns of, 41–43
  - testing of, 46–48
  - used in hydronic radiant floor heating systems, 41–43
  - in wall panel, 5
- heating cycle, in heat pumps, 471–473, 510–511
- heating elements
  - aluminum, 111–112
  - copper, 111–112
  - in electric baseboard heaters, 120–121
  - in electric water heaters, 240, 242
  - expansion of, 113–114
  - in fin-and-tube baseboard heaters, 108, 111
  - for indirect water heaters, 185–188
  - for unit heaters, 130–131
  - in steam humidifier, 525
  - steel, 111–112
  - symptoms of problems with, 243
- heating loads
  - calculating, 26
  - sizing, 396–397
- heating mats
  - checking ohm resistance of, 58
  - detecting break in cable in, 67
  - for electric radiation floor heating systems, 53–54
  - installing in joist cavities under subfloors, 61–65
  - installing over subfloors, 58–61
  - insulation of, 65, 66
  - insulation test for, 58
  - manufacturers of, 53–54
  - ordering, 53
  - repair kits for, 67
  - wiring of, 62
- Heating Season Performance Factor (HSPF), 488
- heating systems
  - in ceiling panels, 2–5
  - electric radiant floor (*see* electric radiant floor heating systems)
  - in floor panels (*see* floor panel heating systems; hydronic radiant floor heating systems)
  - heat-emitting units used in (*see* heat-emitting units)
  - hydronic (*see* hydronic radiant heating systems)
  - most popular installation method for, 2
  - radiator efficiency of, 74, 76–77
  - steam (*see* steam heating systems)
  - supplementary radiant, 476–477
  - for swimming pools (*see* pool heaters)
  - temperature drop in, 44–45
  - values of materials that insulate, 41
  - wall panel, 5
  - warm-air, 417–418, 419
- heat leakage, 386–387
- heat loss, 1
- heat output, 77–78
- heat pump pool heaters, 267
- heat pumps
  - accumulators for, 501
  - adjusting refrigerant charge in, 513
  - air handler in, 517
  - air-handler section of, 490, 491
  - air-source, 476–480
  - anti-restart timer for, 501
  - capacitors for, 498
  - checking operation of, 509–510

## 660 Index

- heat pumps (*continued*)
  - coding cycle of, 511
  - compressor contactor for, 498
  - compressor section of, 490
  - compressors in, 430
  - control box on, 495
  - controls for, 490
  - cooling cycle in, 473, 474
  - crankcase heater for, 503, 505
  - defrost cycle in, 473, 475–476
  - defrost system for, 499–500
  - desuperheaters for, 494
  - disconnect switch for, 501
  - dual-fuel, 486
  - dual-source, 486
  - ductless, 487
  - efficiency ratings for, 487–488
  - fan motors for, 499
  - filter dryer for, 503
  - function of, 471
  - gas-fired, 485–486
  - gauge manifold for, 503, 506
  - ground-source, 481–483
  - heat exchanger for, 482
  - heating cycle of, 471–473, 510–511
    - and heat sink, 473
    - and heat transfer, 473
  - high-pressure switches for, 500–501
  - for hydronic radiant floor heating systems, 7
  - identifying problems with compressors in, 517–518
  - indoor coil and blower for, 491
  - installation of, 507, 509–510
  - lockout relay for, 501
  - low-pressure switches for, 501
  - muffler for, 505
  - operating instructions for, 510–511
  - operating principles of, 471–476
  - outdoor, 489
  - packaged, 478, 480
  - performance ratings for, 487–488
  - refrigerant lines of, 490, 491
  - relays for, 499
  - for residential heating and cooling systems, 477–478, 479
  - reverse-cycle conditioning, 471
  - reversing valve and solenoid in, 491–493, 494
  - room thermostats for, 501–502
  - service valves for, 502–503, 504–505
  - sizing, 505, 507
  - split-system, 477–478, 479, 513
  - for supplementary heat, 502
  - supplementary radiant heating systems for, 476–477
  - system components of, 488–490
  - troubleshooting problems in, 514–517
  - types of, 476
  - water-source, 483–485
- heat pump water heaters, 190–191
- heat recovery ventilators (HRVs), 356, 358
- heat removal method, 325–326
- heat sink, 473, 483
- heat transfer, 1
  - from heat pumps, 473
  - of heat pump water heaters, 190–191
- heat transfer coils, 185
- heat transference, 481
- heat-transfer plates, 38, 40
- heat transfer surface, 183–184
- heat transmission, coefficient of, 387
- hermetic compressors, 429–430, 435, 490
  - troubleshooting problems with, 517–518
- high-limit switches, 257, 277
- high-pressure gauge, 373, 376
- high-pressure switches, for heat pumps, 500–501
- horizontal draft hood, 228
- horizontal slot port cast burner, 211
- hospitals, fresh air requirements for, 288, 385

- hot-water baseboard heaters
  - figures of, 109–110
  - temperature types of, 119
- hot-water heating systems. *See*
  - hydronic radiant heating systems
- hot-water radiators, 73
  - locating vents for, 96
  - water temperature in, 77
- hot water safety relief valve, 19
- hot-water space-heating boilers, 186
- hot-water supply lines
  - circulation in, 230
  - for manual water heaters, 246
  - vacuum relief valve for, 206, 208
  - for water heaters, 196
- humidification, 364
- humidifiers, 364
  - air washers as, 571–572, 573
  - atomizing, 522–523
  - automatic controls for, 526–529
  - automatic flush system for, 534–535
  - best location for, 531, 532, 533
  - bypass, 525–526
  - defined, 521
  - draining reservoir of, 534
  - in gas absorption refrigeration units, 407
  - guiding airflow to, 529, 530
  - humidistats for, 526–529
  - installation of, 529–534
  - maintenance of, 534–535
  - pan, 523–524
  - placing base of, 533
  - power, 526
  - spray, 522–523
  - stationary-pad, 524
  - steam, 524–525
  - troubleshooting problems with, 535–537
  - types of, 522
  - ultrasonic, 523
  - and wet-bulb depression, 367
- humidistats, 349
  - combined with thermostat, 554–555, 557
  - control circuits for, 529, 530
  - defined, 521
  - for electronic air cleaners, 554–555, 557
  - figure of, 528
  - furnace-mounted, 526–527, 528
  - in pan humidifiers, 524
  - programmable, 529
  - for refrigeration dehumidifiers, 542
  - settings on, 542
  - symptoms of problems with, 536, 537, 544
  - wall-mounted, 528
- humidity
  - absolute, 363
  - controlling, 364–365
  - defined, 521
  - description of, 362
  - dew point, 364
  - and drying effect of air, 363–364
  - measuring, 373
  - problems of excessive levels of, 520
  - relative, 363, 519–520
  - specific, 363
  - and wet-bulb readings, 366
- hybrid heating and cooling systems, 418–421
- hydraulic knock, 434
- hydraulic pressure test, 46
- hydronic fan convectors, 106–107
- hydronic forced-air systems, 418
- hydronic radiant floor heating systems
  - air venting requirements for, 32, 33
  - basic description of, 6
  - boilers used in, 6–7
  - coils and coil patterns for, 41–43
  - components of, 6
  - constant water circulation in, 30–32
  - construction details for, 33–40
  - control system for, 25

## 662 Index

- hydronic radiant floor heating
  - systems (*continued*)
  - cooling for, 68–69
  - designing, 28–41
  - design procedures for, 32–33
  - floor coverings for, 40–41
  - heat pumps used in, 7
  - installing, 44–48
  - manifolds for, 14–17
  - for melting ice and snow, 51–52
  - servicing and maintaining, 49
  - sizing calculations for, 32–33
  - testing of heating panels in, 46–48
  - troubleshooting problems in, 49–52
  - tubing used in, 7–14
  - typical size of tubing in, 45
  - valves in, 17–25
  - water heaters used in, 7
- hydronic radiant heating systems
  - air separator for, 26–27
  - applying central air-conditioning to, 411–412, 413
  - automatic controls for, 27–28
  - baseboard heaters, 109–110, 119
  - circulator pump for, 26
  - convector piping connections in, 103
  - and ductless split systems, 420
  - and evaporative coolers, 419
  - expansion tank for, 26, 27
  - with fan coil and flexible ducts, 420–421
  - fittings used in, 10–11
  - heat exchanger for, 27
  - kickspace heaters, 127–129, 131
  - for melting ice and snow, 51–52
  - piping diagram of, 20–21
  - recessed radiation in, 129, 132–133
  - and residential chillers with
    - ceiling-mounted panels, 421
  - thermostat for, 27–28, 29, 30
  - in unit heaters, 137, 138
  - water chiller for, 410–411, 412
  - working with cooling systems, 418–419
- I**
  - ice-melting systems, 51–52
  - ignition systems, for pool heaters, 256
  - impellers
    - function of, 317–318
    - symptoms of problems with, 278
  - indirect-type pool heaters, 251, 255
    - electric-fired, 261, 262–263
    - gas-fired, 255–256
    - oil-fired, 259–260, 261
  - indirect water heaters
    - advantages of, 188–189
    - with built-in coils, 188
    - heat source for, 185–186
    - versus hot-water space-heating boilers, 186
    - piping connections for, 207
    - storage capacity of, 188
    - water circulation in, 188
  - indoor design conditions, 383
  - induced draft, 285, 286
  - induction
    - caused by wind, 297
    - defined, 282
    - in revolving ventilators, 290–291
    - in siphonage ventilators, 294
    - from wind, 282–285
  - induction motors, 435–436
  - industrial buildings, ventilation for, 313
  - infiltration, 309–310
    - calculating heat gain from, 394
    - defined, 392
  - inlet air openings
    - for attic fans, 350
    - in gas absorption refrigeration units, 406–407
    - general rules for, 312
    - for ventilators, 298–299
  - inline thermometers, 23
  - inspections
    - of air filters, 573–574
    - of cross-linked polyethylene (PEX) tubing, 44
    - of fans, 346–347

installations  
 of air filters, 575  
 of baseboard heaters, 113–119  
 of bypass humidifiers, 532–534  
 dry, 6, 34, 39–40  
 of electric baseboard heaters,  
 124–127, 128, 129, 130  
 of electric cable, 65  
 of electronic air cleaners, 564  
 of fans, 344–347  
 of gas-fired water heaters,  
 225–229  
 of heating mats, 58–65  
 of heat pumps, 507, 509–510  
 of humidifiers, 529–534  
 of hydronic radiant floor heating  
 systems, 44–48  
 of pool heaters, 271–273  
 of pressure relief valves,  
 201–202  
 of radiators, 79–86  
 of relief valves, 201–202  
 of stoves, 177–178  
 of temperature relief valves,  
 201–202, 203–204  
 of wall panel heating systems, 5  
 of water heaters, 232–233  
 wet, 6, 33–35, 36  
 instantaneous water heaters,  
 184–185  
 insulating values, for materials  
 covering radiant heating  
 systems, 41  
 insulation, of heating mats, 58,  
 65, 66  
 intermittent ignition systems, 256  
 ionizing wires, 568–569  
 isolation valve, 22–23

**J**

jig, 9  
 joining key, 82, 83, 84  
 joist cavities  
 codes regulating notching of, 62  
 installing electric heating mats  
 in, 61–65  
 sealing ends of, 65

**K**

kickspace heaters, 127–129, 131  
 kitchen fans, 348, 355–356  
 kitchens  
 capture velocities for ranges in,  
 329  
 fresh air requirements for, 288,  
 385  
 ventilation of, 311–312

**L**

large-volume water heaters,  
 182–183  
 latent heat, 368  
 gain of, 379  
 removal of, 541  
 leaks  
 air, 309–310  
 in copper tubing, 9  
 locating source of, 46  
 testing for in heating coils, 46  
 lintels, 151  
 liquid-absorbent dehumidifiers,  
 540  
 liquid heat exchanger, 405  
 liquid line, 455  
 local ventilation, 322, 328–331  
 exhaust hoods for, 332  
 lockout relay, 501  
 loop continuity, 45  
 loops, 7  
 loose fill insulation, 40  
 louver dampers, 305  
 louvers  
 for attic fans, 352–353  
 on evaporative coolers, 398  
 low-pressure switches, 501

**M**

magnet valves, symptoms of  
 problems in, 236  
 main gas–pressure regulator,  
 214–215, 217–219  
 maintenance  
 of air-conditioning equipment,  
 460, 463–470

## 664 Index

- maintenance (*continued*)
  - of air filters, 575
  - of baseboard heaters, 119
  - of condensers, 442–443
  - of dehumidifiers, 542–543
  - of electronic air cleaners, 565, 567
  - of humidifiers, 534–535
  - of hydronic radiant floor heating systems, 49
  - of mechanical refrigeration equipment, 460, 463–470
  - of pool heaters, 273–274
  - of thermostats, 511–513
  - of water heaters, 232–233
- manifold balancing valves, 17
- manifolds
  - combinations of, 15
  - diagrams of, 14–15
  - function of, 14
  - for gas-fired pool heater, 258
  - gauge, 503, 506
  - in hydronic radiant floor heating system installations, 47–48
  - measuring temperature of water in, 17
  - preassembled, 16
  - return, supply, 16–17
  - types of, 14
  - valves for, 16–17
- manifold station, 16
- mantels, 151
- manual gas valves, 214, 217, 223, 224–225
- manual water heaters, 245–246
- masonry filler, 40
- masonry fireplaces, 149–150
- mat-type filters, 575
- mean temperature difference, 296
- mechanical efficiency (ME), 316, 319
- mechanical refrigeration cycle, 401–403
- mechanical refrigeration equipment
  - adding refrigerant to, 465–467
  - automatic controls for, 459
  - capillary tubes in, 454
  - components of, 423
  - compressors in (*see* compressors)
  - condensers for, 439–446
  - electric motors for, 435–437
  - evacuating, 464–465
  - evaporators for, 446–448
  - float valves, 452–454
  - gas engines for, 437
  - maintenance of, 460, 463–470
  - operating pressure in, 449
  - pressure-limiting controls in, 457–458
  - pumping down, 464
  - purging of, 464
  - receivers for, 443, 447
  - refrigerant for, 448–449
  - refrigerant piping in, 454–457
  - water-regulating valves in, 458–459
- mechanical ventilation, 282, 287
- media pads, 549–550
- metal chimneys, 169, 171, 173
- metal tubing, bending, 9
- milled slot port cast burner, 211
- millivolt ignition systems, 256, 257
- mills, fresh air requirements for, 385
- mixing valves
  - automatic, 24
  - locations of, 19, 20–21
  - manual, 24
  - in piping diagram, 20–21
  - in radiant heating systems, 23–24
  - symptoms of problems with, 50
  - thermostatic, 23
- modified fireplaces, 156–157, 158
- motorized zone valve, 24–25
- motor overload protector, symptoms of problems with, 518
- motors, for fans, 333–341
- motor shafts, symptoms of problems with, 278
- mufflers, 505
- multicoil water heaters, 182–183
- multiflue water heaters, 183–184

multimeters, testing heating mats  
with, 58  
multiple stamped ribbon ports, 211  
multiple-story buildings, use of  
ceiling panel heating system  
in, 3–4

## N

National Electrical Manufacturer's  
Association (NEMA), 333  
natural ventilation, 282, 289  
nipples  
for radiator sections, 80–84  
smooth beveled, 85–86  
nonadjustable air valves, 98  
nonbarrier tubing, 11  
nonprogrammable thermostats, 56

## O

office buildings  
ceiling panel heating system in, 5  
fresh air requirements for, 288,  
385  
ohm resistance, checking, 58  
oil burners, symptoms of problems  
with, 277–278  
oil-fired boilers  
hydronic, 186, 187  
use of, 6  
oil-fired pool heaters, 259–260,  
261, 277  
oil-fired unit heaters, 141, 144  
oil-fired water heaters, 182, 183,  
238–240, 241  
open-type compressors, 429  
outdoor design conditions, 383  
outlet velocity (OV), 316  
overflow prevention control,  
symptoms of problems with,  
544  
overload relay heaters, 337  
oxygen barrier tubing (BPEX), 11  
oxygen-induced damage, 191–192

## P

packaged heat pumps, 478, 480  
packed-type radiator valve, 86, 87

packless radiator valve, 86, 88  
pan humidifiers, 523–524  
passive ventilation, 282  
performance curves, 322  
PEX tubing, 11–14, 44–48  
pilot gas–pressure regulator,  
214–215, 217–219  
pilot generators, for gas-fired pool  
heater, 257  
pilot lights  
in millivolt ignition systems,  
256  
symptoms of problems with,  
233, 234, 235, 236, 274,  
275  
pilot valves, symptoms of  
problems with, 236, 515, 516  
pipe bend support, 47  
pipes  
for air-conditioning refrigerant,  
454–457  
wrapping with felt sleeve, 114,  
115, 116  
*See also* tubing  
piping connections  
for convectors, 101, 103–105  
for heat exchangers, 207  
for indirect water heaters, 207  
in mechanical refrigeration  
equipment, 454–457  
for radiators, 92–93, 95–97  
for refrigerants, 454–457  
for unit heaters, 135–138, 139,  
140, 141  
piston compressor, 424–425  
plastic pipe. *See* cross-linked  
polyethylene (PEX) tubing  
plenum adapter kit, 531  
point-of-use water heaters,  
184–185  
pool filters, 278  
pool heaters  
aquastat in, 258  
basic systems of, 249–251  
classifying, 251, 255  
diagrams of system of, 252–254  
direct-type, 251, 255  
electric, 260–263

## 666 Index

- pool heaters (*continued*)
    - and electrical shock, 278–279
    - finding required energy rating for, 270–271
    - gas burner assembly in, 258
    - gas-fired, 255–259, 274–276
    - header for, 258
    - heat-exchanger, 263–264, 265
    - heat exchanger for, 258
    - heat pump, 267
    - ignition systems for, 256
    - indirect-type, 251, 255
    - installing, 271–273
    - manifold for, 258
    - oil-fired, 259–260, 261
    - operating principles of, 251
    - repair and maintenance of, 273–274
    - sizing, 267–271
    - solar, 264, 266–267
    - standard set of clearances for, 272
    - troubleshooting problems in, 274–279
    - wiring diagram for, 259
  - pool pumps, 278
  - port cast burners, 211
  - power humidifiers, 526
  - power venting, 227–228
  - prefabricated roof curbs, 303–304
  - prefilter, 567
  - pressure gauges, 373–374, 376, 377
    - for heating coils, 46
    - location in hydronic heating system, 19
  - pressure-limiting controls, 457–458
  - pressure-reducing valves, 25
  - pressure regulators
    - for gas-fired water heaters, 214–215, 217–219
    - symptoms of problems with, 234
  - pressure relief valves
    - components of, 199–200, 203, 204
    - figures of, 200, 201
    - functions of, 25, 198–199
    - for gas-fired water heaters, 220
    - importance of, 198
    - installation of, 201–202
    - location in hydronic heating system, 19
    - for manual water heater, 245
    - rated capacity of, 204, 205
    - safety requirements for, 199
    - symptom of problems with, 244
    - temperature-sensing element in, 199–200, 201–202
  - pressure switches, 257
    - symptoms of problems with, 274, 275, 276
  - programmable thermostat, 55–56
  - propeller fans, 318, 341, 342
  - psychrometers, 373
  - pumping down, 464
  - pump rooms, 288, 385
  - pumps
    - air-source heat, 476–480, 486
    - aquastats for, 230
    - circulating (*see* circulating pumps)
    - dual-fuel, 486
    - ductless, 487
    - fuel, 277
    - gas-fired, 485–486
    - heat (*see* heat pumps)
    - heat transfer from, 473
    - for pools, 278
    - recirculating, 541
    - for spray dehumidifiers, 541
    - water, 190
  - purge valves, 19, 25
  - purging, 464
  - push nipples, 85–86
- Q**
- quick-recovery heaters, 189
  - quick vents, 98
- R**
- radiant heat, from fireplaces, 158
  - radiant panel heating systems

- ceiling panel systems, 2–5
- electric floor systems (*see* electric radiant floor heating systems)
- floor panel systems (*see* floor panel heating systems)
- heat transfer in, 1
- hydronic floor heating (*see* hydronic radiant floor heating systems)
- principles of, 1–2
- typical control system for, 25
- wall panel systems, 5
- radiation
  - defined, 71
  - from fireplaces, 158
  - recessed, 129, 132–133
- radiation heat loss, 1
- radiators
  - automatic air valves in, 100
  - cast-iron, 72
  - column-type, 72, 74
  - effect of paint on efficiency of, 100
  - exposed, 72
  - finding square-foot equivalent direct radiation (EDR) of, 79
  - heat output from, 77–78
  - hot-water, 73
  - installing, 79–86
  - joining sections of, 79–86
  - leveling, 76
  - location of air vents for, 96
  - manual air valves in, 100
  - operating efficiency of, 74, 76–77
  - pipng connections for, 92–93, 95–97
  - ratings for, 74–76
  - relative radiating surface of, 77
  - removing air from, 86–92
  - sizing, 78–79
  - steam, 72–73
  - steam traps in, 99
  - supply and return connections for, 95
  - surface area of, 77
  - test pressure of, 84
  - troubleshooting problems with, 99–100
  - tubular, 73, 75–76
  - two-pipe connections to, 97
  - types of, 72, 73–74
  - valves for, 86–92
  - venting in, 76–77, 93–94, 96, 98–99
  - venting trapped air in, 98–99
  - waterways in, 72
- radiator sections
  - checking alignment of, 83, 85
  - joining, 79
  - joining of threaded, 80–85
  - joining with smooth beveled nipples, 85–86
- radiator valves
  - air valves, 86–92
  - functions of, 86
  - packed-type, 86, 87
  - packless, 86, 88
  - thermostatic expulsion, 89–90, 92
- ranges
  - capture velocities for, 329
  - categories of, 171–172
  - defined, 171
  - figures of, 176, 178
  - solid fuels used in, 172
  - wood-burning, 176
- rate of flow, 285
- receivers, 443, 447
- recessed heaters, 129, 132–134
- reciprocating compressors, 424–425
- recirculating pumps, 541
- recycling heating, 250–251
- refrigerant cylinder, 465–467
- refrigerants
  - adding to air-conditioning equipment, 465–467
  - adjusting charge in heat pumps, 513
  - and air-conditioning efficiency, 449

## 668 Index

- refrigerants (*continued*)
- automatic expansion valves for, 449–450
  - charging, 465–467
  - control devices for, 449
  - in cooling cycle of heat pumps, 473, 474
  - in crankcase heater, 503, 505
  - defined, 448
  - evaporation of, 447
  - in evaporative condensers, 442
  - and float valves, 453–454
  - Freon, 448
  - in gas absorption refrigeration
    - cooling, 403–404, 405–406
    - and heat pumps, 471–473, 491
    - maintaining line connections of, 512
    - measuring, 513
    - operating pressure in, 449
    - pipng for, 454–457
    - properties of, 448
    - pumping down, 464
    - in refrigeration dehumidifiers, 542
    - removing, 464–465
    - reversing valve for, 491–493, 494
  - in scroll compressor, 426
  - symptoms of overcharged, 463
  - symptoms of problems with, 433, 434, 456, 457, 462, 515
  - symptoms of shortage of, 462
  - thermostatic expansion valves
    - for, 450–453
    - in water-cooled condensers, 441
  - refrigeration dehumidifiers, 541–543
  - relative humidity, 363, 519
    - defined, 521
    - desirable levels of, 520
    - measuring, 373
    - recommended for air-conditioning systems, 378
    - reducing, 520–521
  - relative radiating surface, 77
  - relay contactor, 57
  - relays, 499, 501
  - relief valves
    - components of, 199–200, 203, 204
    - in domestic hot-water heaters, 197–206
    - functions of, 198–199
    - in hot-water discharge line, 202
    - importance of, 198
    - installation of, 201–202
    - in piping diagram, 20–21
    - safety requirements for, 199
    - symptoms of problems with, 237
    - temperature-sensing element in, 199–200, 201–202
    - vacuum, 206, 208
    - See also* pressure relief valves; temperature relief valves
  - repair coupling, 9
  - repair kits, for heating mats, 67
  - resistance tests, 58
  - resistors, 120, 121
  - restaurants, fresh air requirements
    - for, 288, 385
  - return grille electronic air cleaners, 548–549, 552–553, 554, 565, 566, 569, 570
  - return line, in radiant heating systems, 7
  - return manifold, 16
  - reverse-cycle conditioning, 471
  - reversing valve, 473
    - four-way, 492–493
    - in heat pumps, 491–493
  - revolving ventilators, 290–291
  - ridge ventilators, 293–294
  - roof curbs, 303–304
  - roof ventilators
    - angle rings for, 302
    - base of, 289, 299–301
    - components of, 295–296
    - connection to roof, 299–301
    - dampers for, 304–307
    - fan, 294–295
    - function of, 289
    - inlet air openings in, 298–299

- prefabricated roof curbs for, 303–304
- purpose of, 298
- revolving, 290–291
- ridge, 293–294
- siphonage, 294
- stationary-head, 290
- stiffener angles for, 303
- turbine, 291–293
- types of, 289–290
- room air conditioners, 421, 424
- rotary compressors, 427–428
- rotating-bed dehumidifiers, 538, 539
- rpm ratio, 320
- Rumford fireplaces, 158
  - distinguishing features of, 162
  - invention of, 160
  - reducing turbulence in, 162
  - vertical path of flue in, 163
- run capacitor, 498, 518
- S**
- sacrificial anode rod, 193
- saddle valves, symptoms of
  - problems with, 536
- safety codes, for water heaters, 230–231
- safety controls, for gas-fired water heaters, 215–220
- safety relief valves
  - components of, 199–200, 203, 204
  - in domestic hot-water heaters, 197–206
  - functions of, 198–199
  - in hot-water discharge line, 202
  - safety requirements for, 199
  - temperature-sensing element in, 199–200, 201–202
  - See also* pressure relief valves; temperature relief valves
- safety switches, for gas-fired pool heater, 257
- sail switches, 559–561
- sandwich floor construction, 35–36, 37
- scale buildup, 191
- schools, fresh air requirements for, 288, 385
- scroll compressor, 426
- Seasonable Energy Efficiency Ratio (SEER), 424, 488
- semihermetic compressors, 430
- sensible heat, 368
  - gains of, 379
  - removal of, 541
- sensor bulbs, 452–453
- serpentine coil patterns, 41–43
- service check valve, 19
- service valves, for heat pumps, 502–503, 504–505
- shade factors, 391
- sheathed cable, 126
- shops, fresh air requirements for, 288–289, 385
- shutoff valve
  - in piping diagram, 21
  - for testing heating coils, 46
- sidearm heaters, 209, 245
- silver brazing, 467–470
- single-phase motors, ampere ratings for, 334
- single serpentine coil pattern, 41, 43
- single-stage wiring diagrams, 122
- siphonage ventilators, 294
- slab manifold, 17
- slab-on-grade construction, 34, 35
- sliding cone dampers, 306
- sliding sleeve dampers, 306
- sling psychrometer, 373
- slow-recovery heaters, 189
- smoke chambers, 149, 150, 152, 170
- smoke pipes, 167–168, 178
- smoke shelf, 148, 149, 170
- snap-action thermostat, 189
- snow-melting systems, 51–52
- solar collectors, 267
- solar pool heaters, 264, 266–267
- solar radiation
  - heat gain from, 387–388, 389–391
  - and shade factors, 391

## 670 Index

- solar sensors, 266
- solar water heaters, 246–247
- solenoids, 491–493
- solenoid valve, symptoms of
  - problems with, 431, 536
- sorbent material, 538
- space heaters. *See* unit heaters
- specific humidity, 363
- split-system cooling, 411–412, 413
- split-system heat pumps, 477–478, 479, 513
- spray dehumidifiers, 541
- spray humidifiers, 522–523
- square-foot equivalent direct radiation (EDR), 79
- stack effect, 284–285, 309–310
- stack height, 297
- stamped horizontal port burner, 211
- stamped mono-port burner, 211
- standard air, 316
- standard atmosphere, 368
- standards of comfort, 376–377
- standing pilot light, 256
- staple-up method, 36, 38–39
- start capacitors, 494, 498, 518
- static efficiency (SE), 316
- static pressure (SP), 316, 327–328
  - calculation of, 330
  - and fan selection, 341–342
- stationary-bed dehumidifiers, 538–540
- stationary-head ventilators, 290
- stationary-pad humidifiers, 524
- steam
  - cooling with, 398, 408–410
  - in gas absorption refrigeration units, 407
  - heating with (*see* steam heating systems)
- steam cooling systems, 408–410
- steam diverter valve, 407
- steam generator, 407
- steam heating systems
  - applying central air-conditioning to, 411–412, 413
  - convector connections in, 104, 105
  - in unit heaters, 136–138, 139, 140, 141
  - water chiller for, 410–411, 412
- steam humidifiers, 524–525
- steam radiators, 72–73
  - locating vents for, 96
- steam traps
  - in radiators, 99
  - for unit heaters, 136
- steel heating elements, 111–112, 113
- stiffener angles, 303
- storage tanks. *See* water storage tanks
- stoves
  - Atlantic box, 174
  - defined, 169
  - eighteenth-century, 175
  - figures of, 174–176, 177
  - Franklin, 175, 176, 177
  - history of, 170–171, 175
  - installing, 177–178
  - operating instructions for, 178
  - primary function of, 170
  - wood-burning, 174
- strainers, 457, 458
- suction line, 455
- superheat, 452
  - removing, 486
- superheated water, 198
- supply manifold, 16–17
- supply voltage, in electric
  - baseboard heaters, 124, 125
- surface-area method, 268–269, 270–271
- swimming pools
  - diagrams of water-heating system for, 252–254
  - heating systems for (*see* pool heaters)
  - heating through recycling, 250–251
  - heat sources for, 249–250

maintaining proper temperature  
in, 251  
protection from wind, 270  
radiant heating systems for,  
249–250  
solar heating of, 249  
swing-check valve, 22, 230

## T

tankless water heater. *See* indirect  
water heaters

temperature  
comfort chart index, 377–379  
daily range of, 367  
defined, 365  
dry-bulb, 373  
dry-bulb versus wet-bulb,  
365–367  
effective, 377  
and latent heat, 368  
measuring, 372–373, 374  
relationship to relative humidity,  
519  
and sensible heat, 368  
wet-bulb, 373  
and wet-bulb depression,  
367–368  
temperature-control valves, 251  
temperature difference, effect on  
ventilation, 312–313  
temperature drip, 44  
temperature gauge, 19  
temperature-humidity index, 365  
temperature lag, 203, 205  
temperature-limit switches, 121,  
124  
temperature relief valves  
components of, 199–200, 203,  
204  
figures of, 201  
function of, 199  
for gas-fired water heaters, 216,  
219  
importance of, 198  
installation of, 201–202,  
203–204  
rated capacity of, 204, 205

safety requirements for, 199  
symptoms of problems with,  
237, 244  
temperature-sensing element in,  
199–200, 201–202  
temperature rise, in fan motors,  
339  
test plugs, 19  
theaters, fresh air requirements  
for, 288, 385  
theoretical draft, 164  
thermal cutouts, 121, 124  
thermal effect, 282  
and wind effect, 285–287  
thermocouple connections  
for gas-fired pool heater,  
257  
symptoms of problems in, 236,  
275  
in thermoelectric refrigeration  
units, 408  
thermocouple valves, symptoms of  
problems with, 235  
thermoelectric refrigeration,  
397–398, 408  
thermomagnets, 223  
thermometers  
for air temperature, 372–373,  
374  
inline, 23  
in piping diagram, 20–21  
thermostatic expansion valves  
(TXV), 450–453, 493–494  
thermostatic expulsion valves,  
89–90, 92  
illustration of, 93, 94  
thermostatic valves, 212, 213  
thermostats  
for attic fans, 349  
combined with humidistat,  
554–555, 557  
for controlling heat pump  
operation, 501–502  
defrost, 499  
for defrost cycle in heat pumps,  
475  
dew-point, 541

## 672 Index

- thermostats (*continued*)
    - for electric baseboard heaters, 121, 123
    - for electric radiant floor heating systems, 55–56
    - for electric water heaters, 240–241
    - for electronic air cleaners, 554–555, 557
    - for gas-fired pool heater, 258
    - heat anticipator setting, 511
    - for hydronic radiant heating systems, 27–28, 29, 30
    - for instantaneous water heaters, 185
    - maintenance of, 511–513
    - nonprogrammable, 56
      - in piping diagram, 20–21
    - programmable, 55
    - for quick-recovery heaters, 189
    - and refrigeration systems, 437
    - service-light, 501
    - for slow-recovery heaters, 189
    - snap-action, 189
    - for solar water heaters, 247
    - symptoms of problems with, 50, 68, 233, 234, 235, 242–243, 274, 514
    - throttling, 189
      - on wood-burning stoves, 177
    - zone, 26
  - thin-slab construction, 34–35, 36
  - 30-minute cams, 476
  - threaded radiator sections, joining, 80–85
  - three-phase motors
    - ampere ratings for, 335
    - connection diagram for, 338
  - three-way valves, for solar pool heaters, 266–267
  - throttling thermostat, 189
  - time delay, 500
  - time-rise method, 268–269, 271
  - timers, 57
  - time-temperature defrost controls, 499
  - tip speed (TS), 316–317
  - ton of refrigeration, 395
  - total heating load, 26
  - total pressure (TP), 317
  - traps
    - bucket, 138
    - cleanout, 168
    - for radiator steam, 99
    - versus thermostatic expulsion valves, 90
    - for unit heaters, 136
  - triple-venting, 98, 99
  - tubexial fans, 318
  - tubing
    - copper (*see* copper tubing)
    - cross-linked polyethylene (*see* cross-linked polyethylene (PEX) tubing)
    - installing above subfloor, 39–40
    - loop continuity in, 45
    - measuring temperature of water in, 17
    - nonbarrier, 11
    - oxygen barrier (BPEX), 11
    - in radiant heating systems, 7–14
    - return line of, 7
    - spacing of, 45
    - staple-up method for installing, 36, 38–39
    - supply line of, 7
    - symptoms of break in, 51
    - tungsten ionizing wires, 568–569
  - turbine rooms, fresh air
    - requirements for, 288, 385
  - turbine ventilators, 291–293
  - two-stage air cleaners, 553–554, 556
  - two-stage wiring diagram, 123
  - Type L copper tubing, 8–9
- ## U
- U-factor, 387
  - ultrasonic humidifiers, 523
  - unitary system fans, 348
  - unit heaters
    - air stream of, 131, 134
    - components of, 130
    - continuous circulation in, 139

- controls for, 138–140
  - defined, 130
  - fan operation in, 139–140
  - forced-air, 135
  - gas-fired, 140–141, 142–143
  - heat supply from, 130–131
  - horizontal, 131, 135
  - oil-fired, 141, 144
  - pipng connections for, 135–138, 139, 140, 141
  - steam supply to, 137, 139
  - vapor steam system in, 136
  - upward ventilation, 311
- V**
- vacuum
    - greatest area of, 313
    - and inductive action, 283–284
  - vacuum relief valves, 206, 208
  - valves
    - air (*see* air valves)
    - in air conditioners, 458–459
    - automatic air vent, 18
    - automatic pilot, 212, 213–214, 215, 216, 217
    - backflow preventer, 21
    - balancing, 25
    - ball, 19, 21
    - for boilers, 19, 21
    - bypass, 257, 276
    - check, 19–23, 230
    - combination gas, 221–225, 226
    - discharge, 433, 436
    - in domestic hot-water heaters, 197
    - expansion (*see* expansion valves)
    - fill, 20–21
    - float, 452–454, 525
    - float vent, 19
    - flow-control, 19–22
    - functions of, 17–18
    - gas, 257, 258
    - gate, 19, 21
    - globe, 19, 21
    - for heat pumps, 502–503, 504–505
    - for hydronic radiant floor heating systems, 17–25, 47–48
    - isolation, 22–23
    - magnet, 236
    - for manifolds, 16–17
    - manual gas, 214, 217, 223, 224–225
    - in mechanical refrigeration equipment, 458–459
    - mixing (*see* mixing valves)
    - motorized zone, 24–25
    - pilot, 212–217, 236, 515, 516
    - pressure-reducing, 25
    - pressure relief (*see* pressure relief valves)
    - purge, 19, 25
    - for radiators, 86–92
    - for refrigerants, 449–454, 491–493, 494
    - relief (*see* relief valves)
    - reversing, 473, 491–493, 494
    - saddle, 536
    - safety relief (*see* safety relief valves)
    - service, 19, 502–503, 504–505
    - shutoff, 21, 46
    - solenoid, 431, 536
    - steam diverter, 407
    - swing-check, 22, 230
    - temperature-control, 251
    - temperature relief (*see* temperature relief valves)
    - thermocouple, 235
    - thermostatic, 212, 213
    - thermostatic expansion, 450–453, 493–494
    - thermostatic expulsion, 89–90, 92, 93, 94
    - three-way, 266–267
    - vacuum relief, 206, 208
    - water pressure reducing, 19
    - water-regulating, 458–459
    - water-tempering, 206, 208
    - zone, 16–17
    - vaneaxial fans, 318
    - vapor barrier, 46, 47
    - vaporizers, 524–525

## 674 Index

- velocity pressure (VP), 317
  - ventilating systems
    - considerations for, 298
    - localized, 328–332
    - for whole houses, 356–359
  - ventilation
    - air changes required for, 324–325
    - and air leakage, 309–310
    - of attics, 348–354
    - of bathrooms, 356
    - calculating heat gain from, 394
    - versus circulation, 315
    - defined, 281
    - and forces of temperature difference, 312–313
    - of garages, 310–311
    - general, 322
    - general rules for, 312–313
    - importance of, 281
    - and induced draft, 285, 286
    - and inductive action of the wind, 282–285
    - for industrial buildings, 313
    - of kitchens, 311–312, 355–356
    - local, 322, 328–332
    - mean temperature difference in, 296
    - mechanical, 287
    - natural, 282
    - requirements for, 287–289, 384–386
    - thermal effect in, 285–287
    - types of, 282
    - upward versus downward, 311
    - wind effect in, 285–287
    - See also* ventilators
  - ventilation fans, 344, 346
    - for attics, 348–354
    - See also* fans
  - ventilation heat gain, 380
  - ventilators
    - base of, 299–301
    - calculating required number and size of, 307–309
    - capacity of, 296–297
    - dampers for, 304–307
    - energy recovery (ERVs), 356
    - exhaustive capacity of, 307
    - factors for selection of, 296
    - fan, 294–295
    - gravity, 306, 307
    - heat recovery (HRV), 356, 358
    - inlet air openings in, 298–299
    - proper operating conditions of, 308
    - revolving, 290–291
    - ridge, 293–294
    - in roof (*see* roof ventilators)
    - siphonage, 294
    - spacing of, 307, 308–309
    - stack height of, 297
    - stationary-head, 290
    - turbine, 291–293
  - venting systems
    - for gas-fired water heaters, 227–229
    - in hydronic radiant floor heating systems, 32, 33
    - for indoor pool heaters, 272
    - for radiators, 93–94, 96, 98–99
    - regulations for gas-fired water heaters, 226–227
  - vents
    - in radiators, 76–77, 93–94, 96, 98–99 (*see also* radiator valves)
    - symptoms of problems with, 275
  - vertical draft hood, 228
  - vertical drilled port cast burners, 211
  - viscous air filters, 574–575
  - volume of air required, 341
- W**
- wall panel heating systems, 5
  - wall radiators, 73–74
  - warehouses, fresh air requirements for, 288, 385
  - warm-air heating systems, cooling coils in, 417–418, 419
  - water
    - circulating at fixed temperature, 27, 28

- converting from liquid to vapor, 363
- determining circulation rate of, 26
- superheated, 198, 199
- water chillers, 417–418
  - cooling with, 410–411, 412
  - evaporator coil and, 446
- water-cooled condensers, 414, 415–417, 441, 444
- water heaters
  - automatic storage, 180–182, 183, 204, 206
  - Btu output of, 7
  - causes of explosions in, 197–198
  - code requirements for, 230–231
  - combination, 191–192
  - commercial versus domestic, 179
  - direct-fired, 180
  - draft hoods for, 228–229
  - electric, 240–244
  - fuels for, 180
  - function of, 179
  - gas-fired (*see* gas-fired water heaters)
  - heat-control method in, 180
  - heat pump, 190–191
  - hot-water circulating methods in, 230
  - for hydronic radiant floor heating systems, 7
  - indirect, 185–189
  - installation and maintenance
    - checklist for, 232–233
  - instantaneous, 184–185
  - lighting and operating
    - instructions for, 231–232
  - manual, 245–246
  - minimum temperature of, 107
  - most common, 179, 192
  - multicoil, 182–183
  - multiflue, 183–184
  - oil-fired, 182, 183, 238–240, 241
  - placement of flues in, 181, 182, 183
  - power-vent, 227–228
  - quick-recovery, 189
  - recovery rate of, 180
  - requirements for gas supply to, 231
  - safety relief valves in, 197–206
  - service guide for, 232
  - signs of sediment accumulation in, 237
  - slow-recovery, 189
  - solar, 246–247
  - storage tanks for (*see* water storage tanks)
  - for swimming pools (*see* pool heaters)
  - temperature of water in, 195
  - types of, 179–180
  - venting systems for, 227–229
  - water temperature control in, 232
- water pressure
  - reducing valve for, 19
  - regulators for, 23
- water pumps, 190
- water-regulating valves, 458–459
- water sensors, 266
- water-source heat pumps, 483–485
- water storage tanks
  - anodes in, 197
  - antisiphon hole in, 195–196
  - causes of explosions in, 197–198, 199
  - in combination water heaters, 191–192
  - construction details for, 193
  - corrosion in, 193
  - dip tubes in, 194–196, 230–231
  - in electric water heaters, 242
  - fittings for, 194, 195
  - in gas-fired water heaters, 209
  - glass-lined, 193
  - for heat pump water heaters, 190
  - for oil-fired water heaters, 238–239
  - operating life of, 193
  - safety relief valves in, 197–206
  - scale buildup in, 191
  - symptoms of problems with, 243–244

**676 Index**

- water temperature
    - control for, 232
    - in oil-fired water heaters, 238
  - water-tempering valves, 206, 208
  - water valves, symptoms of
    - problems with, 536
  - water vapor
    - latent heat of, 368
    - saturated, 364
  - water-wash controls, 561–563
  - waterways, threaded, 80–85
  - watt output, calculating change in, 125
  - Weil-McLain ratings, 77–78
  - wet-bulb depression, 367–368
  - wet-bulb temperature, 365–367, 373
  - wet installations
    - defined, 6
    - for hydronic radiant floor heating systems, 33–34
    - thin-slab construction, 34–35, 36
  - whole-house ventilation, 356–359
  - windbands, 296
  - wind effect, 285–287
  - window radiators, 73–74
  - window-ventilated buildings, 312
  - wood-burning ranges, 176
  - wood-burning stoves, 174
  - wood heaters, 177
- Y**
- year-round air-conditioning, 412, 413
- Z**
- zone manifold, 17
  - zone thermostat, 26
  - zone valves, 16–17