

Index

A

- absolute humidity, 459, 472
- absolute pressure, 459
- absolute zero, 5, 6–7, 459, 480
- absorption, 459
- absorption central air-conditioning system, 331, 338–341, 366
 - and compression system compared, 338–339, 366
 - cycle of operation, 339–341
- acceleration, 459
- AC motor controls, 413–418
- accumulator, 459
- acrolein, 152, 459
- activated alumina, 459
- adiabatic, 459
- adiabatic process, 459
- adsorbent, 459
- adsorption-type dehumidifiers, 76–77
- aeration, 459
- agitation, 459
- air
 - ambient, 459
 - circulation of, 1, 2, 459
 - cleaning and filtering of, 1, 2–3, 61–62, 97. *See also* air filters
 - components of, 1–2, 12
 - conditioning of, 1
 - cooling, 1
 - defined, 1
 - dehumidifying, 1, 15, 27, 73–74, 98, 467
 - dry, 19, 461
 - fresh, requirements for, 57–58
 - heating, 1
 - humidifying, 1, 15, 27, 472
 - impurities, removal of, 2
 - moisture in, 15. *See also* humidity
 - recirculated, 461
 - return, 461
 - saturated, 461
 - standard, 461
 - volume of, required, 58–59, 90, 91
 - water vapor in, 15
- airborne diseases, 60
- air changes, 459
- air circulation, 1, 2, 459
- air cleaner, 2, 460
- air-cleaning equipment, 97
 - classifications of, 61–62
- air conditioner(s)
 - compressors for, 171–172, 176–215
 - condensers, 173, 214, 217–239
 - cycle of operation, 214–215
 - defined, 460
 - economic considerations and, 29
 - efficiency mandates for, 189
 - electrical components of, 171, 172
 - evaporators for, 173, 241–271
 - expansion valves, 174
 - heat loss in selection of, 29, 51
 - mechanical components of, 171–174, 214
 - nonportable, 357–361
 - receivers, 173, 214
 - refrigerant controls, 174, 214, 245–251
 - refrigerants, selection of, 175–176
 - refrigeration cycle, 174–175
 - room. *See* room air conditioners
 - size of, calculating, 11, 29, 51
 - suspended-type, 361–363
 - troubleshooting, 140–143, 207–214, 363–366, 444–450
- air conditioning
 - air circulation and, 2
 - air-mass modification, adjustments for, 326
 - air moisture and, 15
 - atmospheric conditions affected by, 1, 12, 15

482 Index

- air conditioning (*continued*)
 - automatic, 290, 308, 462
 - automobile, 369–396
 - building materials and choice of, 30–51
 - central-fan system, 460
 - controls, 289–309
 - defined, 1, 460
 - elevation, adjustments for, 326
 - energy consumption
 - considerations, 328
 - indoor design conditions, 311–312
 - maintenance of, 431–451
 - motors and motor controls, 399–428
 - outdoor design conditions, 312–325, 328
 - properties underlying, 3–7
 - unit, defined, 460
 - vegetation, adjustments for, 326
 - water-cooled, winter shutdown of, 204–205
 - year-round central, 331–366, 460
- Air-Conditioning Contractors of America (ACCA), 453
- air-cooled condenser(s), 217–218, 238, 279–280
 - head-pressure controls, 230–232
 - placement of, 217
 - pressure stabilization in, 230–232
 - types of, 217
- air cooler/cooling, 460
- air diffuser, 460–461
- air ducts
 - air velocities, 60, 80, 81
 - console air conditioners, installing, 119–122
 - defined, 468
 - design of, 77–79
 - heat gains in, 79–80
 - location of, 60
 - resistance in, 59, 85–88, 97
 - shape of, 85–86
 - sizing, 80–85, 97
- air-duct ventilation systems, 77–88
 - air velocities, recommended, 80, 81
 - duct design, 77–79
 - heat gains in ducts, 79–80
 - resistance losses in, 85–88, 97
 - sizing calculations, 80–85
 - suitable duct velocities, 80
- air filters, 60–69, 97
 - absorbers, 63
 - central air-conditioning, 335
 - classification of, 61–62
 - dry, 2, 12, 62–63, 97
 - dry plate, 62
 - electronic, 12
 - flushing-type, 65
 - function of, 60
 - immersion-type, 64–65
 - inspection of, 137
 - installation of, 68–69
 - manually cleaned, 64
 - need for, 61
 - purpose of, 12
 - requirements for, 68
 - for suspended-type air conditioners, 383
 - wet (viscous), 2, 64–67, 97
 - wet replacement-type, 64
- air filtration, 60–61, 97
- air humidification, 69
- air infiltration, 19, 27, 29, 53, 461, 473
- air leakage, 53
- air-mass modification, 326
- air moisture
 - grains of moisture, 16, 27
 - and rate of evaporation, 16
 - specific volume, 17
 - See also* humidity
- Air Movement and Control Association (AMCA) International, Inc., 453
- air-movement factor, 17
- air-operated humidifiers, 72–73
- air purifiers, 66–67
- air-supply system, central air conditioning systems, 332

- air volume required, 58–59, 90, 91
 - air washer(s), 70, 98, 335, 461
 - air washing, 2–3
 - alcohol thermometer, 17
 - algae growth, treating, 276, 287
 - altitude, 1, 19, 27, 326
 - ambient temperature, 273, 461
 - American Institute of Architects (AIA), 453
 - American National Standards Institute (ANSI), 454
 - American Society of Heating and Ventilating Engineers, 68, 93
 - American Society of Heating, Refrigeration, and Air Conditioning Engineers (ASHRAE), 311
 - ammonia, 153, 166
 - first aid for exposure to, 168
 - ammonia machine, 461
 - analyzer, 461
 - anemometer, 461
 - antifreeze, 204, 461–462
 - artificial cold, properties
 - underlying the production of, 3–7
 - atmospheric condenser, 462
 - atmospheric conditions, 1, 12
 - measuring. *See* psychrometry
 - atmospheric pressure, 8–9, 10, 13
 - defined, 462
 - standard at sea level, 9, 13, 19, 27
 - atomize, 462
 - attic fans, 94
 - installation of, 95–97
 - automatic air conditioning, 290, 308, 462
 - automatic expansion valve(s), 139, 301
 - defined, 462
 - function of, 174, 300, 308–309
 - automatic viscous filters, 64–67
 - automobile air-conditioning, 369–396
 - air distribution, 384, 386
 - air output, 385–386
 - components of, 369, 370, 375–384, 395
 - compressor, 372, 375–376, 395
 - compressor clutch, 387, 396
 - compressor malfunction, 386–387
 - condenser, 376, 387, 396
 - controls, 384, 386
 - cooling, malfunctions of, 385
 - evaporator, 380, 388, 396
 - hot-gas bypass-valve control, 371, 373
 - installation of, 389–391, 395
 - magnetic clutch control, 369, 372, 381–382, 395
 - operation of, 373–375
 - receiver-dehydrator, 376–377
 - refrigerant-flow control, 369–371, 374, 395
 - refrigerant lines, 388
 - refrigerant used in, 162, 373, 388
 - service and maintenance, 384–389
 - sight glass, use of for diagnosis, 389
 - solenoid control, 380–381
 - suction pressures, checking, 386
 - suction-throttle valve, 382–384, 388, 396
 - temperature controls, 369, 395
 - thermostat, 369
 - thermostatic expansion valve, 377–380, 387–388, 396
 - troubleshooting, 392–394
- B**
- back pressure, checking, 434
 - bacteria, 1, 12, 60
 - baffle, 462
 - balanced pressure, 462
 - barometer, 10
 - defined, 8, 13, 462
 - using, 8–9
 - barometric pressure, 9, 10, 27
 - belt drives, motors, 215, 422
 - blast coils, 244

484 Index

- blast heater, 462
- bleeder, 462
- bleeder shell-and-tube condenser, 219
- BOCA International, Inc. 456
- body heat, 19, 27
- boiler, 462
- boiler horsepower, 462
- boiling point, 7, 15, 27
 - defined, 462
 - Freons, 156–157
 - refrigerants, 147, 148, 152, 154, 245
- bore, 462
- boxed-in fans, 95
- Boyle and Charles, combined law of, 6
- Boyle's law, 6
- brine, 462
- brine refrigeration systems, 154–155, 241, 242, 462
- British thermal unit (Btu), 4, 10, 27, 463
- building materials, effect of on air-conditioning systems, 30–51
- butane, 463
- C**
- calcium chloride (CaCl₂), 154–155, 463
- calcium sulfate, 463
- calibration, 463
- calorie, 463
- capacitor motors, 91–92, 133–134
- capacitors, 91, 411–412, 474
- capacitor-start motors, 407–408, 428
- capacity
 - compressor, 205
 - cooling, 103
 - evaporator, 251, 252, 269, 271
 - refrigerant controls, 251
 - refrigerant cylinders, 167–168
 - refrigeration, 10–12, 463
 - room air conditioners, 103–104
 - ventilator, 56
- capacity reducer, 463
- capillarity, 463
- capillary tube(s), 305, 309, 463
- carbon dioxide, 1, 12, 154, 166
- carbon dioxide ice, 463
- carbon monoxide, 1, 2, 12
- carbon tetrachloride (CCl₄), 214
- Carnot cycle, 163
- casement windows, installing air conditioners in, 111–115
- Celsius scale
 - converting to Fahrenheit, 7–8
 - defined, 7, 463
- central air-conditioning. *See* year-round central air conditioning
- centrifugal-and-turbine fans, 334, 335
- centrifugal compressor, 171, 192–193, 195–198, 215
 - component parts of, 195
 - construction features, 195–196
 - defined, 192, 463, 464
 - lubrication system, 196–198
 - uses of, 192–193, 195
- centrifugal fans, 89, 95, 98, 469
- centrifuge, 463
- change of air, 464
- change of state, 464
- charge, 464
- Charles, law of, 5
- check valves, 267–269, 271
- chilling units, 247–249
- chimney effect, 464
- chlorofluorocarbon compounds (CFCs), 147–148.
 - ban on use of, 148
 - See also* Freon family of refrigerants
- choke coil, 127
- circulating fans, 94
- class-A–D motors, 400–401
- class 1–3 refrigerants, 150
- cleaning
 - air, 1, 2–3, 61–62, 97
 - dry filters, 63
 - compressors, 214

- condensers, 232, 233–235, 239
- inhibitor powder, 234
- clearance, 464
- climatic conditions
 - and individual comfort levels, 25, 26–27
 - in U.S., by state, 314–325
- clouds, 15
- coefficient of expansion, 464
- coefficient of heat transfer, 251, 270
- coefficient of performance
 - heat pump, 464
 - refrigerants, 163–164
- coil(s), 244, 464. *See also* cooling coils; heating coils
- coiled evaporator, 241, 243–244
- cold storage, 464
- combination gages, 437
- combined law of Boyle and Charles, 6
- comfort
 - air moisture and, 15, 27
 - atmospheric conditions affecting, 1
 - designing for, 311–312, 326–328
 - climatic conditions and, 25, 314–325
 - recommended indoor temperatures for, 25–27
 - temperature-humidity index and, 18
- comfort chart, 25–27, 464
 - optimum comfort line, 26–27
- compound gages, 10, 12, 436
- compound-wound motors, 399, 425
- compression process, 175, 215
- compression system, 464
- compressor(s)
 - amperage, 139
 - automobile air-conditioning, 375–376, 395
 - booster, 465
 - capacity, 205
 - centrifugal, 171, 192–193, 195–198, 215, 463, 464
 - classification of, 171–172, 176–177, 214, 215
 - cleaning, 214
 - closed-type, 178
 - clutch, 387, 396
 - components of, 172, 214
 - connecting rods, 181, 182, 465
 - cooling, 184
 - crankshafts, 181–183
 - defined, 464
 - flowback protection, 199–200
 - foundation, 198
 - function of, 171, 176, 214
 - hermetic, 178, 179, 184, 215, 472
 - installation and maintenance of, 198–205
 - knocks, 202
 - lubrication, 184
 - malfunction of in automobile air-conditioning, 386–387
 - mechanical efficiency, 205
 - motor and belts, installation and maintenance of, 135–137, 199
 - motor controls, 402–421, 428
 - open-type, 178, 464
 - operation of, 214–215
 - performance, 205
 - pistons and piston rings, 178–181
 - reciprocating, 125, 153, 171, 177–184, 215, 465
 - removal of, 202–203
 - replacement of, 203
 - room air conditioner, 101, 103, 124–125
 - rotary, 153, 171, 184–189, 215, 465
 - scroll, 189–192, 193
 - shaft-seal, 183–184, 201
 - sizes, 171, 214
 - startup, 203
 - stuck-up, 202
 - testing, 134–135, 205–106
 - tight, 202
 - troubleshooting, 207–213

486 Index

- compressor(s) (*continued*)
 - valves, 178, 200–201, 435–436, 444
 - volumetric efficiency, 205
 - winter shutdown of, 204–205
- compressor clutch, 387, 396
- compressor valves, 178, 200–201
 - checking, 435–436, 444
- condenser(s)
 - air-cooled, 173, 217–218, 238, 279–280
 - atmospheric, 462
 - automobile air-conditioning, 376, 387, 396
 - charging, 235
 - classification of, 217, 238
 - cleaning, 232, 233–235, 239
 - defined, 465
 - evaporative, 235, 239
 - flushing, 235
 - function of, 173, 214, 217, 238
 - gravity and forced circulation, 236–237
 - head-pressure controls, 228–232
 - installation of, 232–233
 - maintenance of, 232–237, 239
 - outdoor units, 237–238
 - placement of, 217, 229
 - room air conditioner, 101, 103
 - scale formation, removing, 236
 - types of, 173, 217
 - water-cooled, 173, 219–227, 238
 - water sources, 273, 287
- condensing
 - defined, 465
 - point of, 6
 - pressure, 159, 228
 - process, 175, 215
- condensing unit
 - defined, 465
 - cycling, 255–256
 - sealed, 465
- condensing-water controls, 421
- conduction
 - defined, 3, 12
 - thermal, 465
- conductivity, thermal, 465
- conductor, electrical, 465
- congealing tanks, 155
- connecting rods, 181, 183, 465
- conservation of energy, law of, 6
- conservation of matter, law of, 5–6
- console air conditioners, installing
 - self-contained units, 116–119
 - window-mounted units, 119–122
- constant-pressure valve, 465
- constant-speed motor, 92
- constant-temperature valve, 465–466
- control(s)
 - automatic, 290, 308
 - automobile air-conditioning, 384
 - dampers, 299, 308
 - defined, 466
 - devices for, 290–297, 308
 - differential of, 467
 - duct thermostats, 294
 - head pressure, 228–232
 - high-pressure, 466
 - low-pressure, 466
 - hygrostat, 295–297, 308
 - immersion thermostats, 295
 - limit, 297–298, 308
 - manual, 289–290, 308
 - pressure regulators, 297, 308
 - purpose of, 308
 - refrigerant, 174, 214, 245–247, 300–309
 - relays, 299–300, 308
 - room thermostats, 291–294
 - semiautomatic, 290, 308
 - suspended-type air conditioners, 363
 - temperature, 466
 - thermostats, 291–294, 308
 - twin-type thermostats, 294, 295, 296
 - types of, 289–290
 - valves, 298–299, 308
- control board, 335–336
- control systems, checking, 386
- control valves, 298–299, 308

- convection
 - defined, 3, 12, 466
 - forced, 466
- cooling
 - capacity, 103
 - cycle of, 342
 - evaporative, 469
 - process, steps in, 175
 - reciprocating compressors, 184
- cooling coils, 334
- cooling effect, measurement of, 10
- cooling ponds, 278, 287
- Cooling Technology Institute (CTI), 456
- cooling tower, 466
- cooling unit, 466
- cooling water, 466
- cooling water circuits, 220
- copper plating, 466
- corrosive, 466
- counter flow, 466
- crankcase pressure-regulating valves, 305–306, 309
- crank integral, 181
- crankshafts, 181–183
- critical pressure, 7, 466
- critical temperature
 - defined, 7, 466
 - of refrigerants, 160
- critical velocity, 467
- crohydrate, 467
- current-and-thermal-type overload protector, 419, 428
- current supply, testing, 131
- cut-in, 467
- cycle
 - Carnot, 163
 - cooling, 342
 - defined, 467
 - defrost, 346, 467
 - heating, 341–342
 - refrigeration, 165, 174–175, 467
- D**
- Dalton's law of partial pressure, 467
- dampers, 299, 308
- defrosting,
 - automatic, 255, 432
 - defined, 467
 - manual, 255–256
- degree day, 467
- dehumidification, 73, 98
- dehumidifier(s), 73–77, 98
 - adsorption-type, 76–77
 - based on honeycomb desiccant wheel principle, 76–77
- controls, 75–76
 - defined, 467
 - electric, 74–75
 - humidistat, 75–76
 - operation of, 74, 75
 - performance of, 75
 - stationary-bed type, 77, 78
- dehumidify, 15, 27, 73–74, 467
- dehydrators, 264–265, 270, 467
- density, 467
- design conditions
 - air-mass modification, adjustments for, 326
 - altitude, adjustments for, 326
 - frequency of occurrence levels, 326
 - indoor, 311–312, 328
 - outdoor, 312–325, 328
 - summer, 313
 - U.S. climate and, 314–325
 - vegetation, adjustments for, 326
 - weather-oriented, 326–328
 - winter, 312–313
- dew point, 17, 27, 467
- dew-point temperature, 17
- dichlorodifluoromethane, 147, 160
- differential (of a control), 467
- diffusion, 58
- direct connected, 467
- direct drives, motors, 215
- direct expansion, 468
- discharge lines, 283–284, 288
- discharge valves, 178
- displacement, 468
- distribution, 1, 12

488 Index

- double-hung windows, installing
 - air conditioners in, 106–111
- double-pipe condenser, 219
- double-seated valves, 299, 308
- double-tube condenser, 219, 220–224
- drier(s), refrigerant, 263–264, 270, 468. *See also* dehydrators
- dry air, 19, 461
- dry-bulb temperature, 16, 17
- dry-bulb thermometer, 10, 16
- dry capillary-tube system, 305
- dry evaporator, 173, 468
- dry-expansion evaporators, 247, 248, 249–251, 269
- dry filters, 2, 12, 62–63, 97
- dry plate, 62
- dry-steam humidifier, 71–72, 73, 74
- duct thermostats, 294
- ducts. *See* air ducts
- dust, 1, 2, 12
 - components of, 60, 97
 - defined, 468
 - effect of on health, 60–61, 97
 - studies of, 61
 - sources of, 60–61, 97
 - types of, 61
- E**
- eccentric shaft, 182
- economizer, 468
- effective temperature, 17
- efficiency
 - compressor, 205
 - evaporator, 248
 - heat-transfer, 243
 - loss of by superheating, 160
 - mechanical, 90, 205, 468
 - Seasonal Energy Efficiency Ratio (SEER), 189, 192
 - static, 90
 - test of, 205–206
 - volumetric, 205, 468
- ejector, 468
- electrically-operated humidifiers, 71–72
- electrical system, room air
 - conditioners, 122–129
 - components, 124–127
 - cords and plugs, 123
 - fan motors, 127–128
 - National Electrical Code for, 122
 - power supply, 122
 - thermostats, 128–129
 - troubleshooting, 426–428
 - unit control switch, 129
- electrical testing, 130–135
 - capacitor, 133–134
 - compressor motor overload, 134–135
 - compressor motor relay, 134
 - current supply, 131
 - fan motors, 131–133
 - relay check, 134
- electric dehumidifier, 74–75
- electronic filters, 12
- electronic leak detector, 442–443
- element, bimetallic, 468
- elevation. *See* altitude
- eliminators, 335
- emulsion, 468
- engine, 468
- English scale. *See* Fahrenheit scale
- entropy, 468
- equalizer, 468
- ethyl chloride, 152–153
- eutectic solution, 469
- evaporating pressure, Freons, 159–160
- evaporation, and air moisture, 16
- evaporative condensers, 224, 226–227, 239
 - cleaning, 235
 - defined, 224, 469
 - head-pressure controls, 229–230, 231
 - operation of, 226–227
 - pipng to and from, 230, 231
 - placement of, 220
 - schematic view of, 227
- evaporative cooling, 469
- evaporative-type humidifier, 71

- evaporator(s)
 - area of, 252–253
 - automobile air-conditioning, 380, 388, 396
 - capacity, 251, 252, 269, 271
 - check valves, 267–269, 271
 - coiled, 241, 243–244
 - cycling the condensing unit, 255–256
 - defined, 469
 - dehydrators, 264–265, 270
 - driers, 263–264, 270
 - dry, 173, 468
 - dry-expansion, 247, 248, 249–251, 269
 - efficiency of, 248
 - exterior conditions, 253
 - finned, 241, 242, 269
 - flooded, 173, 247, 248, 269, 470
 - function of, 173, 215, 241
 - heat exchangers, 257–260, 270
 - K factor calculations, 251–252, 270
 - maintenance, 255–257
 - mufflers, 266, 270
 - oil separators, 260–263, 270
 - operating principle, 269
 - operation of, 241, 269
 - pipe-coil installation, 249
 - plain-tubing, 241, 242–243, 269
 - plate, 241, 242
 - prime-surface, 242
 - room air conditioner, 101
 - strainers, 265–266, 270
 - subcoolers, 266–267, 268, 271
 - surface-area determination, 253–255
 - surge drums, 260, 270
 - temperature, 138–139
 - time clocks, 256–257, 270
 - types of, 173, 241–242, 247–248, 269
 - wet-expansion, 247, 248, 269
 - evaporator pressure-regulating valve, 306, 307, 309
 - exciter, 404
 - exhaust fans, 93–94
 - expansion valves
 - automatic, 139, 174, 300, 301, 308–309, 462, 469
 - defined, 175
 - function of, 174
 - thermostatic, 174, 300–303, 309, 377–380, 387–388, 396, 469, 478
 - extended surface, 469
 - external equalizer, 469
- F**
- Fahrenheit scale
 - converting Celsius to, 7–8
 - defined, 7, 469
 - fan(s)
 - air volume, 90, 91
 - for central air-conditioning, 334–335
 - applications of, 93–94
 - attic, 94, 95–97
 - boxed-in, 95
 - centrifugal, 89, 95, 98, 469
 - centrifugal-and-turbine, 334, 335
 - circulating, 94
 - defined, 469
 - drive methods, 91–92
 - exhaust, 93–94
 - horsepower requirements, 90
 - inlet area, 90
 - kitchen, 94
 - mechanical efficiency, 90
 - motors, selecting, 91–92
 - motors, testing, 131–133
 - noise, decreasing, 94–95
 - operation of, 94–95, 97
 - outlet area, 90
 - performance parameters, 89–90
 - power input/output, 90
 - propeller, 89, 98, 334–335, 469
 - room air conditioners, 127–128
 - selection of, 92–93
 - speeds, 91, 98
 - static efficiency, 90
 - static pressure, 90
 - total pressure, 90

490 Index

- fan(s) (*continued*)
 - tubeaxial, 89, 98, 469
 - types of, 89
 - vaneaxial, 89, 98
 - velocity pressure, 90
 - volume handled by, 89
- Federation of European Heating and Air-Conditioning Associations, 457
- filler panel, 113
- filters
 - absorbers, 63
 - central air-conditioning, 335
 - classification of, 61–62
 - defined, 470
 - dry, 2, 12, 62–63, 97
 - dry plate, 62
 - electronic, 12
 - flushing-type, 65
 - function of, 60
 - immersion-type, 64–65
 - inspection of, 137
 - installation of, 68–69
 - manually cleaned, 64
 - need for, 61
 - purpose of, 12
 - requirements for, 68
 - for suspended-type air conditioners, 363
 - wet (viscous), 2, 64–67, 97
 - wet replacement-type, 64
 - See also* strainers
- finned evaporators, 241, 242, 269
- finned-tube condenser, 217
- first aid, for exposure to refrigerants
 - ammonia fumes, 168
 - Freons, 168
 - methyl chloride, 168
 - sulfur dioxide
- flammability
 - defined, 470
 - of early refrigerants, 147
 - of Freons, 158
- flare fitting, 470
- flash gas, 470
- float valves, 303–305, 470
- flooded atmospheric condenser, 219
- flooded capillary-tube system, 305
- flooded evaporator, 173, 247, 248, 269, 470
- flue effect, 54–55, 97
- fluid, 470
- flushing-type air filters, 65
- foaming, 470
- fog, 15
- freezing point, 7, 160, 470
- freeze-up, 470
- Freezol, 154
- Freon family of refrigerants, 147, 156–160, 169
 - amount of liquid refrigerant circulated, 158
 - boiling point, 156–157
 - chemical properties of, 157
 - common types of, 156–157
 - condensing pressure, 159
 - early types of, 147
 - environmental effects of, 148, 157, 169
 - evaporating pressure, 159–160
 - first aid for exposure to, 168
 - flammability, 158
 - handling of, 166
 - leaks, testing for, 441–442
 - physical properties of, 157–158
 - volume (piston) displacement, 158–159
- Freon-11, 156
- Freon-12, 156, 158, 159, 162, 281, 373, 470
- Freon-13, 156
- Freon-21, 156
- Freon-22, 156–157, 281
- Freon-113, 157
- Freon-114, 157
- Freon-115, 157
- Freon-502, 157
- frequency of occurrence levels, 326
- fresh-air requirements, by building/room type, 57–58
- frostback, 470

- frostbite, 166, 168
 fumes, 2
 furnace, 470
 fusible plug, 470
- G**
- gage(s), 436–437
 combination, 437
 compound, 10, 12, 436
 defined, 471
 high-pressure, 10, 436
 low-pressure, 10, 436
 pressure, 10, 12, 245, 436–437, 475
 gage pressure, 9, 436
 gas, 1, 4, 12, 471
 gas-compression air-conditioning system, 331, 366
 generator, 471
 glossary of terms, 459–480
 grain, defined, 16, 27
 grains of moisture, 16, 27
 gravity, specific, 471, 477
 grille, 471
- H**
- halide-torch leak testing, 441–442, 451, 471
 head pressure
 air-cooled condensers, 230–232
 checking, 432–433, 451
 evaporative condensers, 229–230, 231
 refrigerants, 160
 water-cooled condensers, 228–229
 heat
 body, 19, 27
 defined, 12, 471
 from electrical apparatus, 19, 27
 latent, 4, 13, 18–19, 473
 latent heat of evaporation, 5, 13, 162–163, 473
 latent heat of fusion, 4–5, 13
 mechanical equivalent of, 474
 pressure–temperature relationship, 5–7
 sensible, 4, 12, 18–19, 471
 specific, 4, 12, 163, 471, 477
 superheat, 5, 13, 245–247, 478
 total, 18–19, 27, 479
 transfer of, 3, 12, 243, 270
 heat-anticipation device, 294
 heat exchangers, 248, 257–260, 270
 heat gain
 in air ducts, 79–80
 preventing, 286
 heating coils, 333, 361
 heating cycle, 341–342
 Heating, Refrigeration, and Air Conditioning Institute of Canada (HRAI), 455
 heating system
 defined, 471
 electric, 471–472
 steam, 472
 vacuum, 472
 warm-air, 472
 heat leakage, 29–51
 brick veneer, frame walls, 50
 brick veneer on hollow tile wall, 37
 brick wall, 4-in cut stone, 41
 calculating, 30, 51
 cinder and concrete block wall, 35
 cinder and concrete block wall, brick veneer, 36
 concrete floors, on ground, 46
 concrete floors and ceilings, 47–48
 concrete wall, brick veneer, 33
 concrete wall, exterior stucco finish, 32
 concrete wall, 4-in cut stone, 34
 concrete wall, no exterior finish, 31
 formula for, 29
 frame floors and ceilings, no fill, 44
 frame floors and ceilings, with fill, 49

492 Index

- heat leakage (*continued*)
 - hollow tile wall, 4-in cut-stone veneer, 38
 - hollow tile wall, stucco exterior, 39
 - interior walls and plastered partitions, no fill, 44
 - limestone or sandstone wall, 40
 - masonry partitions, 45
 - reference tables for determining, 30–50
 - solid brick wall, no exterior finish, 42
 - specifying, 29, 51
 - wood siding clapboard frame or shingle walls, 43
 - heat leveling device, 294
 - heat loss
 - in air conditioner selection, 29, 51
 - caused by leakages. *See* infiltration
 - estimating maximum, 29, 51
 - through surfaces, 29
 - heat of fusion, 471
 - heat of vaporization, 471
 - heat pump(s), 341, 464, 471. *See also* reverse-cycle air-conditioning system
 - heat-pump principle, 306
 - heat transfer, 3, 12
 - conduction, 3, 12
 - convection, 3, 12
 - efficiency, increasing, 243
 - equation, 270
 - radiation, 3, 12
 - hermetically sealed unit, 178, 179, 184, 215, 472
 - high-pressure cutout, 472
 - high-pressure gages, 10, 436
 - high side, 472
 - high-side float valve, 305, 472
 - hold over, 472
 - holdover tanks, 155
 - honeycomb desiccant wheel
 - principle, 76–77
 - horsepower
 - calculating, 423–425
 - defined, 472
 - power-conversion factors, 425
 - required for fans and blowers, 90
 - hot-gas bypass-valve control, automobile air-conditioning, 371, 373
 - HP-20 model, scroll compressor, 192, 193
 - HS-22 model, scroll compressor, 192, 194
 - humidifier(s), 69–73, 98
 - air-operated, 72–73
 - air-washers, 70, 98
 - defined, 69, 472
 - dry-steam, 71–72, 73, 74
 - electrically-operated, 71–72
 - evaporative-type, 71
 - pan-type, 71
 - purpose of, 98
 - types of, 69
 - humidify, 15, 27, 472
 - humidistat, 71, 75–76, 295, 472. *See also* hygrostat
 - humidity, 1, 12
 - absolute, 459, 472
 - and comfort levels, 25–26
 - control methods, 69–77, 290
 - relative, 9, 15–18, 27, 311–312, 328, 473
 - specific, 473
 - HVAC Excellence, 454
 - hydrocarbons, 473
 - hydrofluorocarbons (HFCs), 162, 169
 - hydrolysis, 473
 - hygroscope, 473
 - hydrostatic pressure, 473
 - hygrostat, 72, 295–297, 308, 336. *See also* humidistat
- I**
- ICC Evaluation Services, Inc., 456
 - ice-melting equivalent, 473
 - immersion thermostats, 295
 - immersion-type air filters, 64–65

- indirect cooling system, 473
- indoor design conditions, 311–312, 328
- inductive reactance, 401
- infiltration, 19, 27, 29, 53, 461, 473
- inhibitor powder, 234
- installation
 - of air filters, 68–69
 - of automobile air conditioner, 389–391, 395
 - of attic fans, 95–97
 - in casement window, 111–115
 - of compressors, 199, 203
 - of condensers, 232
 - of console units, 116–122
 - in double-hung window, 106–111
 - of reverse-cycle units, 346–347, 348, 349
 - support brackets, 115
 - of window air conditioners, general, 104–105
 - of window-mounted console air conditioners, 119, 120
- insulation, 286–287, 473
- International Institute of Ammonia Refrigeration (IIR), 455
- irritant refrigerant, 473
- isobutane, 154, 473
- K**
- K* factor calculations, evaporators, 251, 270
- kilowatt, 473
- kitchen fans, 94
- knocks, compressor, 202
- L**
- lag of temperature control, 473
- latent heat, 4, 13, 18–19, 473
- latent heat of evaporation, 13
 - defined, 5, 473
 - refrigerants, 162–163
- latent heat of fusion, 4–5, 13
- laws of pressure–temperature relationship
 - Boyle’s law, 6
 - combined law of Boyle and Charles, 6
 - critical pressure, 7
 - critical temperature, 7
 - law of Charles, 5
 - law of conservation of energy, 6
 - law of conservation of matter, 5–6
 - point of liquefaction or condensing, 6
- leakage
 - air, 53
 - heat, 29–51
 - refrigerant, 139, 151, 152, 153, 154
 - around shaft seals, 201
 - system, room air conditioners, 137
- leak detection, 473
 - electronic device for, 442–443
 - halide-torch method, 441–442, 451, 471
- limit controls, 297–298, 308
- liquefaction, point of, 6
- liquid, 4, 474
- liquid lines, 281–282, 474
- liquid receiver, 474
- load, 474
- low-pressure control, 474
- low-pressure gages, 10, 436
- low side, 474
- low-side float valves, 303–304, 474
- lubrication
 - centrifugal compressors, 196–198
 - oil circulation, 283, 287
 - reciprocating compressors, 184
- M**
- magnetic-clutch control, automobile air-conditioning, 369, 372, 381–382, 395
- main, 474

494 Index

- maintenance
 - adding oil, 439
 - adding refrigerant, 437–439
 - of automobile air-conditioning, 384–389
 - back pressure, checking, 434
 - combination gages, use of, 436
 - compressor, checking, 444
 - compressor, malfunctioning, 386–387
 - of compressor valves, 435–436
 - of condensers, 232–237, 387
 - of console air conditioners, 119
 - evacuating the system, 443–444
 - of evaporators, 255–257, 388
 - gages, use of, 436–437
 - general procedures for, 431–432, 450–451
 - head pressure, checking, 432–433, 451
 - leaks, testing for, 441–443, 451
 - of motors, 422–423
 - purging the system of
 - noncondensables, 441, 451
 - refrigerant charge, 434–435
 - refrigerant lines, 388
 - removing oil, 439
 - removing refrigerant, 439
 - of reverse-cycle units, 346–347
 - of room air conditioners, 129–139
 - sight glass, use of, 389
 - suction pressure, checking, 386, 433
 - suction-throttle valve, 388
 - system pump-down, 440–441
 - of thermostatic expansion valve, 387–388
 - See also* troubleshooting
- manometer, 474
- manual control, 289–290, 308
- manually cleaned filters, 64
- measurements and measuring devices
 - barometer, 8–9, 10, 13, 462
 - British thermal unit (Btu), 4, 10, 27, 463
 - pressure gages, 10, 12, 245, 436–437, 475
 - refrigeration capacity, 10–12
 - relative humidity, 16
 - sling psychrometer, 9–10, 11, 16, 27
 - thermometer, 7–8, 13, 16, 17, 478
- mechanical efficiency
 - compressor, 205
 - defined, 474
 - fan, 90
- mechanical equivalent of heat, 474
- mechanical ventilation, 97
 - defined, 53, 58
 - duct-system resistance, 59–60
 - and natural ventilation
 - compared, 58
 - volume of air required, 58–59
- mercury thermometer, 17
- methyl chloride, 151–152
 - defined, 474
 - first aid for exposure to, 168
- micron (μ), 474
- mixing chamber, 332–333
- moisture condensation,
 - preventing, 286
- Mollier chart, 474
- motion, 1, 12
- motor(s)
 - alternating current (AC), 399, 428
 - belt drives, 215, 422
 - capacitors, 91, 411–412, 474
 - capacitor-start, 407–408, 428
 - classes, compared, 400–401
 - compound-wound, 399, 425
 - compressors, 199
 - constant speed, 92
 - controls. *See* motor controls
 - defined, 474
 - direct current (DC), 399, 425
 - direct drives, 215
 - exciter, 404
 - fan, 127–128
 - horsepower calculations, 423–425

maintenance, 422–423
 oiling of, 137
 permanent split-capacitor,
 408–409, 428
 permanent split-phase capacitor,
 127
 polyphase, 399–406, 428
 positive, 299
 power source, 399
 pull-in torque, 417
 repulsion induction, 409, 428
 repulsion-start induction,
 409–410, 428
 reversing, 299
 series-wound, 399, 425
 shaded-pole, 91, 127
 shunt-wound, 399, 425
 single-phase, 91, 399, 406–412,
 428
 slip-ring, 92
 split-phase, 91, 406–407, 428
 squirrel cage, 400–401, 402,
 428
 synchronous, 403–406, 428
 torque, 416, 417
 troubleshooting, 425,
 426–428
 two-value capacitor, 408
 types used for air-conditioning,
 399
 voltage, 399
 windings, 417
 wound-rotor, 401–403, 428
 motor controls
 AC, 413–418
 compressor, 420–421
 condensing-water, 421
 pressure, 421
 single-phase, 418–420
 solenoid valves, 421, 428
 squirrel cage motors, 413–414
 synchronous motors, 416–418
 temperature-motor, 420–421
 wound-rotor motors, 414–416,
 417
 mufflers, 266, 270
 multi-blade dampers, 299

N

National Association of Fan
 Manufacturers, 89
 National Electrical Code, room-air
 conditioners, 122
 National Electrical Manufacturers'
 Association (NEMA), 400
 National Fire Protection
 Association (NFPA), 455–456
 natural ventilation, 53–56, 97
 combined wind and temperature
 forces, 55
 defined, 53
 and mechanical ventilation
 compared, 58
 roof ventilators, 55–56
 temperature-difference forces,
 54–55
 ventilator capacity, 56
 wind forces, 53–54
 neon, 1, 12
 night-and-day thermostat, 294
 nitrogen, 1, 12
 noise
 evaporators, 270
 fans, 94–95
 noncondensables
 defined, 474
 purging the system of, 441, 451
 nonportable air conditioners,
 357–361
 construction principles, 358
 heating coils, 361
 plumbing connections, 358–359
 water-cooling tower, 359–360

O

odors, 1, 12, 75
 oil
 adding, 439
 automatic lubrication system,
 centrifugal compressors,
 196–198
 circulation of, in water-cooling
 systems, 283, 287
 pour point, 475
 removing, 439

496 Index

- oil separators, 196, 260–263, 270
- oil trap, 475
- optimum comfort line, 26–27
- outdoor condensing units, 237–238
- outdoor design conditions, 312–325
 - summer, 313
 - U.S. climatic conditions, 314–325
 - winter, 312–313
- output, 475
- overload protectors
 - current-and-thermal type, 419, 428
 - room air conditioners, 126, 134–135, 136
 - single-phase motors, 418–419
 - thermal type, 419, 428
 - testing, 134–135
- oxygen, 1, 2, 12
- ozone, 12
 - and chlorofluorocarbon compounds (CFCs), 148
 - defined, 475
 - and Freons, 157
 - source of, in air, 1
- P**
- packing, 475
- packless valve, 475
- pan-type humidifiers, 71
- parallel pass condenser, 217
- performance factor, 475
- permanent split-capacitor motors, 408–409, 428
- permanent split-phase capacitor motors, 127
- phenolphthalein paper, 153
- phosgene, 373
- phosphorous pentoxide, 475
- pipng
 - cooling-unit, 280–281
 - discharge lines, 283–284
 - insulation, 286–287
 - liquid lines, 281–282
 - oil circulation, 283
 - pressure-drop considerations, 280–281
 - purposes of, 281
 - refrigerant, arrangement of, 284–287, 288
 - selection of, 280
 - suction lines, 282
 - supports, 285–286
- pistons, compressors, 178–181
- plain-tubed condenser, 217
- plain-tubing evaporators, 241, 242–243, 269
- plate evaporators, 241, 242
- plate-type condenser, 217
- pneumatic relays, 300
- point of liquefaction or condensing, 6
- polyphase motors, 399–406, 428
 - squirrel cage motors, 400–401, 402, 428
 - synchronous motors, 403–406, 428
 - wound-rotor motors, 401–403, 428
- poppet valves, 178
- portable air conditioning units, 101
- positioning relays, 300
- positive motors, 299
- pounds per square inch (psi), 9
- pour point, oil, 475
- power, 475
- power-conversion factors, 425
- power factor, electrical devices, 475
- power input/output, fan, 90
- preheater, 333–334
- pressure
 - absolute, 459
 - air, at sea level, 9, 13, 19, 27
 - atmospheric, 8–9, 10, 13, 19, 27, 462
 - back, checking, 434
 - balanced, 462
 - barometric, 9, 10, 27
 - condensing, 159, 228
 - control devices, 291
 - critical, 7, 466

- defined, 475
- evaporating, Freons, 159–160
- gage, 9, 436
- head, 160, 229–232, 432–433, 451
- hydrostatic, 473
- regulators, 297, 308
- stabilization of, in air-cooled condensers, 230–232
- static, 90
- suction, 386, 433
- total, 90, 479
- velocity, 90
- pressure drop, 287
 - defined, 475
 - pipng and, 280–281, 287
 - refrigerants, 164
- pressure gages, 245, 436–437
 - combination, 437
 - compound, 10, 12, 436
 - defined, 10, 475
- pressure-motor control, 421
- pressure-reducing process, 175, 215
- pressure-regulating valves, 305–306, 307, 309
- pressure regulators, 297, 298, 308
- pressure-relief valve, 475
- pressure–temperature relationship
 - Boyle’s law, 6
 - combined law of Boyle and Charles, 6–7
 - critical pressure, 7
 - critical temperature, 7
 - law of Charles, 5
 - law of conservation of energy, 6
 - law of conservation of matter, 5–6
 - point of liquefaction or condensing, 6
 - refrigerants, 160, 161
- prime-surface evaporators. *See* plain tubing evaporators
- professional organizations, list of, 453–457
- propeller fans, 89, 98, 334–335, 469
- psychrometer, sling, 9–10, 11, 16, 27
- psychrometric charts
 - calculation examples, 19, 21–25
 - defined, 18, 475
 - instructions for using, 19, 20
- psychrometry
 - air and water-vapor mixtures, 15
 - comfort charts, 25–27
 - defined, 15
 - humidifying and dehumidifying, 15
 - psychrometric charts, 18–25
 - relative humidity, 15–18
 - pull-in/pull-out torque, 417
 - pump-down procedure, 440–441
 - purging, 475
 - purifiers, air, 66–67
 - pyrometer, 476
- Q**
- quick-connect couplings, 350–353, 476
- R**
- R-134a refrigerant, 162, 169, 373
- radiation, 3, 12, 476
- reactor, room air conditioners, 127
- Reamur scale, 7
- receiver-dehydrator assembly, automobile air-conditioning, 376–377
- receivers, 173, 214
- reciprocating compressors, 125, 153, 171, 177–184, 215
 - closed-type, 178
 - component parts, 177, 178, 179, 180
 - connecting rods, 181
 - crankshaft, 181–183
 - drive methods, 177–178
 - hermetic-type, 178, 179, 215
 - lubrication and cooling, 184
 - open-type, 178
 - pistons and piston rings, 178–181
 - shaft seals, 183–184
 - valves, 178, 180, 181

498 Index

- reed valves, 178
- refrigerant(s)
 - adding, 437–439
 - ammonia, 153, 166, 168
 - automobile air-conditioning, 162, 373, 388
 - boiling point, 147, 148, 152, 153, 154, 169
 - Boyle's law and, 6
 - calcium chloride (CaCl₂), 154–155, 463
 - carbon dioxide, 154, 166
 - charge, checking, 434–435
 - chlorofluorocarbon compounds (CFCs), 147–148
 - circulation of, 159, 258
 - classification of, 148–150, 169
 - coefficient of performance, 163–164
 - controls. *See* refrigerant controls
 - critical temperature, 160–161
 - cylinder capacity, 167–168
 - cylinders, storing and handling of, 166–167
 - defined, 175, 476
 - desirable properties of, 147, 175
 - driers, 263–264
 - early types of, 150
 - environmental effects of, 148, 157, 169
 - ethyl chloride, 152–153
 - first aid for exposure to, 168
 - flowback, protection from, 199–200
 - freezing point, 160
 - Freezol, 154
 - Freon family of, 156–160, 166, 168, 169
 - handling, 166–168
 - head pressure, 160
 - hydrofluorocarbons (HFCs), 162, 169
 - irritant, 473
 - isobutane, 154
 - latent heat of evaporation, 162–163
 - leaks, detecting, 139, 151, 152, 153, 154
 - methyl chloride, 151–152, 168, 474
 - pipng arrangement, 174, 284–287, 288
 - power consumption, 163–164
 - pressure–temperature relationships, 149, 160, 161
 - R-134a, 162, 169, 373
 - receivers, 173, 214
 - refrigerating effect of, 162–163
 - removing, 439
 - selection of, 147, 169, 176
 - specific heat, 163
 - spillage, 259–260
 - sulfur dioxide, 151, 160, 166, 168
 - toxicity of, 147, 166
 - tubing, reverse-cycle air conditioning, 348–350
 - typical, characteristics of, 148
 - vaporization of, 166
 - volume of liquid circulated, 148, 164
- refrigerant controls, 174, 214, 245–251, 300–309
 - automobile air conditioning, 369–371, 374, 388, 395
 - automatic expansion valves, 300, 308–309
 - capacity requirements, 251
 - capillary tubes, 305, 309
 - chilling units, 247–249
 - crankcase pressure-regulating valves, 305–306, 309
 - dry-expansion coil arrangements, 249–251
 - evaporator pressure regulating valve, 306, 307, 309
 - high-side float valves, 305
 - low-side float valves, 303–304
 - reversing valves, 306–308, 309
 - superheat, 245–247
 - thermostatic expansion valves, 300–303, 309

- refrigerant cylinders
 - capacity, 167–168
 - handling and storage of, 166–167
- refrigerant system
 - automatic expansion valves, 139
 - brine systems, 154–155
 - components of, window air conditioner, 101
 - compressor amperage, 139
 - congealing tank, 155
 - evaporator temperature, 138–139
 - holdover tank, 155
 - servicing, 138–139
- refrigerating effect, 162–163, 258
- refrigerating system, 476
- refrigeration
 - calculating amount needed, 19, 27
 - capacity, 10–12, 463
 - cooling process, steps in, 175
 - cycle, 165, 174–175
 - defined, 147, 169
 - necessary, calculation of, 27
 - simple system, operation of, 164–166
 - ton of, 10, 51, 103, 144, 478
- refrigeration cycle, 165, 174–175
- refrigerator
 - components of, 164
 - controls, 174
 - reinstallation
 - of compressor, 203
- relative humidity, 328
 - calculating, 15, 27
 - defined, 15, 27, 476
 - as a design condition, 311–312, 328
 - dew-point temperature, 17, 27
 - dry-bulb temperature, 17
 - effective temperature, 17
 - grains of moisture, 16, 27
 - measurements of, 9, 16, 27
 - specific volume, 17
 - temperature-humidity index, 18
 - total heat content, 18, 27
 - wet-bulb depression, 18
 - wet-bulb temperature, 17
- relays, 134, 299–300, 308, 419–420
- relief valve, 476
- repulsion induction motors, 409, 428
- repulsion-start induction motors, 409–410, 428
- resistance
 - air-duct, 59, 85–88
 - electrical, 476
 - thermal, 476
- reverse-cycle air conditioning system, 341–354, 351–354
 - control equipment, 344–346
 - cooling cycle, 342
 - defrost-cycle operation, 346
 - heating cycle, 341–342
 - indoor arrangement, 347–348
 - installation and maintenance, 346–347, 348, 349
 - quick-connect couplings, 350–353
 - refrigerant tubing, 348–350
 - reversing valve operation, 342–344, 345, 354, 355–356
 - system troubles, 353–354
- reversing motors, 299
- reversing valves, 306–308, 309
 - operation of, 342–344, 345
 - troubleshooting, 354, 355–356
- revolving roof ventilator, 56
- ridge roof ventilator, 56
- ring-plate valves, 178
- roof ventilators, 55–56
- room air conditioners
 - advantages of, 101
 - automatic expansion valves, 139
 - capacity requirements, 103–104
 - casement window installation, 111–115
 - checking capacitors, 133–134
 - cleaning, 137, 144
 - components of, 102, 144
 - compressor amperage, 139

500 Index

- room air conditioners (*continued*)
 - compressor motor, 135–137
 - compressor motor overload, 134–135
 - compressor motor relay, 134
 - compressors, 124–125, 144
 - console-type systems, 116–122
 - cooling capacity, 103
 - cords and plugs for, 123, 144
 - defined, 101, 143, 460
 - dismantling, 130
 - double-hung window
 - installation, 106–111
 - electrical components, 124–127, 144
 - electrical system, 122–129, 144
 - electrical testing, 130–135, 144
 - evaporator temperature, 138–139
 - fans in, 127–128
 - filters, 137, 144
 - installation methods, 104–122, 144
 - National Electrical Code, 122
 - oiling of, 137
 - operation of, 101–103, 143–144
 - outside support bracket, 115
 - overload protector, 126
 - portable units, 101
 - power supply, 122
 - refrigerant leaks, 139
 - refrigerant-system service, 138–139
 - relay check, 134
 - run-capacitors, 127
 - servicing, 129–139, 144
 - starting capacitors, 126–127
 - starting relay, 126
 - system leaks, 137
 - thermostats, 128–129
 - troubleshooting, 140–143, 145
 - unit control switch, 129
 - window units, 101, 102
 - winter care, 137–138, 144
 - room cooler, 476
 - room thermostats, 291–294
 - rotary compressor, 153, 171, 184–189, 215
 - commercial applications, 189
 - defined, 184, 476
 - operation of, 184
 - rotating blade, 184, 187–189
 - stationary-blade, 184–187
 - types of, 184–189
 - rotating blade rotary compressor, 184, 187–189
 - run-capacitors, room air conditioners, 127
 - running time, 476
- S**
- saturated vapor, 476
 - saturation temperature, 17, 27
 - Schraeder valve, 476
 - scroll compressor, 189–192
 - efficiency and, 189
 - HP-20 model, 192, 193
 - HS-22 model, 192, 194
 - operation of, 191–192
 - scroll compression process, 189–191
 - seal, shaft, 476
 - sealed unit, 476
 - sea-level air pressure, 9, 13, 19, 27
 - Seasonal Energy Efficiency Ratio (SEER), 189, 192
 - self-cleaning air filters, 64–67
 - semiautomatic control, 290, 308
 - sensible heat, 4, 12, 18–19, 471
 - series condenser, 217
 - series-wound motors, 399, 425
 - shaded-pole motors, 91, 127
 - shaft seals, 183–184
 - leaks in, 201
 - shell-and-coil condenser, 219, 224, 226
 - shell and tube, 219, 476–477
 - shunt-wound motors, 399, 425
 - sight glass, use of, 389, 434
 - silica gel, 477
 - single-blade dampers, 299
 - single-phase motors, 406–412, 428
 - capacitors on, 411–412

- capacitor-start, 407–408, 428
 - controls, 418–420
 - fans, 91
 - overload protectors, 418–419, 428
 - permanent split-capacitor, 408–409, 428
 - repulsion induction, 409, 428
 - repulsion-start induction, 409–410, 428
 - split-phase, 406–407, 428
 - start relays, 419–420
 - two-value capacitor, 408
 - single-seated valves, 299, 308
 - sling psychrometer, 9–10, 11, 16, 27
 - slip-ring motor, 92
 - sludge, 477
 - smoke, 2
 - soda lime, 477
 - solenoid valves, 71, 380–381, 421, 428, 477
 - solid, 477
 - solubility, 477
 - solution, 477
 - specific gravity, 471, 477
 - specific heat
 - defined, 4, 12, 471, 477
 - refrigerants, 163
 - of water, 4
 - specific humidity, 473
 - specific volume, 17, 477
 - split-phase motors, 406–407, 428
 - spray-cooling ponds, 279
 - spray pond, 477
 - squirrel cage motors, 400–401, 402, 428
 - controls, 413–414
 - squirrel cage winding, 417
 - starting capacitors, room air conditioners, 126–127
 - start relays
 - room air conditioners, 126
 - single-phase motors, 419–420
 - stationary-bed type dehumidifier, 77, 78
 - stationary-blade rotary compressor, 184–187
 - stationary roof ventilator, 56
 - steam, 15, 477
 - steam-jet central air-conditioning system, 331, 366
 - steam trap, 477
 - strainers, 265–266, 270
 - subcoolers, 266–267, 268, 271
 - subcooling, 258, 282, 477
 - sublimation, 477
 - suction accumulators, 260
 - suction lines, 282, 287, 478
 - suction pressure
 - checking, 386, 433
 - defined, 478
 - suction valves, 178
 - suction-throttle valves, 382–384, 388, 396
 - sulfur dioxide, 151, 160, 166
 - first aid for exposure to, 168
 - superheat, 245–247
 - checking, 246–247
 - defined, 5, 13, 478
 - superheater, 478
 - support bracket, window air conditioners, 115
 - surge accumulators, 260
 - surge drums, 260, 270
 - suspended-type air conditioners, 361–363
 - Suva™ refrigerant. *See* R-134a refrigerant
 - sweating, 478
 - switching relays, 300
 - synchronous motors, 403–406, 428
 - controls, 416–418
 - syphonage roof ventilator, 56
 - system, 478
 - system evacuation, 443–444
- T**
- temperature, 1, 12
 - ambient, 273, 461
 - average annual minimum, 312
 - control devices, 290
 - critical, 7, 160–161, 466
 - critical, refrigerants, 160–161
 - defined, 478

502 Index

- temperature (*continued*)
 - dew-point, 17
 - dry-bulb, 16, 17
 - effective, 17
 - evaporator, 138–139
 - indoor, recommended for
 - comfort, 25–27, 311–312
 - median of extremes, 312
 - and pressure, relationship with, 5–7
 - saturation, 17, 27
 - wet-bulb, 16, 17
 - temperature-humidity index, 18
 - temperature-motor control, 420–421
 - thermal conductivity, 478
 - thermal effect, 54, 97
 - thermal-type overload protector, 419, 428
 - thermistor, 478
 - thermocouple, 478
 - thermodynamics, 478
 - thermometer, 7–8
 - alcohol, 17
 - defined, 7, 13, 478
 - dry-bulb, 10, 16
 - Celsius scale, 7–8
 - Fahrenheit scale, 7
 - mercury, 17
 - Reamur scale, 7
 - wet-bulb, 10, 16
 - thermostat(s), 308
 - automobile air-conditioning, 369
 - defined, 478
 - duct, 294
 - electrical circuitry for, 293
 - immersion, 295
 - microprocessor-based, 128
 - night-and-day, 294
 - room, 291–294
 - in room air conditioners, 128–129
 - twin-type, 294, 295
 - thermostatic expansion valve,
 - 300–303, 309
 - automobile air-conditioning, 377–380, 387–388, 396
 - defined, 478
 - function of, 174, 300–301
 - operation of, 301
 - sizing of, 302–303
 - three-way valves, 299, 308
 - time clocks, 256–257, 270
 - ton of refrigeration, 10, 51, 103, 144, 478
 - total heat, 18–19, 27, 479
 - total pressure, 90, 479
 - toxic gases, 1, 12
 - trichlorofluoromethane, 147
 - troubleshooting
 - air conditioners, general, 207–214, 444–450
 - automobile air-conditioning, 392–394
 - central air-conditioning, 363–366
 - compressors, 207–213
 - electrical system, 426–428
 - reverse-cycle air conditioning system, 353–354, 355–356
 - room air conditioners, 140–143, 145
 - tubeaxial fans, 89, 98, 469
 - tube quick-connect (TQC) couplings, 350
 - turbine roof ventilator, 56
 - turbulent flow, 479
 - twin-type thermostats, 294, 295
 - two-value capacitor motors, 408
- U**
- unit control switch, room air conditioners, 129
 - unit coolers, 244
 - unit heater, 479
 - unit system, 479
 - unloader, 479
- V**
- vacuum, 479
 - valve(s)
 - automatic expansion, 139, 174, 300, 301, 308–309
 - check, 267–269, 271

- compressor, 178, 200–201, 435–436, 444
 - constant-pressure, 465
 - constant-temperature, 465–466
 - control, 298–299, 308
 - crankcase pressure-regulating, 305–306, 309
 - defined, 479
 - discharge, 178
 - double-seated, 299, 308
 - evaporator pressure-regulating, 306, 307, 309
 - external adjustment of, 378
 - float, 303–305, 470
 - maintenance, 200–201
 - packless, 475
 - poppet, 178
 - pressure-relief, 475
 - pressure-regulating, 305–306, 307, 309
 - reed, 178
 - reversing, 306–308, 309, 342–344, 345, 354, 355–356
 - ring-plate, 178
 - Schraeder, 476
 - single-seated, 299, 308
 - solenoid, 71, 380–381, 421, 428, 477
 - suction-throttle, 382–384, 388, 396
 - thermostatic expansion, 174, 300–303, 309, 377–380, 387–388, 396, 469, 478
 - three-way, 299, 308
 - water-regulating, 219, 220, 228, 276–278
 - vaneaxial fan, 89, 98
 - vapor, 479
 - vapor-compression refrigeration cycle, 174–175
 - vaporizing process, 175
 - vegetation, 326
 - velocity pressure, 90
 - ventilation
 - air-duct systems, 77–88
 - air filters, 61–69, 97
 - air filtration, 60–61
 - air leakage, 53
 - defined, 53, 97
 - dehumidifiers, 73–77, 98
 - fans and blowers, 89–97, 98
 - fresh-air requirements, 57–58
 - humidifiers, 69–73, 98
 - mechanical, 53, 58–60, 97
 - natural, 53–56, 97
 - requirements, 90
 - ventilators
 - airflow in, 55
 - capacity, 56
 - mechanical, typical, 59
 - roof, 55–56
 - wind stream and, 54
 - viscosity, 479
 - volume, fans, 89
 - volumetric efficiency, 205, 468
- W**
- water-cooled condensers, 219–227, 238
 - bleeder shell-and-tube, 219
 - configurations of, 224, 225
 - cooling-water circuits, 220
 - double tube, 219, 220–224
 - evaporative, 224–227
 - flooded atmospheric, 219
 - head-pressure controls, 228–229
 - metal combinations in, 223
 - shell-and-coil, 219, 224, 226
 - types of, 219, 220–227
 - winter shutdown of, 204–205
 - water cooler, 479
 - water-cooling systems, 273–288
 - ambient temperatures and, 273
 - atmospheric cooling methods, 274–279
 - combination units, 273
 - cooling ponds, 278, 287
 - cooling-unit piping, 280–287
 - discharge lines, 283–284, 288
 - liquid lines, 281–282
 - oil circulation, 283, 287
 - piping insulation, 286–287
 - piping supports, 285–286

504 Index

- water-cooling systems (*continued*)
 - refrigerant-piping arrangement, 284–287, 288
 - selection of, 273
 - spray-cooling ponds, 279
 - suction lines, 282, 287
 - water sources, 273, 287
 - water towers, 274–278, 279, 287
 - winter operation of, 273
 - water filters, 12
 - water-regulating valve, 219, 220, 228, 276–278
 - water towers, 274–278, 287
 - algae growth in, 276, 287
 - operation of, 275–276
 - as source of cooling water for
 - nonportable air conditioner, 359–360
 - water-regulating valves in, 276–277
 - winter preparation of, 276
 - water vapor
 - defined, 5, 27
 - percent of in total air by volume, 15
 - weight of, 16, 27
 - wax, 479
 - weather, as a design consideration, 326–328
 - weather stripping, 53
 - wet-bulb depression, 18, 479
 - wet-bulb temperature, 17
 - wet-bulb thermometer, 10, 16
 - wet compression, 479–480
 - wet-expansion evaporators, 247, 248, 269
 - wet replacement-type filters, 64
 - wet (viscous) filters, 2, 97
 - air purifiers, 66–67
 - automatic-type, 64–66
 - flushing-type, 65
 - immersion-type, 64, 66
 - manually cleaned type, 64, 65
 - wet replacement type, 64
 - wind, 53–54
 - window air conditioners, 101
 - dismantling, 130
 - installation of, 104–115
 - window frosting, preventing, 53
 - window-mounted console air conditioners, installing, 119, 120
 - wound-rotor motors, 401, 403, 404, 428
 - controls, 414–416, 417
- X**
- xylene, 480
- Y**
- year-round central air-conditioning
 - absorption system, 331, 338–341, 366
 - advantages of, 331–332, 366
 - air-supply fans, 334–335
 - air-supply system, 332
 - air washers, 335
 - classification of, 331, 366
 - controls, 335–336
 - cooling coils, 334
 - filters, 335
 - gas-compression system, 331, 366
 - heating coils, 333
 - mixing chamber, 332–333
 - noise, 335
 - nonportable units, 354, 357–361
 - preheaters, 333–334
 - purpose of, summer vs. winter, 331
 - reverse-cycle systems, 341–354
 - steam-jet vacuum system, 331, 366
 - suspended-type air conditioners, 361–363
 - system selection, 337–338
 - troubleshooting, 363–366
 - zone control, 336–337
- Z**
- zero, absolute, 5, 7–6, 459, 480
 - zone, 336
 - comfort (average), 480
 - zone control, 336–337