

Index

A

- accelerators, 19
- acoustical hardboard, 185
- adfreezing
 - cause of, 67
 - of footings, 49
 - of foundations, 49
- adhesives
 - applied to furring strips, 506
 - applying, 260–261
 - applying to ceramic tile, 594–596
 - applying to masonry walls, 474
 - for attaching wallboard to insulation, 477
 - in bulk form, 466
 - in cartridge form, 466
 - exposed to air, 261
 - for floor panels, 255, 257–259
 - for installing paneling, 519, 520
 - for plasterboard installations, 463, 466
 - for prefinished wallboard, 498, 500, 505–506
 - selecting, 260
- admixtures
 - accelerating, 19
 - air-entraining agents, 18–19
 - defined, 18
 - pozzolans, 20
 - retarders, 19–20
 - types of, 32
 - water-reducing, 20
- Aerogels, 394
- aggregates, 18
- air barrier, 430–431
- air-entrained concrete, finishing, 91–92
- air-entraining agents, 18–19
- air-entraining natural cement, 17–18
- air-freezing index (F), 48–49
- Aircrete, 128, 428–429
- air leakage, 432
- air retarders. *See* house wraps; vapor diffusion retarders (VDR)
- Airtight Drywall Approach (ADA), 371, 433
- allowable bending stress (F_b)
 - defined, 220
 - of different types of wood, 221, 222–237
 - of girders, 238, 239
 - of steel beams, 241
- Alpine fir, 228–229
- aluminum foil, permeance values of, 370
- aluminum siding, 381–382
- aluminum strip roofing, 328
- American Concrete Institute (ACI) Building Code of, 19
 - classification of slabs by, 51–53
- American Drainage Systems (ADS), tubing from, 65–66
- American Institute of Steel Construction (AISC), 241
- American Society of Heating, Refrigerating, and Air-Conditioning Engineers (ASHRAE), 368
- American Wood Preservers Bureau (AWPB) Foundation (FDN) Standard, 70
- anchor bolts
 - carrying loads for, 487
 - deeply embedded, 196
 - for sills and plates, 124, 126
- APA, on cover sheathing, 340–341
- Arkansas House
 - clips used in, 272, 281
 - Corner-back in, 274
 - corner studs of, 271–272, 274, 281
 - creator of, 271
 - framing of, 271
 - purpose of, 271, 289
 - reduction in lumber of, 271
 - revival of concepts of, 271
 - Romex wire in, 272–273

664 Index

- ash pit, 147, 149
 - asphalt
 - in built-up roof, 331, 332
 - ice dam shields for, 342–343
 - polymeric, 59
 - rubberized, 58–59
 - for waterproofing, 58
 - asphalt felt, permeance values of, 370
 - asphalt shingles
 - drip-edge flashing for, 343–344
 - for hips, 345–346
 - and ice dams, 343
 - installing, 344–346
 - nailing of, 345
 - patterns of, 339
 - picture of, 330
 - qualities of, 327
 - strips of, 353
 - underlayment of, 339–342
 - in valleys, 345
 - astragals, 399
 - attics
 - cellulose insulation in, 412–414
 - disappearing stairs in, 544, 546
 - equipped with fans, 608–609
 - radiant barriers in (*see* radiant barriers)
 - ventilation of (*see* attic ventilation)
 - attic ventilation
 - airflow patterns in, 606–610, 613, 614
 - building codes for, 603
 - combining gable and soffit vents for, 608–609
 - criteria for, 605–606
 - determining area of, 604
 - drip-edge vents for, 617–618
 - effect of wind on, 606–607
 - exhaust vents for, 606
 - external baffles for, 613–615
 - fans for, 608–609
 - for hip roofs, 619
 - intake vents for, 606
 - and moisture control, 604
 - necessity of, 619–620
 - and radiant barriers, 453, 456
 - ridge vents for, 612–615
 - with roof louvers, 608
 - shingle-over ridge vents for, 618
 - soffit vents for, 607–609, 612, 615–617
 - solutions for problems with, 610, 612
 - during summer, 604–606
 - turbine vents for, 610, 611
 - universal form of, 603
 - automatic door openers, 585, 587–588
 - automatic levels, 6, 7
 - awning window, 396, 400
- B**
- backer blocks, 373
 - backer board, 460
 - backfilling
 - and basement cracks, 67
 - compaction of, 67–68
 - with dirty soils, 60
 - importance of, 81, 83
 - for permanent wood foundations (PWF), 73, 75
 - process of, 67–68
 - protecting walls during, 67
 - in relation to foundation sill, 68
 - uses of, 66–67
 - backing, 314
 - baffles, 613–615
 - balloon framing, 190–191, 194–195
 - balsam fir, 222–223
 - balusters, 537, 539
 - bar supports
 - chairs, 29–30
 - materials for, 26
 - plastic, 26
 - welded-wire fabric, 26–29
 - basement stairs, 537, 538
 - basement walls
 - concrete blocks for, 124
 - dampness of, 523
 - thickness of, 124, 131
 - bastard sawing, 167

- battens, 399
- batten-type siding, 373–374
- batter boards, 9–10
- batts, 404–405
- bay window, 396, 400
- beadboard, 416
- beams
 - allowable bending stress (F_b) of, 220–221
 - box, 286–288
 - flitch, 240–241
 - glulam, 245–246
 - horizontal shear in, 220
 - rot on end of, 209–211
 - solid versus built-up, 221, 238–239
 - steel, 241–244
- bearing capacity
 - defined, 37–38
 - and foundation systems, 35
 - of soil, 40–42, 81
 - ultimate, 38
- benchmark, 6
- bentonite clays, 59–60
- bevel siding
 - installation of, 373
 - nailing, 380
 - sizes of, 372
 - treating corners of, 380–381
- bitumen
 - application of, 55–56
 - disadvantages of, 56–57
 - types of, 55
- Bituthene, 342, 343
- blackbody, 387
- bleeding, 85
- Blown-in-Blanket (BIB) insulation, 405
- board feet
 - computing, 189–190
 - defined, 207
- bow window, 396–397, 400
- box beams, 286–288
- box cornices, 355
- box end finish, 359
- box return, 358
- brick masonry
 - for fireplace construction, 143, 147
 - around metal fireplace forms, 151–154
 - permeance values of, 370
- brick masonry heaters, 140
- pictures of, 141–142
- wood burning efficiency of, 142
- brick walls
 - with extruding joint construction, 129
 - foundations for, 110, 113, 114
- British thermal unit (Btu), 435
- brooming, 89, 90
- builders
 - dealing with building codes, 249–251
 - preframing conferences for, 288
- building codes
 - for floor joists, 199
 - for footings in frost line, 48
 - performance-type, 249
 - specification-type, 249–251
 - ventilation requirements in, 603
- building frames. *See* frames
- building materials
 - emissivity of, 388
 - permeance of, 368, 370
 - typical weights of, 43
 - See also* lumber; roofing; wood
- buildings
 - anchoring to foundation, 196
 - batter boards for, 9–10
 - Certificate of Occupancy (CO) for, 12
 - Certified Plot Plan for, 10–11
 - on corner lots, 2
 - covenants for, 1
 - foundation of (*see* foundations)
 - frames for (*see* frames)
 - laying out with transit level, 6–9
 - measuring squareness of corners of, 10
 - natural grades and contours in, 3
 - on nonconforming lots, 2
 - offset stakes for, 10
 - required documentation for, 1

666 Index

- buildings (*continued*)
residential (*see* houses)
and septic systems, 1–2
sheathing for (*see* sheathing)
siding for (*see* siding)
total loading area of, 246
and wells, 1–2
zoning ordinances for, 1
built-up girders, 221, 238–239
built-up roof (BUR), 331–333
bull floats, 86
butt marker, 580
- C**
calcium chloride, 19
cantilevered in-line joist system,
251–255
capillarity
controlling, 54–55
defined, 54
protection against, 55–66
capillary break, for girders, 211
carpeting, 570
carriages
defined, 539
figure of, 541
fitting outline of tread and risers,
532–533
nailed to stringer, 534
casement windows
and air currents, 399
alternate name for, 400
with mullion, 399
origin of, 385
separating, 399
sill construction for, 399
types of, 399
casing, 579
cast-in-place concrete, 35
caulking
of corner joints of ceramic tile,
600–601
of hardboard siding, 376
caulks
mudding on prefinished
wallboard, 507–508, 509,
510
for permanent wood foundation
walls, 72
cedar shingles, 328–329, 377
ceiling joists, and disappearing
stairs, 546, 547, 548
ceilings
fireproof, 477, 488
making opening for disappearing
stairs in, 545–548
steel frame, 479, 488, 489
typical weights of, 43
cellular glass, 422
cellular plastics
cellular glass insulation, 422
expanded foam, 416
extruded polystyrene, 56, 78–79,
362, 364, 417, 457
foil-faced insulations and
gypsum board, 424–427
forms of, 416
for insulating concrete, 428–429
perlite, 423–424
phenolic, 418
polyisocyanurate (PIRs), 417,
418
Polymaster, 421–422
polystyrene, 416
polyurethanes (PURs), 417, 418
radiant barriers for, 427–428
tripolymer foam, 421
urea-formaldehyde (UFFI),
420–424
vermiculite, 423
cellulose insulation
application of, 411
in attics, 412–414
blowing in, 412
energy savings from, 631
installed versus settled thickness
of, 413–414
manufacture of, 410
processing, 410–411
risks of, 409–410
R-values of, 409, 412–413, 414
settling of, 411
spray-in, 415–416
Story Jig, 416

- two holes versus one hole for
 installation of, 411–412
- Celotex, 419
- cement
 - low heat of hydration in, 17
 - natural, 17–18
 - Portland, 15–17, 115
 - types of, 115
 - See also* concrete
- cement paste, 17
- ceramic tile
 - applications of, 591, 593, 594, 595
 - applying adhesive to, 594–596
 - applying grout to, 597, 600
 - architectural effects of, 568–569
 - basic description of, 591, 601
 - in bathroom, 591, 593
 - block style, 595
 - corner joints of, 600
 - for countertops, 594
 - cutting, 597, 598–599
 - history of, 591
 - ingredients of, 591
 - installing, 592–601
 - installing on floor, 600
 - planning layout of, 593–594
 - on sink tops, 591, 594
 - spacers for, 598
 - types of, 592
 - uses of, 601
- Certificate of Occupancy (CO), 12
- Certified Plot Plan, 10–11
- chairs, 29–30
- chimneys
 - cause of poor draft in, 134
 - cleanout trap for, 138
 - construction above roof, 133
 - construction of, 137–139
 - cross-section of, 143
 - defined, 161
 - extension above roof, 134, 135
 - flues for, 136–137, 138
 - foundation for, 139
 - framing around, 206–207
 - intensity of draft in, 134
 - mortar for, 137–138
 - poor draft in, 157
 - precautionary measures for, 133
 - preventing leakage of smoke
 from, 137–138
 - producing natural draft in, 134
 - providing hood for, 157
 - reducing resistance in walls of,
 136
 - temperature range of, 136–137
 - testing for leaks, 139
- chlorofluorocarbons (CFCs),
 417–418
- clapboard siding, 372–373
- clay lining, 136, 137
- cleanout trap, 138
- closed cornices, 355, 356
- closed rake, 358–359
- coal tar, 58
- coal-tar pitch roofs, 351
- collar beams, 202
- columns
 - footings for, 218–220
 - for girders, 218–220
 - lally, 218, 219, 220, 239–240
 - spacing, 239–240
 - tributary area of, 219
- common lumber, 188–189
- common rafters
 - cuts for, 305–307
 - defined, 298
 - view of, 309
- compaction, of backfill, 67–68
- compactors, 68
- COM-PLY, 183
- compressive creep, 79
- concave joint, 129
- concrete
 - aggregates, 18
 - air-entrained, 91–92
 - bar supports for, 26–30
 - bending strength of, 28–29
 - bleeding in, 85
 - brooming, 89, 90
 - cast-in-place, 35
 - causes of cracks in, 89
 - components of, 16
 - consolidation of, 22–23

668 Indexconcrete (*continued*)

- controlling shrinkage of, 46
- crack control for, 26, 28–29, 46, 47
- curing, 93–98
- drop-chutes for, 22, 25
- edging, 90, 92
- factors for strength of, 93–94, 99, 115
- fiber reinforced, 53
- finishing, 86–91
- floating, 86–88
- grooving, 89–90, 91
- grout, 18
- handling, 20–21
- hardening of, 17
- heaving under, 89
- history of, 15
- hydration in, 94
- insulating, 428–429
- jitterbugging, 86
- limitations of, 15–16
- versus mortar, 18, 114–115
- natural, 15
- normal, 17–20
- placing, 21–22, 23, 24, 25
- ponding, 96
- Portland, 15–17, 115
- pouring during hot weather, 19–20
- preventing loss of moisture from, 96
- preventing random cracking of, 89
- proper storage of, 85
- qualities of, 15
- rebars for, 23–26
- relative strength of, 95
- rodding, 85
- screeding, 85
- segregation of, 20–21
- slump of, 30–31
- smoothing surface of, 85, 86
- sprinkling with water, 96
- stiffness of, 18–19
- tamping, 86
- troweling, 89
 - wet coverings for, 96
- See also* cement
- concrete blocks
 - allowing room for mortar on, 101, 104
 - applying mortar to, 118–119
 - for basement walls, 124
 - building with, 116–124
 - compressive strength of, 101
 - for corners, 101
 - decorative, 101, 103–106
 - grille, 105, 106, 107
 - insulated, 428
 - laying at corners, 117–118
 - mortar for, 114–115
 - for patio floor, 108, 111
 - patterned, 106
 - permeance values of, 370
 - pictures of, 102
 - placing, 119
 - screen, 105–106, 107
 - setting, 119–120
 - sizes of, 101, 103, 104
 - slump, 104–105
 - solid forms of, 101
 - special finishes on, 106
 - split, 101, 103, 104
 - standard, 106, 108–109, 110, 111–112, 131
 - for supporting sloping ground level, 108, 111
 - thickness of, 131
 - for walkway, 108, 111
 - weight of, 101
- concrete-block walls
 - adequate flashing in, 128, 131–132
 - for basements, 124
 - building around door and window frames, 120, 122
 - building between corners, 117–118
 - building techniques for, 124–131
 - construction of, 116–124
 - electrical outlets in, 125, 127

- fill insulation for, 125, 127–128
- foundations for, 110, 113, 114, 131
- horizontal reinforcement bars for, 109–110, 113
- installation of heating and ventilating ducts in, 125, 127
- interior, 123, 124
- placing blocks on, 119
- placing sills and lintels in, 120, 123–124
- planning for openings in, 116–117
- setting blocks on, 119–120
- standard, 116
- thickness of, 109–110, 112, 113
- tooling joints of, 130, 131
- types of joints in, 129–131
- concrete mixer trucks, 21, 32
- concrete pumps, 21–22, 24
- concrete-shell pile, 37
- concrete slabs. *See* slabs-on-grade
- concrete walls, 47
- conduction, 387, 434
- conductivity (*U*), 435–436
- conical roof, 296
- consolidation, 22–23
- construction adhesives, 260–261. *See also* adhesives
- construction sites
 - known reference line on, 3–6
 - natural grades and contours in, 3
 - preparing for frost-protected shallow foundations, 78
 - preparing for permanent wood foundations (PWF), 69–70
 - preparing for slabs-on-grade, 53–54
 - staking out house location on, 3–10
 - testing for radon levels at, 624–625
- contemporary window, 400
- origin of, 385
- convection
 - in walls, 426, 427
 - through windows, 386
- corkboard, permeance values of, 370
- Corner-back, 274
- corner boards, 380
- corner joints
 - of ceramic tile, 600–601
 - sealing, 488, 526
- corner lots, 2
- corner markers, 4
- corners, measuring squareness of, 10
- corner studs
 - defined, 200
 - detailed view of, 201
 - weight carried by, 277
- cornice returns, 357–358, 360
- cornices
 - box, 355
 - closed, 355
 - defined, 355
 - gable-end finish of, 358–359
 - open, 356–357
 - rake finish of, 358–359
 - return on, 357–358, 360
 - wide box, 355–356
- corrugated plastic tubing, 63–66
- cotton insulation, 429–430
- covenants, 1
- crawl spaces, 49–50
- cripple jack rafters, 299, 315–316
- crushed stone
 - as drain envelope, 63–64
 - for permanent wood foundations (PWF), 70
- cup shakes, 169
- curing
 - defined, 94
 - importance of, 93–94
 - methods for, 96–98
 - proper amount of time for, 94–95
- curing compound, 96–98
- cutbacks, 55, 56
- cut nails, 260
- cut of roof, 298

670 Index

D

- dampers
 - control for, 148
 - in metal fireplace forms, 155
- damp proofing
 - backfilling for, 66–68
 - bituminous compounds for, 55–57
 - and extruded expanded polystyrene (XPS), 55–56
 - of girders, 211
 - by parging, 55, 57
 - with polyethylene sheeting, 57–58
 - purpose of, 55
- dead load (DL)
 - defined, 39
 - of girders, 218
- decorative blocks
 - grille, 105, 106, 107
 - patterned, 106
 - screen, 105–106, 107
 - slump, 104–105
 - special finishes on, 106
 - split, 101, 103, 104
- deep foundations, types of, 35, 37, 81
- deep-wall construction, 484–485
- deformed steel bar. *See* rebars
- diagonal sheathing
 - application of, 361, 382
 - diagram of, 363–364
- diffusion-driven radon, 624
- disappearing stairs
 - adjusting, 550–552
 - folding, 544, 546
 - framing support for, 547–548
 - in houses with trusses, 545, 547, 548
 - locating, 545, 547
 - making rough opening for, 545–548
 - placing in rough opening, 548–550
 - securing during installation, 549
 - temporary support for, 548
 - trimming feet of, 551–552
- documentation, required for
 - buildings, 1
- dome roof, 296, 297
- doorframes, 576–577, 589
- doorjambs, 577–578, 579, 589
- doors
 - building concrete-block walls around, 120, 122
 - casing openings for, 579
 - flush, 573, 589
 - frames for, 576–577, 589
 - framing, 284–285
 - for garages, 583, 585–588
 - hanging, 579–582, 583
 - hollow-core, 575, 589
 - installing, 575–579
 - installing hinges on, 579–580, 581
 - installing lock and handle on, 580–581
 - jambes of, 577–578, 589
 - lock stile of, 579
 - louver, 575
 - paneled, 573, 589
 - for patios, 588–589
 - placing wedges for installation of, 579, 580
 - planning for in concrete block walls, 116–117
 - sealing space between wall and, 369, 371
 - sliding, 582–583, 584
 - solid-core, 573–574
 - stock sizes of, 573
 - swinging, 582, 589–590
 - trim for, 579
 - types of, 573–575
- door trim, 579
- dormers, 202–204
- double-gable roof, 294, 295
- double-hung window
 - advantages and disadvantages of, 398
 - air conditioners in, 399
 - origin of, 385
 - parts of, 398
 - picture of, 398

Index **671**

- double-layer construction, 526
 - double-nail method, 464
 - double sills, 194
 - Douglas fir
 - for girder lumber, 221
 - for plywood, 176
 - strength properties of, 223–225
 - downrafts, 134, 135
 - downdraft shelf, 148
 - downspouts, 349–350
 - draft
 - and chimney-wall resistance, 136
 - high-quality, 137
 - intensity of, 134
 - producing, 134
 - draft stops, 205–206
 - drainage systems, subsurface, 62–66. *See also* footing drains
 - drain envelope, 63–64
 - drain screens
 - backfilling for, 66–68
 - classic system for, 60
 - fiberglass, 60, 72–73
 - free-draining materials for, 61–62, 63
 - free-draining membranes for, 60–61
 - materials for, 65
 - plastic mats for, 62
 - drip-edge flashing, 343–344
 - drip-edge vents, 617–618
 - drop siding, 372, 374
 - dry rot, 169
 - drywall. *See* plasterboard
 - drywall clips, 271–272, 273
 - ducts
 - in crawl spaces, 49–50
 - installing in concrete-block walls, 125, 127
 - duplex sheet, permeance values of, 370
- E**
- Eastern hemlock, 226
 - Eastern spruce, 227–228
 - edging, 90, 92
 - electrical boxes, and paneling installations, 516, 517
 - electrical outlets, in concrete-block walls, 125, 127
 - emissivity
 - of blackbody, 387–388
 - of building materials, 388
 - defined, 387
 - and reflectivity, 438–439
 - of windows, 387–388
 - emulsions, 55, 56
 - Engelmann spruce, 228–229
 - Engineered framing system, 274
 - engineered joists
 - advantages of, 263
 - description of, 261
 - various brands of, 262–263, 264–267
 - engineered lumber
 - glulam, 245–246
 - history of, 244
 - laminated layered products, 244, 246, 261, 266–267
 - Environmental Protection Agency (EPA), 627
 - ethylene propylene diene monomer (EPDM), 59
 - expanded foam, 416
 - expanded polystyrene (EPS), 417
 - expansion joints, 467
 - exterior siding. *See* siding
 - exterior stairs, 537–538, 540
 - exterior walls. *See* outer walls
 - external baffles, 613–615
 - extruded expanded polystyrene (XPS), 56
 - calculating loading of, 78–79
 - manufacture of, 417
 - R-value of, 457
 - as sheathing material, 362, 364
 - extruded joint, 129
- F**
- F_b . *See* allowable bending stress (F_b)
 - face-shell bedding, 118–119
 - facia, 312, 359

672 Index

- fasteners
 - for metal ceilings, 488
 - for permanent wood foundations (PWF), 71
 - for shelf brackets in plasterboard, 486
- Federal Housing Administration (FHA), standard for testing sheathing, 366
- fiberboard sheathing, 361
- FiberBond, 502, 503
- fiberglass
 - energy savings from, 631
 - handling, 409–410
 - as loose-fill insulation, 407–410
 - See also* mineral fiber
- fiberglass boards, 60
- fiberglass drain screen, 72–73
- Fiberiffic, 406–407
- fiber reinforced concrete (FRC), 53
- fill insulation, 125, 127–128
- filters, for footing drains, 64
- fire
 - ceilings resistant to, 479, 488
 - and glulam beams, 246
 - and heavy timber, 243–244
 - partitions resistant to, 479, 480–485
 - and plasterboard, 462
 - and radiant barriers, 454
 - roofing materials resistant to, 351
 - steel beams and, 241, 243–244
 - walls resistant to, 477, 479–488
- Fire Acoustical Thermal System (F.A.T.S.), 407
- fireplaces
 - air circulation in, 160
 - ash pit of, 147, 149
 - burning wood in, 156
 - construction of, 147–156
 - cross-section of, 143
 - efficiency of, 140, 162
 - framing around, 206–207
 - freestanding, 157, 160
 - hearths of, 148, 150
 - for home built on concrete slab, 147, 148
 - hooded type, 155
 - importance of dimensions of, 150
 - importance of hearth to, 148
 - location of, 143, 145
 - multifaced, 139–140
 - pit of, 147
 - positioning flue in, 156–157
 - prefabricated, 157–161
 - problems with, 161–162
 - ready-built forms for, 150–155
 - recommended dimensions of, 145–147
 - recommended sizes of openings in, 146
 - returning heat to rooms from, 151
 - Rumford, 139, 162
 - Russian, 140–142
 - single-face, 139
 - smoky, 156–161
 - styles of, 144, 145
 - as supplemental heat sources, 139
 - two-sided, 155
 - types of, 139–143
- fireproof ceilings, 479, 488
- fire screens, 140
- fire stops, 205–206
- flake board, 181–182
- flashings
 - for concrete-block walls, 128, 131–132
 - drip-edge, 343–344
 - for valleys in roofs, 345
- flat-roof dormer, 203
- floating corners, 281, 283
- floating floor, 560, 566
- floating interior angle method, 281, 283
- floats
 - advantages of, 87–88
 - for air-entrained concrete, 92
 - bull, 86
 - finishing concrete with, 86–88

- long-handled, 88
- pictures of, 87, 88
- floor framing
 - alternative methods and materials for, 249–251
 - cantilevered in-line joist system, 251–255
 - construction adhesives for, 260–261
 - of glued floors, 255, 257–259
 - glue for, 268
 - I-joists for, 261–267
 - nails to use for, 259–260
 - selecting joists with, 249
- flooring
 - adhesive backs on, 570
 - carpeting as, 570
 - causes of squeaks in, 557, 571–572
 - ceramic tile, 568–569
 - essential qualities of, 555
 - glueless, 561–566
 - laminated, 560
 - materials for, 555–556
 - minimizing squeaks in, 557–558
 - nailing, 558–560
 - parquet, 566–567
 - resilient, 569, 570, 571
 - soundproof, 560, 566
 - waxless, 569–570
 - with wood strips (*see* wood strip flooring)
- floor joists
 - building codes for, 199
 - cutting schedule for, 256
 - determining length of, 199
 - gluing subfloor to, 255
 - lumber and sizes for, 253
 - lumber ties for, 249, 250
 - resistance to bending over girder, 217–218
 - selecting, 249
 - setting, 249
 - and strip flooring, 557
- floor-plate hinge, 582, 584
- floors
 - causes of squeaks in, 557, 571–572
 - glued, 255, 257–259
 - installing ceramic tile on, 600
 - minimizing squeaks in, 557–558
 - spacing at panel edges of, 258
 - typical weights of, 43
- floor tile, 600
- flues
 - clay lining for, 136, 148
 - for coal-burning furnaces, 136
 - diagram of, 138, 148
 - fireproof lining for, 136
 - for gas-fired furnaces, 136
 - protecting from eddy currents, 156–157
 - temperature ranges in, 136–137
- flush doors
 - description of, 573, 589
 - hanging, 579–582, 583
- fly ash, 20, 32
- flyers, 539
- Foamglas, 80, 422
- folding stairs, 544, 546
- footing drains
 - description of, 63–64
 - diagram of, 61
 - functioning of, 60, 61
 - placing, 66
 - in relation to septic systems, 2
- footings
 - adfreezing of, 49
 - defined, 35, 81
 - finding total load on, 218–220
 - and frost line, 48
 - for frost-protected shallow foundations, 77
 - heat-loss path under, 77
 - IDR footer-blocks, 38, 39
 - loads on, 39–44
 - minimum width of, 36
 - from National Concrete Masonry Association (NSMA), 35–36, 38, 39
 - nonreinforced width of, 39
 - for permanent wood foundations (PWF), 70, 71

674 Index

- footings (*continued*)
 - purpose of, 35
 - and rotting of wood, 210–211
 - sizing, 37, 38–44
 - stepped, 46–48
- formaldehyde emissions, 420–421
- forms, for concrete, 96
- foundations
 - adfreezing of, 49
 - backfilling for, 66–68
 - capillarity of, 54–55
 - causes of cracks in, 57
 - for chimneys, 139
 - for concrete block walls, 110, 113, 114
 - condensation on, 210–211
 - controlling cracking of, 46, 47
 - controlling shrinkage of, 46
 - and crawl spaces, 49–50
 - damp proofing, 55–58
 - defined, 35
 - design details for, 36–38
 - drainage for, 81
 - drain screens, 60–62, 63
 - footings for (*see* footings)
 - frost protection of, 47–49, 73, 76–81
 - permanent wood (PWF), 68–73, 74–75
 - purpose of, 35
 - reinforcing, 45–46
 - Rub-R-Wall coating for, 55, 56, 57
 - slabs-on-grade, 50–54
 - stepped footings for, 46–48
 - subsurface drainage systems for, 62–66
 - thickness of, 81
 - types of, 35, 81
 - use of rebar in, 45–46
 - waterproofing, 58–60
- foundation sills
 - anchorage of, 196
 - balloon framing of, 194–195
 - defined, 193–194
 - length of, 196
 - placing, 198
 - plank-and-beam construction of, 195
 - sealers for, 198
 - size of, 194–196
 - splicing, 196
 - western-frame construction of, 195
- foundation walls
 - framing for permanent wood foundations (PWF), 71–73
 - insulation thickness for, 80
 - protecting during backfilling, 67
 - typical weights of, 43
- frames
 - bracing corners of, 362, 364–367
 - collar beams for, 202
 - construction terms for, 208
 - corner studs for, 200, 201
 - for doors, 576–577
 - dormers in, 202–204
 - fire stops in, 205–206
 - floor joists in, 199
 - foundation sills for, 193–198
 - girders for, 198
 - headers for, 200
 - hip roof of, 202
 - interior partitions in, 199–200
 - lumber for, 189
 - rafters for, 200–202
 - reinforcing walls of, 367
 - stairways in, 204–205
 - for stairwells, 531–532
 - tributary area of, 216–217
 - weight distribution on, 216–217
- framing
 - balloon-frame construction, 190–191, 194–195
 - around chimneys and fireplaces, 206–207
 - engineered system for, 274–275
 - of exterior walls (*see* outer wall framing)
 - of floors (*see* floor framing)
 - methods of, 190–193
 - modular, 275–277
 - around openings, 200

- plank-and-beam construction, 191–192
 - of roof (*see* roof framing)
 - of walls (*see* outer wall framing; wall framing)
 - western-frame construction, 192–193
 - framing square
 - on common rafters, 305–306
 - for end cut of rafter, 307
 - finding length of rafters with, 301–303
 - importance of, 291
 - for octagon rafters, 321–322
 - reading, 304
 - table length on, 308
 - framing table method, 316
 - free-draining membranes, 60–62, 63
 - French drain, 63–64
 - frost
 - causes of, 48
 - depth of penetration, 78, 79
 - protecting foundations from, 47–49
 - frost lines, 48–49, 81
 - frost-protected shallow foundations, 73, 76
 - basis of, 76–77
 - design details for, 78
 - footings for, 77
 - and freezing degree days, 78, 79
 - ground insulation for, 81, 82–83
 - for Hoult houses, 76
 - insulation of foundation walls in, 80
 - international developments for, 77–78
 - site preparation for, 78
 - subslab insulation for, 78–80
 - for Usonian houses, 76
 - frozen soil, laying foundations in, 47–49
 - fungi
 - conditions for growth of, 175–176, 209–210
 - description of, 175
 - killing, 176
 - furring strips
 - adhesives applied to, 506
 - installation of wallboard to masonry with, 475, 476
 - installed over insulation, 475, 477
 - installing horizontally, 498, 504
 - leveling, 521
 - mounting, 475, 477
 - for paneling, 520–523
 - on plasterboard, 467, 470
 - for prefinished wallboard, 498, 504, 505
- G**
- gable-end finish, 358–359
 - gable-end louvered vents
 - airflow patterns with, 606–607, 608–609
 - combined with soffit vents, 605, 608–609
 - description of, 603
 - effect of wind on, 606–607
 - exhaust vent of, 605, 606
 - intake vent of, 606
 - and moisture removal, 616
 - strengths and weaknesses of, 603
 - gable-end walls, 277
 - gable-roof dormer, 204
 - gable roofs
 - cornice on, 357–358
 - description of, 292
 - popularity of, 292
 - gambrel roof, 292, 293
 - garage doors
 - advantage of, 583
 - automatic openers for, 585, 587–588
 - designs for, 585, 587
 - matching architecture with, 585, 586
 - ordering, 585
 - overhead, 585
 - sections of, 585
 - types of, 585, 586–587
 - uses of, 583

676 Index

- garden walls, 109
 - gas-filled windows, 389, 400
 - Georgia-Pacific Wood I Beam joists, 263, 264
 - girders
 - allowable bending stress (F_b) of, 220–221, 239
 - calculating size of, 211–216
 - construction of, 209
 - damp-proofing, 211
 - defined, 209
 - description of, 198
 - fitch beams for, 240–241
 - horizontal shear in, 220
 - lally column for, 218, 219, 220
 - live and dead loads on, 218
 - load distribution on, 217–218
 - load per lineal foot on, 216, 217
 - materials for, 209
 - reducing span of, 239
 - rot on end of, 209–211
 - selecting, 220–221
 - selecting lumber for, 221, 222–237
 - size and allowable spans of, 238
 - solid versus built-up beams for, 221, 238–239
 - spacing columns of, 239–240
 - steel beams for, 241–244
 - supports for, 198, 218
 - total loading area on, 246
 - and tributary area, 216–217
 - glass fiber shingles, 327
 - glass fire screens, 140
 - gliding window, 396, 400
 - glued floors, 255, 257–259
 - glueless flooring, 561–566
 - glulam, 245–246
 - gravel
 - as drain envelope, 63–64
 - for permanent wood foundations (PWF), 69–70
 - gravel stop, 332
 - green lumber, 169
 - grille blocks, 105, 106, 107
 - grooved panels, 518
 - groove treatment, 511–513
 - grooving, 89–90, 91
 - ground insulation, 81, 82–83
 - grout
 - applying to joints of ceramic tile, 597, 600
 - description of, 18
 - gutters, 349–350
 - gyp-clip, 281
 - Gypsonite
 - cutting, 504
 - manufacture of, 502–503
 - weight of, 503
 - gypsum board
 - applying, 281, 283
 - and foil-faced insulations, 424–427
 - permeance values of, 370
 - Gypsum Construction Handbook*, 281, 283
- ## H
- Handi-Foam, 395
 - handrails, 537, 539, 540, 542
 - hand tamper, 86
 - hard-coat low-E, 388
 - hardboard
 - acoustical, 185
 - buckling of, 375–376
 - manufacture of, 182–183, 186
 - for paneling, 509, 511
 - perforated, 184
 - permeance values of, 370
 - Plylap, 185
 - service, 184
 - as siding, 185, 375–377
 - specialty, 184–185
 - standard, 183–184
 - tempered, 184
 - types of, 183–184
 - weight and density of, 182–183
 - hardboard siding, 185, 375–377
 - hardwood flooring, 555–556
 - hardwoods, 170, 555–556
 - hatchets, used for shingling, 335–336
 - headers
 - classes of, 200

- insulation of, 286, 287
- load-bearing, 200
- nonbearing, 200
- in outer wall framing, 286–288
- sizes of, 200
- header stud
 - framing, 279, 284
 - locating, 279
- hearths
 - dimension of, 148
 - figure of, 150
 - importance of, 148
- heart shakes, 168, 169
- heartwood, 165
- heat flow
 - conduction of, 434
 - rate of, 435
 - thermal conductivity (k) of, 434
 - thermal transmittance of, 436
- heating degree days (HDD), 49
- heat mirror, 389–390, 391
- heat of hydration, 16
- heat transfer
 - by conduction, 387
 - by convection, 386
 - laws of, 387
 - by radiation, 387
 - reduction of, 438
 - in windows, 386–387
- heaving, 89
- hem-fir, 221, 229–230
- high-density batts, 405
- hinged stairs. *See* disappearing stairs
- hinged windows, 399
- hip-and-valley rafters
 - cuts of, 307–313
 - line of measurement for length of, 308
 - side cuts of, 313
- hip-and-valley roof
 - description of, 293–294
 - with jack rafters, 315
 - modifications in, 294
- hip jack rafters, 299, 315–316
- hip rafters
 - backing, 314
 - defined, 299
 - description of, 202
 - diagram of, 299
 - necessity for increasing sizes of, 202
 - tangent value of, 319–320
- hip roofs
 - cornice in, 355–356
 - cutting shingle butts for, 335–337
 - figure of, 293
 - formation of, 292
 - installing metal shingles under wood shingles on, 338
 - laying tin shingles on, 337
 - venting, 619
- hips
 - asphalt shingles for, 345–346
 - wood shingles for, 335–337, 338
- hollow-core doors, 575, 589
- Holtzclaw, Frank, 271
- horizontal shear, 220
- hot-dipped galvanized nails, 259
- hot-weather concreting, 19–20
- Hoult house foundation, 76
- houses
 - cost savings for, 277, 279, 280
 - depressurized, 622–624
 - efficiencies of equipment in, 631
 - frames of (*see* frames)
 - on frost-protected shallow foundations, 76
 - girder size and allowable spans for, 212–215
 - laying out with transit level, 6–9
 - modular framing for, 275–277
 - radon in, 621–624
 - radon prevention in, 625–626
 - requirements for reinforced foundations of, 45
 - sheathing for (*see* sheathing)
 - siding for (*see* siding)
 - staking out location of, 3–10
 - trusses for, 322–323

678 Index

- house wraps
 - exposure time of, 371
 - function of, 368–369, 371
 - importance of, 371
 - recommended brands of, 368, 369
 - requirements of, 367–368
 - taping seams of, 369
 - traditional types of, 367
 - Tyvek, 368, 369, 371, 383, 409
- housing, 541
- H-strips, 376
- hurricane braces, 73, 75
- hydration
 - in concrete, 93, 94–95
 - See also* moisture
- I**
- ice dam shields, 342–343
- IDR footer-blocks, 35–36, 38, 39
- I-joists
 - advantages of, 263
 - description of, 261
 - various brands of, 262–263, 264–267
- impregnated paper felts, 339–342
- InSol-8, 389, 390, 393
- insulating concrete, 428–429
- insulating wallboards, 459–460
- insulation
 - with Airkrete, 428–429
 - with cellular plastics (*see* cellular plastics)
 - with concrete, 428–429
 - for concrete-block walls, 125, 127–128
 - convection through, 426, 427
 - cooling load factors for, 634
 - cost of, 442
 - cotton, 429–430
 - determining thickness of, 80
 - energy savings from, 631
 - for exterior walls, 269
 - fiber saturation point of, 430
 - foil-faced, 424–427
 - of foundation walls, 80
 - function of, 439
 - ground, 81, 82–83
 - of headers, 286, 287
 - and heat flow basics, 434–437
 - heating load factors for, 635
 - loose-fill, 407–410
 - mineral fiber, 404–140
 - permeance values of, 370
 - between plasterboard and masonry walls, 475, 477, 478
 - with radiant barriers (*see* radiant barriers)
 - recent history of, 403
 - resistance of, 435
 - R-value of, 457
 - savings with additions to, 451, 452
 - subslab, 78–80
 - thermal conductivity (*k*) of, 434
 - thermal transmittance of, 436
 - types of, 404, 457
 - with vapor diffusion retarders (*see* vapor diffusion retarders (VDR))
- Insul-Cot, 429–430
- in-swinging windows, 399
- interior partitions, 199–200
- interior walls
 - backer board for, 460
 - building, 123, 124
 - with cellulose, 410–416
 - dealing with dampness in, 522–524
 - deep-wall construction, 484–485
 - finishing inside corners of, 494, 495
 - finishing joints of, 488, 490, 491–495
 - finishing outside corners of, 494, 496, 497
 - fireproof, 477, 479–488
 - furring strips on, 467, 470
 - installing paneling on uneven surfaces of, 519–522
 - insulating wallboards, 459–460
 - junction with outer wall, 285–286

Index **679**

- locating high spot on, 520, 521
 - metal, 480–483
 - moisture-resistant board for, 460
 - paneling for (*see* paneling)
 - placing prefinished wallboard over, 501–502, 508
 - plasterboard for (*see* plasterboard)
 - of prefinished wallboard (*see* prefinished wallboard)
 - problems in construction of, 524–526
 - scribing, 518
 - single-layer construction of, 462–464, 465
 - sound insulation with, 467, 468–471
 - two-layer construction of, 464–465, 468–469
 - wood-derived, 410–411
- J**
- jack rafters, 299
 - cuts in, 317–319
 - finding length of, 316–317
 - method of tangents for, 319–320
 - types of, 315
 - Jacobs house, 76
 - jamb, 577–578, 579
 - jitterbug, 86
 - joint compounds, 488
 - applying, 490–494, 495
 - applying to inside corners of walls, 494, 495
 - applying to outside corners of walls, 494, 496, 497
 - joints
 - of ceramic tile, 597, 600–601
 - in concrete block walls, 129–131
 - for exterior walls, 129
 - finishing, 488, 490, 491–495
 - on girders, 209
 - for interior walls, 129
 - sealing, 488, 526
 - tooling of, 130, 131
 - joists
 - balloon framing of, 194
 - cantilevered in-line system of, 251–255
 - cutting schedule for, 256
 - engineered, 261–267
 - fastening metal ceilings to, 488
 - in floor (*see* floor joists)
 - lapped, 217
 - lineal footage of, 276
 - lumber and sizes for, 253
 - in modular framing, 275–277
 - parallel to partitions, 199–200
 - partitions at right angles to, 200
 - plank-and-beam construction of, 195
 - for stairwells, 531–532
 - western-frame construction of, 195
- K**
- kiln-dried lumber, 169, 210
 - kips, 239–240
 - known reference line, 3–6
 - kraft paper, permeance values of, 370
- L**
- lally columns, 218, 219, 220, 239–240
 - laminated layered products, 244
 - laminated plank floors
 - assembling glueless planks of, 562–565
 - cutting last row of, 565–566
 - disassembling, 565
 - installing, 561–566
 - installing under doorjamb, 566
 - necessary conditions for, 560–561
 - laminated veneer lumber (LVL), 244, 246, 261, 266–267
 - landing, 541
 - lapped joists, 217
 - large-head nails, 379
 - large-scale climate simulator (LSCS), 407–408
 - laser levels, 6, 8
 - lean-to, 291

680 Index

- let-in corner bracing, 364–367
 - level line, 298
 - levels, laying out buildings with, 6–9
 - light-framed construction, 190–193
 - line length, 298
 - line of travel, 529
 - lintels
 - placing in concrete-block walls, 120, 123–124
 - reinforcing, 123
 - liquid-applied coating materials, permeance values of, 370
 - live load (LL), 39, 218
 - load-bearing headers, 200
 - Lodgepole pine, 230–231
 - longest jack method, 316
 - long-handled float, 88
 - lookouts, 355
 - loose-fill insulation, 407–410
 - energy savings from, 631
 - Louisiana-Pacific, engineered joists from, 263, 265–266
 - louver doors, 575
 - low-E glazing, 388
 - low emissivity coatings, 388
 - lug sills, 124
 - lumber
 - air-drying, 169, 170
 - allowable bending stress (F_b) of, 220–221
 - classes of, 187
 - common, 188–189
 - computing board feet of, 189–190
 - cutting at mill, 166–167
 - decay of, 174–176
 - defects in, 168–169
 - defined, 166
 - engineered, 244–246, 261
 - for framing, 189
 - for girders, 212–215
 - grades of, 169–170, 187–189
 - green, 169
 - hardboard, 182–185
 - for joists, 253–254
 - kiln-dried, 169, 210
 - laminated veneer, 244, 246, 261, 266–267
 - measuring quantities of, 207
 - particleboard, 181–182
 - for permanent wood foundations (PWF), 70
 - plain sawed, 166, 167
 - plywood (*see* plywood)
 - quartersawed, 166
 - select, 187–188
 - selecting for girders, 221, 222–227
 - selection of, 169–174
 - selling, 166–167
 - sizes of, 166–167, 187, 188
 - strength properties of, 222–237
 - types of trees for (*see* trees)
 - See also* wood
 - lumber ties, 249, 250
- M**
- Mansard roof, 294, 295–296
 - masonry cement. *See* mortar
 - masonry walls
 - applying adhesive to, 474
 - dealing with dampness in, 522–524
 - dealing with uneven surfaces of, 522, 523, 524
 - installing plasterboard over, 472, 474–477
 - mesh
 - for attic vents, 604
 - securing for tile installations, 599
 - metal anchors, 196, 197
 - metal ceilings, 479, 488
 - metal corners, 381
 - metal forms, for fireplaces, 150–155
 - metal joists, 488
 - metal walls
 - handling ceiling and base finishing of, 482–483
 - intersections and jambs in, 481
 - with metal studs and tracks, 480
 - method of tangents, 319–320

- Micro-Lam, 244
 - mid-height backer, 271–272
 - mildew, inside of exterior corners, 277, 279, 281, 282
 - mineral fiber
 - as batts, 404–405
 - loose-fill insulations, 407–410
 - manufacture of, 404
 - spray-in, 405–407
 - miter cut, 312
 - mitered corners, 380–381
 - mixers
 - conveyors for, 21, 22
 - discharging concrete from, 21
 - motorized buggies for, 21, 23
 - modular framing, 275–277
 - moisture
 - from air leakage, 432
 - in attics, 616
 - barriers versus retarders for, 430–431
 - controlling in attics, 604, 620
 - in hardboard siding, 375–376
 - and insulation, 430
 - in masonry walls, 522–524
 - preventing problems with, 453
 - and radiant barriers, 440, 452–453
 - in spray-in cellulose, 415
 - surfaces impervious to, 591
 - in wood strip flooring, 557
 - moisture-resistant board, 460, 472, 473
 - mold, inside of exterior corners, 277, 279, 281, 282
 - monolithic, 460–461
 - monolithic slabs, 76
 - mortar, 18
 - applying to concrete blocks, 118–119
 - for chimneys, 137–138
 - versus concrete, 114–115
 - for concrete blocks, 114–115
 - factors for strength of, 115
 - for installing sill plates, 198
 - placing for corners, 117
 - squeezed out of joints, 119
 - standard for, 115
 - types of, 115
 - Mountain hemlock, 231–232
 - mudding, 507–508, 509, 510
 - mud plates, 198
 - mullion, 399
 - multifaced fireplaces, 139–140
 - multiple-pane window, 385
- N**
- nails
 - for applying asphalt shingles, 344–345
 - cement-coated, 259
 - cut, 260
 - for flooring, 558–560
 - for framing floors, 259–260
 - for installation of siding, 379–380
 - for installing prefinished wallboard, 498, 503
 - large-head, 379
 - noncorrosive-type, 379–380
 - for paneling, 518–519
 - placement in shingles, 353
 - for plasterboard installations, 462–463, 464
 - rust-resistant, 379
 - for slate roofing, 347
 - small-head casing, 379
 - steel wire, 379
 - and underlayment, 342
 - withdrawal resistance of, 259
 - in wood shingles, 335
 - National Association of Home Builders (NAHB), 270–271
 - National Building Code* (BOCA), 48. *See also* building codes
 - National Concrete Masonry Association (NCMA), 35–36, 38, 39
 - natural cement, 17–18
 - neoprene, 59
 - Net Free Venting Area (NFVA), 604–605, 612, 615–616
 - newels, 537, 539, 541
 - nippers, 597

682 Index

nonbearing headers, 200
 nonconforming lots, 2
 noncorrosive-type nails, 379–380
 non-load-bearing walls, 114, 115
 normal concrete, 32
 admixtures for, 18–20
 essential ingredients of, 17
 mixed with water, 17
 natural cement, 17–18
 nosing, 543
 no-wax floors, 569–570

O

octagon rafters, 299, 320–322
 offset stakes, 10
 ogee roof, 294, 295
 one-story houses
 cost savings for, 277, 279, 280
 foundation plan for, 216
 girder size and allowable spans
 for, 212–213
 open cornices, 356–357
 optical levels, 6, 7
 Optimum Value Engineering,
 270–271
 oriented strand board (OSB), 182,
 183
 gluing, 258
 for sheathing, 362
 surface unevenness of, 259
 outer wall framing
 applying gypsum board to, 281,
 283
 in Arkansas House, 271–274
 corner studs of, 277, 289
 of doors, 284–285
 Engineered framing system for,
 274–275
 floating interior angle
 application, 281, 283
 headers in, 286–288
 insulation of, 269
 modular framing, 275–277
 mold and mildew in, 277, 279,
 281
 preframing conferences for, 288
 reducing costs of, 277, 279, 280

spacing studs for, 269, 289
 value engineering for, 269–271
 of windows, 284–285
 outer walls
 air infiltration to, 371
 convection loop, 426, 427
 junction with interior walls,
 285–286
 layers of, 189
 treating corners of, 380–381
 out-swinging window, 399
 Owens Corning Fiberglass
 Company, 404

P

paint
 permeance values of, 370
 as vapor diffusion retarder
 (VDR), 433
 paneled doors, 573, 589
 paneling, 527
 adhesive installation of, 519, 520
 construction that causes
 problems for, 524–526
 cutting, 516–517
 and damp walls, 522–524
 faces of, 508
 figuring required amounts of,
 513–514
 fitting into corners, 517–518
 furring strips for, 520–523
 groove treatment of, 511–513
 installation of, 514–522, 523,
 524
 installing on uneven surfaces,
 519–522, 523, 524
 locating studs for, 514, 515, 516
 measuring, 515–516
 measuring floor-to-ceiling height
 for, 515
 nails for, 518–519
 plywood, 509, 511
 securing, 517–519
 storage of, 514, 515
 variety of, 508, 511
 parallel strand lumber (PSL), 261
 parging, 57

Index **683**

- particleboard, 181–182, 186
 - for paneling, 509, 511
- partitions
 - fireproof, 479, 480–485
 - interior, 199–200
 - mortar for, 115
 - parallel to joists, 199–200
 - raising, 487–488
 - at right angles to joists, 200
 - securing to exterior wall, 285–286
 - semisolid, 479, 484, 486–488, 490, 491
- patio doors, 588–589
- patterned block, 106
- pegboard, 184
- pentane, 418
- perforated felt, 331
- perforated films, 368
- perforated tape, 490, 492–493
- performance codes, 249
- Pergo Presto glueless flooring, 561–566
- perlite, 423–424
- permafrost, laying foundations to, 47–49
- permanent wood foundations (PWF), 68–69
 - advantages of, 69
 - backfilling for, 73, 75
 - completed, 75
 - fasteners for, 71
 - footings for, 70, 71
 - lumber treatment for, 70
 - polyethylene sheeting for, 72, 74
 - preparing site for, 69–70
 - wall framing for, 71–73
- permeance, 368, 370
- phenolic, 418
- pine trees, 230–231, 233–236
- pipes, in crawl spaces, 49–50
- pitch, 298
- pitch roof, 292
- pith, 165
- plank-and-beam construction, 191–192, 195
- plank floors
 - assembling glueless planks of, 562–565
 - cutting last row of, 565–566
 - disassembling, 565
 - installing, 561–566
 - installing under doorjamb, 566
- plaster, permeance values of, 370
- plasterboard
 - adhesives for, 463, 466
 - Airtight Drywall Approach (ADA) for, 371
 - backer board, 460
 - backing material for tiled areas, 472, 473, 526
 - construction with, 461–477, 526
 - expansion joints in, 467
 - fastening shelf brackets to, 486
 - fastening to studs, 462–464, 465–466
 - finishing joints of, 488, 490, 491–495
 - fire retardation with, 462
 - furring strips on, 467, 470
 - insulating wallboards, 459–460
 - laminated directly to foam insulation, 475, 478
 - laminating, 491
 - over masonry walls, 472, 474–477
 - moisture-resistant, 460
 - mounting to suspended ceiling structures, 489
 - nails for installation of, 462–463, 464
 - prebowing of, 464
 - ratings for, 461
 - and semisolid partitions, 479, 484, 486–488, 490, 491
 - as single layer on wood studs, 462–464, 465–466
 - sizes of, 459, 526
 - sound insulation with, 462, 467, 468–471
 - two-layer construction of, 464–465, 468–469
 - vinyl-covered, 460–461

684 Index

- plasterboard ceilings, 467, 471
- plastic sheets, for curing concrete, 96, 97, 98
- plastic siding, 382
- plumb line, 298
- Plylap, 185
- plywood
 - APA performance-rated, 179
 - application of adhesive to, 183
 - bracing corners with, 362
 - exposure durability of, 177–179
 - exposure 1 panels, 178–179
 - exposure 2 panels, 179
 - exterior panels, 178
 - grade designations for, 176, 178
 - interior panels, 179
 - lap siding with, 185
 - manufacture of, 183
 - performance-rated panel
 - composition of, 183
 - permeance values of, 370
 - popular type of, 185
 - sanded, 177, 180
 - specialty panels, 181
 - splice patterns for, 257
 - touch-sanded, 177, 180
 - trees for, 176
 - unsanded, 177
 - veneer grades of, 178
 - as wall sheathing, 361–362, 365, 382
- plywood headers, 286–288
- plywood paneling, 509, 511, 527
- plywood sheathing, 361–362, 365
- plywood siding, 374–375
- polyethylene sheeting, 433
 - for foundation walls, 72, 74
 - permeance values of, 368, 370
 - value of, 57–58
 - as vapor and air barrier, 430–431
- polyisocyanurate (PIRs), 417, 418
- Polymaster, 421–422
- polymeric asphalt, 59
- polystyrene, 416
 - expanded (EPS), 417
 - extruded expanded (XPS) (*see* extruded expanded polystyrene (XPS))
- polyurethane foam, 395, 369, 371
- polyurethanes (PURs), 417, 418
- ponding, 96
- porch steps, 537–538, 540
- Portland cement, 15–16
 - ingredients of, 16
 - and mortar, 115
 - types of, 16–17
- pozzolans, 20, 32
- prefabricated fireplaces, 157–161
- prefinished wallboard, 526–527
 - adhesives for, 498, 500, 505–506
 - cutting, 496–497, 498, 499
 - cutting circles in, 497, 501
 - cutting squares in, 497, 502
 - description of, 495
 - FiberBond, 502–504
 - furring strips for, 498, 504, 505
 - Gypsonite, 502–504
 - installation methods for, 495–496
 - installing, 498, 500–502
 - mudding caulk on, 507–508, 509, 510
 - nailing, 498, 503
 - placing over walls, 501–502, 508
 - pre-installation considerations for, 496
 - push-on trim for, 501, 507
 - rectangular cutouts in, 502
- preframing conferences, 288
- present value tables, 447–452
- pressure-driven radon, 624
- Prest-on clips, 272, 274, 281, 283, 288
- primed siding, 185
- property lines
 - paralleling building with, 6
 - on plot plan, 4
 - as reference point, 3
- push-on trims, 501, 507
- pyramid roof, 292–293
- Pythagorean theorem method, 10

R

- radiant barriers, 427
 - adding conventional insulation
 - to attics with, 442
 - and attic ventilation, 453, 456
 - average reduction in ceiling heat flow due to, 443–444
 - characteristics of, 440
 - versus conventional insulation, 439
 - cooling load factors for, 632
 - cost of installation, 440–441
 - description of, 437–438
 - effect of dust on, 445
 - effect on heating and cooling bills, 442–452
 - effect on roof temperatures, 453
 - emissivity of, 438–439, 440
 - fire ratings of, 454
 - functioning of, 438–439
 - function of, 437–438
 - heating load factors for, 633
 - installation of, 438, 454–456
 - and insulation levels, 444–445
 - locations for, 454–456
 - nonenergy considerations for, 452–454
 - potential for moisture
 - condensation on, 452–453
 - and reductions in summer utility bills, 444
 - reflective surface of, 440, 456
 - reflectivity of, 438–439, 440
 - roof-mounted, 439
 - safety considerations for, 457
 - savings on heating and cooling bills with, 446–452
 - savings with attic floor installations of, 448
 - savings with installations draped over rafters, 450
 - savings with installations on rafter bottoms, 449, 451–452
 - tests on effects of, 442–445
 - and water vapor, 440
 - during winter, 439
- radiation, 387
- radon
 - danger of, 621
 - detection of, 621
 - diffusion-driven, 624
 - entry routes of, 623
 - half-life of, 621
 - in household water, 622–623
 - in houses, 621–624, 628–629
 - methods for reduction of,
 - 624–628
 - pressure-driven, 624
 - preventing entry into houses,
 - 625–626
 - site evaluation for, 624–626
 - source of, 621
 - and subslab ventilation, 626–628
- rafters, 296
 - backing, 314
 - collar beams for, 202
 - cuts of, 305–313
 - finding length of, 301–305
 - with full tail, 306
 - function of, 200
 - hip, 202
 - jack, 315–320
 - length of, 202
 - octagon, 320–322
 - parts of, 299
 - side cuts of, 313
 - size of, 201
 - spacing of, 201
 - span of, 201
 - types of, 298–300
 - using framing square on,
 - 301–303
- raked joint, 129
- rake finish, 358–359
- ready-built fireplace forms,
 - 150–155
- ready-mix trucks, 21, 32
- rebars, 23–26, 32
 - for concrete-block walls,
 - 109–110, 113
 - placement of, 26
 - in residential foundations, 81
 - supports for, 26–30

686 Index

- rebars (*continued*)
 - used in residential foundations, 45–46
- Red pine, 233
- redwood, 174, 175
- reflective insulation (RI), 424–425
- reflectivity, 438–439
- reinforcement bars. *See* rebars
- reinforcing rods
 - in foundations for walls, 114
 - for lintels, 123
- RE-RINGS, 30
- residential foundations. *See* foundations
- resilient flooring, 569, 570, 571
- resistance (R), 435–436
- retarders, 19–20
 - of air (*see* house wraps)
 - vapor diffusion (*see* vapor diffusion retarders (VDR))
- Richardson house, 76
- ridge vents, 612–615
 - shingle-over, 618–619
- rigid exterior foam sheathing, 362, 364–367
- rise in inches, 297, 303
- riser, 543
- riser-to-tread ratio, 530–531
- rock wools, 404, 407
- roll roofing, 327, 329–331
 - permeance values of, 370
 - and slope of roofs, 328
- Romex wire, 272–273
- roof framing
 - asphalt shingles, 339–346
 - basics of, 296–298
 - jack rafters for, 316–317
 - prefabricated roof trusses for, 322
 - rafters for (*see* rafters)
 - tools for, 291
- roofing
 - and building regulations, 351
 - for built-up roof (BUR), 331–333
 - drip-edge flashing for, 343–344
 - fire resistance of, 351
 - gutters and downspouts for, 349–350
 - roll, 329–331
 - selecting materials for, 350–351
 - with slate, 346–349
 - and slope of roof, 328
 - supports for repairs in, 348
 - types of, 327–328, 352
 - typical weights of, 43
 - wood shingles, 333–339
 - See also* shingles
- roof louvers, 608
- roof materials. *See* roofing
- roofs
 - common types of, 297
 - conical, 296
 - construction of, 296–298
 - cornice of, 355–360
 - cut of, 298
 - detection of leaks in, 351–352
 - dome, 296, 297
 - dormers in, 202–204
 - double-gable, 294, 295
 - drip-edge flashing for, 343–344
 - effect of radiant barriers on
 - temperatures of, 453
 - effect of solar energy on, 439
 - framing (*see* roof framing)
 - gable, 292
 - gambrel, 292, 293
 - gravel stop on, 332
 - gutters and downspouts for, 349–350
 - hip, 202, 292, 293
 - hip-and-valley, 293–294
 - ice dams on, 343
 - impregnated paper felts for, 339–342
 - on lean-to, 291
 - level line of, 298
 - line length of, 298
 - Mansard, 294, 295–296
 - octagon, 320–322
 - ogee, 294, 295
 - pitch, 292
 - pitch of, 298
 - plumb lines of, 298

- pyramid, 292–293
 - rafters for (*see* rafters)
 - rise in inches of, 297
 - saw-tooth, 291–292
 - selecting roofing materials for, 350–351
 - on shed, 291
 - shingling hips of, 335–337
 - shingling valleys of, 337–339
 - slope of, 328–329
 - span of, 297
 - total rise of, 297
 - total run of, 297
 - types of, 291–296
 - units of measurement for, 297
 - roof sheathing, 359–360
 - roof trusses
 - advantages of, 322
 - configurations of, 324
 - cost of, 323
 - cutting ceiling joists in houses with, 546, 547, 548
 - labor requirements for, 323
 - lumber requirements for, 323
 - prefabricated, 322–325
 - selecting materials for, 324–325
 - spacing of, 323
 - rot, on ends of girders, 209–211
 - routers, 516
 - rubberized asphalt, 58–59
 - rubber trowel, 600
 - Rub-R-Wall coating, 55, 56, 57
 - Rumford fireplaces, 139, 162
 - Russian fireplaces, 140–142
 - R-values, 392
 - of Air Krete, 429
 - of cellulose, 409, 412–413, 414
 - defined, 458
 - of fiberglass, 405
 - and heat flow basics, 434–437
 - and insulation costs, 442
 - of Insul-Cot, 429
 - of perlite, 424
 - of phenolic, 418
 - of Polymaster, 422
 - of reflective insulations, 424–426
 - of tripolymer foam, 421
 - of urea formaldehyde, 420
 - of vermiculite, 423
- S**
- sapwood, 165
 - sash doors, 573, 589
 - hanging, 579–582, 583
 - Saskatchewan Conservation House (SCH), 430–431
 - saw-tooth roof, 291–292
 - screeding, 85, 98
 - screen block, 105–106, 108
 - screen mesh. *See* welded-wire fabric (WWF)
 - screws, for plasterboard installations, 462, 465
 - seasonable high water table (SHWT), 2
 - segregation
 - of cement aggregates, 20–21
 - preventing, 21
 - seismic zone map, 45
 - select lumber, 187–188
 - semisolid partitions, 479, 484, 486–488, 490, 491
 - septic systems
 - and building locations, 1–2
 - and seasonable high water table (SHWT), 2
 - service hardboard, 184
 - setbacks, 1
 - shading coefficient (SC), 396
 - shakes, 377
 - shallow foundations
 - frost-protected, 73, 76–81
 - types of, 35, 36
 - sheathing
 - diagonal, 361, 363–364, 382
 - fiberboard, 361
 - function of, 361
 - plywood, 361–362, 365
 - rigid exterior foam, 362, 364–367
 - for roof, 359–360
 - standard for testing, 366
 - types of, 361
 - wood, 361, 363

688 Index

- sheathing paper, 331–332, 367–368
 - exposure time of, 371
 - function of, 368–369, 371
 - importance of, 371
 - recommended brands of, 369
- sheds, 291
- shelf brackets, 486
- shims
 - under girders, 20
 - leveling floor joists with, 249
- shingles
 - aligning, 344
 - asphalt, 327, 330, 339–346
 - glass fiber, 327
 - ridging of, 340
 - types of, 342
 - wood, 327, 328, 333–339, 377
- ShingleVent II, 618
- shingling hatchet, 335–336
- shortest jack method, 316
- siding
 - aluminum, 381–382
 - bevel, 372, 272
 - drop, 372, 374
 - hardboard, 185, 375–377
 - installing, 378–381
 - moisture content of, 371–372
 - nails for application of, 379
 - plywood, 374–375
 - spacing for, 378
 - square-edge, 372–373
 - starting, 378, 379
 - treated, 375
 - treating corners of, 380–381
 - vertical, 373–374
 - vinyl, 382
 - wood, 371–377
- sills
 - foundation, 193–196, 198
 - function of, 123
 - lug, 124
 - placing in concrete-block walls, 120, 123–124
 - slip, 123–124
- sill sealers, 198, 207
- Simpson H1 hurricane braces, 73, 75
- Simpson mud anchors, 197
- single-face fireplaces, 139
- single-story houses. *See* one-story houses
- slabs-on-grade, 50–51
 - curing time for, 95
 - preparation of site for, 53–54
 - reinforcing, 51, 52
 - types of, 51–53
- slag wools, 404
- slate roofing, 327
 - colors and sizes of, 347
 - examining, 348–349
 - installing, 347–349
 - manufacture of, 346–347
 - replacing, 347–348
- sliding doors, 582–583, 584
- slip sills, 123–124
- slotted polyethylene pipe, 64–66
- slump, 30–31, 32
- slump block, 104–105
- slump test, 31
- small-head casing nail, 379
- small-line concrete pumps, 21
- smoky fireplaces, 156–161
- soffits, function of, 355
- soffit vents
 - airflow patterns with, 607–608, 613
 - combined with gable vents, 608–609
 - dimensions of, 615
 - double-louvered, 616, 617
 - excessive venting from, 615
 - for hip roofs, 619
 - and moisture removal, 616
 - Net Free Venting Area (NFVA) of, 615–616
 - placing, 616–617
 - and rain penetration, 616
 - with ridge vents, 613, 614, 615
 - screening, 616
 - selecting, 615–616
 - types of, 612
- soft-coat, low-E, 388

- softwood flooring, 555
- softwoods, 170, 555
- soils
 - acquiring information on, 53
 - for backfilling, 67
 - bearing capacities of, 37–38, 40–42, 81
 - characteristics of, 40–42
 - and foundation systems, 35
 - frozen, 47
- solid-core doors, 573–574
- solid girders, 221, 238–239
- solid wood sheathing, 361, 363
- soundproof floors, 560, 566
- Southern pine, 221, 234–235, 325
- spaced roofing boards, 328–329
- span
 - allowable for girders, 238
 - allowable for one-story houses, 212–213
 - allowable for two-story houses, 214–215
 - of rafters, 201
 - reducing for girders, 239
 - of roofs, 297
- Sparfil, 428
- specialty hardboard, 184–185
- specification codes, 249–251
- spire roof, 296
- split block, 101, 103, 104
- spray-applied rock wool, 407
- spray-in cellulose, 415–416
- spray-in mineral fiber, 405–407
- spray-in polyurethane foam (PUR), 395, 369, 371
- spring clips, 471
- spruce-pine-fir, 221, 235–236
- spruce trees, 227–229
- square-edge siding, 372–373
- squeegees, 597, 600
- stack effect, 624
- staircase, 543
- stairs
 - basement, 537, 538
 - circular, 539, 542
 - construction of, 529–539
 - design of, 531
 - disappearing, 544–552
 - exterior, 537–538, 540
 - folding, 544, 546
 - front string of, 539
 - functional types of, 529
 - glossary of terms for, 539–544
 - half-space of, 540
 - housing for, 541
 - landing of, 541
 - line of travel of, 529
 - molding on edge of treads of, 536
 - ratio of riser to tread in, 530–531
 - riser heights of, 530–531
 - run of, 543
 - straight flight of, 543
 - stringers for, 532–536
 - tread of, 544
 - winders of, 529, 544, 545
- stairways, 204–205
 - handrails for, 537, 539
 - headroom in, 552–553
 - newels for, 537, 539
- stairwell, framing, 531–532
- standard hardboard, 183–184
- star shakes, 169
- steel beams, 241–244
- steel frame ceilings, 479, 488, 489
- steel square. *See* framing square
- steel wire nails, 379
- Step 1 caulk, 507, 509, 510
- stepped footings, 46–48
- steps
 - fitting treads and risers to stringer of, 534–535
 - and footings, 46–48
- step-taper pile, 37
- Story Jig, 416
- strand board, 182, 183
- straw, for curing concrete, 98
- stringers
 - cut and mitered, 535–536
 - defined, 543–544
 - fitting outline of tread and risers, 532–533
 - fitting treads and risers to, 534–535

690 Index

- stringers (*continued*)
 - and landing baseboards, 533–534
 - nailed on wall, 534
 - ploughed out, 533
 - types of, 533
 - strip flooring
 - materials for, 555–556
 - wood (*see* wood strip flooring)
 - structures
 - Certificate of Occupancy (CO) for, 12
 - Certified Plot Plan for, 10–11
 - on corner lots, 2
 - covenants for, 1
 - dealing with grades and contours on sites for, 3
 - foundation of (*see* foundations) on nonconforming lots, 2
 - required documentation for, 1 and septic systems, 1–2 and wells, 1–2
 - zoning ordinances for, 1
 - studs
 - at corner, 200, 201
 - locating, 514, 515, 516, 525
 - out-of-sequence, 525
 - subfloor
 - for plank floors, 560
 - preparing for flooring, 557
 - subslab insulation, 78–80
 - subslab ventilation, 626–628
 - subsoil insulation, 83–84
 - subsurface drainage systems, 62–66
 - super insulation, 403
 - super-plasticizers, 20
 - Swiggle Strip, 393
 - swinging doors, 582, 589–590
 - switchable glazings, 394
 - swivel spring hinges, 582, 584
- T**
- Tailored Chemical Products, Inc., 421
 - tamping, 86
 - taping, 3
 - tar felt, permeance values of, 370
 - tempered hardboard, 184
 - theoretical draft, 134
 - Thermacube, 408
 - Thermadry, 62, 63
 - thermal conductivity (*k*), 434
 - thermal insulation, permeance values of, 370
 - Thermo-Ply sheathing, 366
 - tile. *See* ceramic tile
 - tile cutters, 597, 599
 - tile nippers, 597
 - tile roofs, 327, 329
 - timber, 166
 - TJI brand joists, 262–263
 - tooling devices, 131
 - total rise, 297, 303
 - total run, 297, 303
 - transit levels, laying out buildings with, 6–9
 - treated siding, 375
 - trees
 - Alpine fir, 228–229
 - Balsam fir, 222
 - characteristics of wood from, 171–173
 - Douglas fir, 221, 223–225
 - Eastern hemlock, 226–227
 - Eastern spruce, 227–228
 - Engelmann spruce, 228–229
 - layers of, 164–166
 - Lodgepole pine, 230–231
 - Mountain hemlock, 231–232
 - pith of, 165
 - for plywood, 176
 - Red pine, 233
 - Southern pine, 221, 234–235
 - used for wood siding, 371
 - Western hemlock, 237
 - tributary area, 216–217, 219
 - tripolymer foam, 421
 - trowel blades, 89
 - for mortar, 118–120
 - for smoothing grout, 600
 - troweling, 89
 - trusses
 - advantages of, 322

configurations of, 324
 cost of, 323
 cutting ceiling joists in houses
 with, 546, 547, 548
 labor requirements for, 323
 lumber requirements for, 323
 prefabricated, 322–325
 selecting materials for,
 324–325
 spacing of, 323
 tubing
 from American Drainage
 Systems (ADS), 65–66
 for subsurface drainage,
 63–66
 turbine vents, 610, 611, 620
 Tu-Tuf, 211
 two-story houses, girder size and
 allowable spans for, 214–215
 two-stud corners, 271, 273, 281,
 282
 Type 15 felt, 342, 383
 Type A slabs, 51
 Type B slabs, 52
 Type C slabs, 52
 Type D slabs, 52–53
 Type E slabs, 53
 Type F slabs, 53
 Type K cement, 115
 Type M cement, 115
 Type NA cement, 17–18
 Type N cement, 17–18, 115
 Type O cement, 115
 Type S cement, 115
 Tyvek, 368, 369, 371, 383, 409

U

U-factor, 435–436
 ultimate bearing capacity, 38
 underground drainage systems,
 62–66
 underlayments, 339–342, 343
 unit of run, 297
 urea-formaldehyde, 420–424
 urea-formaldehyde foam
 insulation (UFFI), 128
 Usonian House concept, 76

V

vacuum-sputtered coatings, 388
 valley rafters, 299, 300, 315–316
 tangent value of, 319–320
 valleys
 flashing materials for, 345
 shingling, 337–339
 value analysis (VA), 269, 624–625
 value engineering, 269–271
 vapor diffusion retarders (VDR),
 28
 Airtight Drywall Approach
 (ADA) and, 433
 and attic ventilation, 620
 versus barriers, 430–431
 defined, 369, 383
 holes in, 433
 location of, 433–434
 necessity of, 431–434
 paints used as, 433
 purpose of, 368
 requirements for, 432–433
 veneer grades, 178
 vent area, 604
 ventilation
 of attics (*see* attic ventilation)
 in crawl spaces, 50
 subslab, 626–628
 vermiculite, 423
 vertical siding, 373–374
 vibrating roller compactors, 68
 vibration plate compactors, 68
 vinyl-covered plasterboard,
 460–461
 vinyl-covered wallboard. *See*
 prefinished wallboard
 vinyl siding, 382
 Visionwall, 390, 392
 ‘V’ joint, 129

W

wafer board, 181–182
 for sheathing, 362
 wallboards
 foil-backed, 459–460
 mounting to suspended ceiling
 structures, 489

692 Index

- wallboards (*continued*)
 - prefinished (*see* prefinished wallboard)
- wall braces, 367
- wall framing
 - of exterior walls (*see* outer wall framing)
 - junction of interior and exterior walls, 285–286
 - for permanent wood foundations (PWF), 71–73
- walls
 - calculating heat loss through, 436–437
 - ceramic tile for, 592
 - of concrete blocks (*see* concrete-block walls)
 - conductivity of, 435
 - control joints in, 47
 - convection in, 426, 427
 - dealing with dampness in, 522–524
 - dealing with uneven surfaces of, 520–521, 523
 - exterior (*see* outer walls)
 - horizontal reinforcement bars for, 109–110, 113
 - installing ceramic tile on, 593–600
 - interior (*see* interior walls)
 - junction of exterior and interior, 285–286
 - locating high spot on, 520, 521
 - outer (*see* outer walls)
 - preparing for ceramic tile, 593–594
 - reinforcing, 367
 - sealing space between doors and windows and, 369, 371
 - typical weights of, 43
 - wall tile backing, 472, 473
 - WARM-N-DRI, 61, 62
 - water/cement ratio, 93
 - waterproofing, 58–60
 - backfilling for, 66–68
 - waterproof paper, 96, 98
 - water reducers, 20
 - water vapor diffusion, 431–432
 - waxless flooring, 569–570
 - Weathertight Premier, 364
 - welded-wire fabric (WWF), 26–29
 - alternative to, 53
 - wells, and building locations, 1–2
 - western-frame construction, 192–193, 195, 207
 - Western hemlock, 237
 - wet coverings, 96
 - wet-sprayed cellulose, 415–416
 - wide box cornices, 355–356
 - wide cornice, 358
 - winders, 544, 545
 - windows
 - aerogels in, 394
 - air leakage in, 395–396
 - awning, 396, 400
 - bay, 396, 400
 - bow, 396, 400
 - building concrete-block walls around, 120, 122
 - calculating R-values for, 392–394
 - casement, 399, 400
 - contemporary, 385
 - double-hung, 385, 398–399
 - emissivity of, 387–388
 - fiber glass, 394
 - frame of, 396–397
 - framing, 284–285, 397
 - function of, 385
 - gas-filled, 389, 400
 - gas leakage from, 389
 - gliding, 396, 400
 - heat mirror, 389–390, 391
 - heat transfer in, 386–387
 - hinged, 399
 - installing, 394–395
 - in-swinging, 399
 - low-E glazing of, 388
 - multiple glazings of, 358–386, 387
 - origins of, 385
 - out-swinging, 399

- planning for in concrete-block walls, 116–117
- purchasing, 395
- ratings for, 389
- R-values of, 387
- sash of, 397
- sealing space between wall and, 369, 371
- shading coefficient (SC) of, 396
- spacer for, 393
- Swiggle Strip for, 393
- switchable glazings in, 394
- types of, 396–397
- Visionwall, 390, 392, 393
- wall area covered by, 385
- wind shakes, 169
- windwashing, 279
- wood
 - allowable bending stress (F_b) of, 221
 - balsam fir, 222–223
 - characteristics of, 171–173
 - char zone of, 243–244
 - classifying, 163–164, 170
 - cutting at mill, 166–167
 - decay of, 174–176
 - Douglas fir, 221, 223–225
 - Eastern hemlock-Tamarack, 226–227
 - Eastern spruce, 227–228
 - Engelmann spruce-Alpine fir, 228
 - fungi on, 175–176
 - grains of, 163
 - hardboard, 182–185
 - hem-fir, 221, 229–230
 - importance of, 163
 - layers of, 164–166
 - Lodgepole pine, 230–231
 - Mountain hemlock, 231–232
 - particleboard, 181–182
 - plain sawed, 166, 167
 - plywood (*see* plywood)
 - pressure-treating, 176
 - quarter-sawing, 166
 - Red pine, 233
 - shades of, 163
 - Southern pine, 221, 234–235
 - spruce-pine-fir, 221, 235–236
 - stiffness of, 258
 - strength properties of, 222–237
 - strongest area of, 183
 - used for flooring, 555–556
 - used for sheathing (*see* sheathing)
 - used for siding (*see* wood siding)
 - See also* lumber
 - wood shakes, 377
 - wood sheathing, 361, 363
 - wood shims
 - under girders, 209
 - leveling floor joists with, 249
 - wood shingles, 327, 328
 - amount of lap in, 333, 334
 - better grades of, 352–353
 - cedar, 328–329, 377
 - chalk line method for laying, 335
 - exposed to weather, 333–334
 - gauge-and-hatchet method for laying, 335, 336
 - for hips, 335–337
 - nailing, 335
 - requirements for application of, 333
 - space covered by, 334
 - spaced roofing boards and, 328–329
 - spacing of, 334
 - straightedge method for laying, 335
 - swelling of, 334
 - for valleys, 337–339
 - wood siding
 - bevel, 372, 373
 - drop, 372, 374
 - essential properties required for, 383
 - hardboard, 375–377
 - moisture content of, 371–372
 - plywood, 374–375
 - properties required for, 371
 - square-edge, 372–373
 - treated, 375

694 Index

treating corners of, 380–381
vertical, 373–374
wood strip flooring
causes of squeaks in, 557
delivery conditions for, 557
and floor joist, 557
grades of, 555
installation of, 556–566
laminated plank floors, 560–566
minimizing squeaks in, 557–558
nailing, 558–560
nailing first strip of, 558, 559
nails for, 558
and subfloors, 557

thickness of, 558
woods used for, 355–356
Wright, Frank Lloyd, 76

X

XPS. *See* extruded expanded polystyrene (XPS)

Y

yard lumber, 187–189

Z

zoning ordinances, 1
Zonolite, 127–128